
POWERDNS 

dnsdist

PowerDNS.COM BV

Apr 26, 2019

CONTENTS

1	dnsmdist Overview	1
1.1	Running dnsmdist	1
1.2	Questions, requests or comments?	1
2	Installing dnsmdist	3
2.1	Installing from Packages	3
2.1.1	Debian	3
2.1.2	RedHat	3
2.1.3	FreeBSD	3
2.2	Installing from Source	3
2.2.1	From tarball	4
2.2.2	From git	4
2.2.3	OS Specific Instructions	4
3	Quickstart Guide	5
3.1	Running in the Foreground	5
3.2	dnsmdist Console and Configuration	5
3.2.1	Changing Server Settings	6
3.3	Restricting Access	7
3.4	More Information	7
4	Running and Configuring dnsmdist	9
4.1	Running as unprivileged user	9
5	Packet Policies	11
5.1	Packet Actions	11
5.1.1	Examples	11
5.2	Rule Generators	12
5.3	Managing Rules	15
5.4	Matching Packets (Selectors)	19
5.4.1	Combining Rules	22
5.4.2	Convenience Functions	23
5.5	Actions	23
6	Statistics	29
6.1	acl-drops	29
6.2	cache-hits	29
6.3	cache-misses	29
6.4	cpu-sys-msec	29
6.5	cpu-user-msec	29
6.6	downstream-send-errors	30
6.7	downstream-timeouts	30
6.8	dyn-block-nmg-size	30
6.9	dyn-blocked	30
6.10	empty-queries	30

6.11	fd-usage	30
6.12	frontend-noerror	30
6.13	frontend-nxdomain	30
6.14	frontend-servfail	30
6.15	latency-avg100	30
6.16	latency-avg1000	31
6.17	latency-avg10000	31
6.18	latency-avg1000000	31
6.19	latency-slow	31
6.20	latency0-1	31
6.21	latency1-10	31
6.22	latency10-50	31
6.23	latency50-100	31
6.24	latency100-1000	31
6.25	no-policy	31
6.26	noncompliant-queries	32
6.27	noncompliant-responses	32
6.28	queries	32
6.29	rdqueries	32
6.30	real-memory-usage	32
6.31	responses	32
6.32	rule-drop	32
6.33	rule-nxdomain	32
6.34	rule-refused	32
6.35	rule-servfail	32
6.36	security-status	33
6.37	self-answered	33
6.38	servfail-responses	33
6.39	trunc-failures	33
6.40	uptime	33
7	Caching Responses	35
8	Exporting statistics via Carbon	37
8.1	Setting up a carbon export	37
8.2	Query counters	37
9	Working with the dnsmdist Console	39
10	DNS-over-TLS	41
11	DNSCrypt	43
12	Configuring Downstream Servers	45
12.1	Healthcheck	45
12.2	Source address selection	46
13	Dynamic Rule Generation	47
13.1	DynBlockRulesGroup	47
14	Guides	49
14.1	Built-in webserver	49
14.1.1	Security of the Webserver	49
14.1.2	dnsmdist API	49
14.2	Server pools	58
14.3	Loadbalancing and Server Policies	59
14.3.1	Built-in Policies	59
14.3.2	Lua server policies	60
14.3.3	ServerPolicy Objects	60

14.3.4	Functions	60
15	Advanced Topics	63
15.1	Access Control	63
15.1.1	Listening on different addresses	63
15.1.2	Modifying the ACL	64
15.2	TeeAction: copy the DNS traffic stream	64
15.3	Lua actions in rules	64
15.4	Runtime-modifiable IP address sets	65
15.5	Using EDNS Client Subnet	66
15.6	Rules for traffic exceeding QPS limits	66
15.7	eBPF Socket Filtering	67
15.8	Performance Tuning	68
15.9	SNMP support	69
15.10	AXFR, IXFR and NOTIFY	82
15.11	Running multiple instances	82
15.11.1	Using systemd	83
16	Reference Guides	85
16.1	Configuration Reference	85
16.1.1	Functions and Types	85
16.1.2	Global configuration	85
16.1.3	Servers	91
16.1.4	Pools	94
16.1.5	Client State	97
16.1.6	Status, Statistics and More	97
16.1.7	Dynamic Blocks	99
16.1.8	Other functions	102
16.2	Constants	104
16.2.1	OPCode	104
16.2.2	DNSTClass	105
16.2.3	RCode	105
16.2.4	EDNSOptionCode	105
16.2.5	DNS Packet Sections	106
16.2.6	DNSAction	106
16.2.7	DNSQType	106
16.2.8	DNSResponseAction	107
16.3	ComboAddress	107
16.4	NetmaskGroup	108
16.5	DNSName objects	108
16.5.1	Functions and methods of a DNSName	109
16.6	DNSNameSet objects	109
16.6.1	Functions and methods of a DNSNameSet	109
16.7	The DNSQuestion (dq) object	110
16.8	DNSResponse object	112
16.9	DNSHeader (dh) object	112
16.10	EDNSOptionView object	113
16.11	eBPF functions and objects	113
16.12	DNSCrypt objects and functions	115
16.12.1	Certificates	116
16.12.2	Certificate Pairs	116
16.12.3	Context	116
16.13	Protobuf Logging Reference	118
16.14	dnstap Logging Reference	120
16.15	Carbon export	121
16.16	SNMP reporting	121
16.17	Tuning related functions	121

17	Manual Pages	123
17.1	dnsdist	123
17.1.1	Synopsis	123
17.1.2	Description	123
17.1.3	Scope	123
17.1.4	Options	123
17.1.5	Bugs	124
17.1.6	Resources	124
18	Changelog	125
18.1	1.4.0-alpha2	125
18.1.1	New Features	125
18.1.2	Improvements	125
18.1.3	Bug Fixes	125
18.2	1.4.0-alpha1	125
18.2.1	New Features	125
18.2.2	Improvements	126
18.2.3	Bug Fixes	126
18.3	1.3.3	127
18.3.1	New Features	127
18.3.2	Improvements	127
18.3.3	Bug Fixes	128
18.4	1.3.2	128
18.4.1	Bug Fixes	128
18.5	1.3.1	128
18.5.1	New Features	128
18.5.2	Improvements	128
18.5.3	Bug Fixes	129
18.6	1.3.0	129
18.6.1	New Features	130
18.6.2	Improvements	130
18.6.3	Bug Fixes	131
18.6.4	Removals	131
18.7	1.2.1	131
18.7.1	New Features	131
18.7.2	Improvements	131
18.7.3	Bug Fixes	131
18.8	1.2.0	132
18.8.1	New Features	132
18.8.2	Improvements	133
18.8.3	Bug Fixes	133
18.8.4	Removals	134
18.8.5	misc	134
18.9	1.1.0	134
18.9.1	Improvements	134
18.9.2	Bug fixes	134
18.10	1.1.0-beta2	135
18.10.1	New features	135
18.10.2	Improvements	135
18.10.3	Bug fixes	135
18.11	1.1.0-beta1	136
18.11.1	New features	136
18.11.2	Improvements	136
18.11.3	Bug fixes	137
18.12	1.0.0	137
18.12.1	Improvements	137
18.12.2	Bug fixes	138
18.13	1.0.0-beta1	138

18.13.1	New features	138
18.13.2	Improvements	138
18.13.3	Bug fixes	138
18.14	1.0.0-alpha2	139
18.14.1	New features	139
18.14.2	Bug fixes	139
18.14.3	Web interface	140
18.14.4	Various documentation updates and minor cleanups:	140
18.15	1.0.0-alpha1	140
19	Upgrade Guide	141
19.1	1.3.x to 1.4.0	141
19.2	1.3.2 to 1.3.3	141
19.3	1.2.x to 1.3.x	141
19.4	1.1.0 to 1.2.0	142
20	Security Advisories	143
20.1	PowerDNS Security Advisory 2017-01 for dnsmdist: Crafted backend responses can cause a denial of service	143
20.2	PowerDNS Security Advisory 2017-02 for dnsmdist: Alteration of ACLs via API authentication bypass	143
20.3	PowerDNS Security Advisory for dnsmdist 2018-08: Record smuggling when adding ECS or XPF	144
21	Glossary	145
	HTTP Routing Table	147
	Index	149

DNSDIST OVERVIEW

dnsmist is a highly DNS-, DoS- and abuse-aware loadbalancer. Its goal in life is to route traffic to the best server, delivering top performance to legitimate users while shunting or blocking abusive traffic.

dnsmist is dynamic, its configuration language is Lua and it can be changed at runtime, and its statistics can be queried from a console-like interface or an HTTP API.

A configuration to balance DNS queries to several backend servers:

```
newServer({address="2001:4860:4860::8888", qps=1})
newServer({address="2001:4860:4860::8844", qps=1})
newServer({address="2620:0:ccc::2", qps=10})
newServer({address="2620:0:ccd::2", name="dns1", qps=10})
newServer("192.168.1.2")
setServerPolicy(firstAvailable) -- first server within its QPS limit
```

1.1 Running dnsmist

If you have not worked with dnsmist before, here are some resources to get you going:

- *Install dnsmist.*
- To get a feeling for how it works, see the *Quickstart Guide.*
- *Running and Configuring dnsmist*
- The *Packet Policies* page covers how to apply policies to traffic
- There are several *Guides* about the different features and options
- *Advanced Topics* describes some of the more advanced features
- *Reference Guides* has all the configuration and object information

1.2 Questions, requests or comments?

There are several ways to reach us:

- The [dnsmist mailing-list](#)
- [#powerdns](#) on [irc.oftc.net](#)

If you require commercial support, please see the [PowerDNS.com website](#) or email us at powerdns.support.sales@powerdns.com.

This documentation is also available as a [PDF document](#).

INSTALLING DNSDIST

dnscat only runs on UNIX-like systems and there are several ways to install dnscat. The fastest way is using packages, either from your own operating system vendor or supplied by the PowerDNS project. Building from source is also supported.

2.1 Installing from Packages

If dnscat is available in your operating system's software repositories, install it from there. However, the version of dnscat in the repositories might be an older version that might not have a feature that was added in a later version. Or you might want to be brave and try a development snapshot from the master branch. PowerDNS provides software repositories for the most popular distributions. Visit <https://repo.powerdns.com> for more information and installation instructions.

2.1.1 Debian

For Debian and its derivatives (like Ubuntu) installing the `dnscat` package should do it:

```
apt-get install -y dnscat
```

2.1.2 RedHat

For RedHat, CentOS and its derivatives, dnscat is available in [EPEL](#):

```
yum install -y epel-release  
yum install -y dnscat
```

2.1.3 FreeBSD

dnscat is also available in [FreeBSD ports](#).

2.2 Installing from Source

In order to compile dnscat, a modern compiler with C++ 2011 support (like GCC 4.8+ or clang 3.5+) and GNU make are required. dnscat depends on the following libraries:

- Boost
- Lua 5.1+ or LuaJit
- Editline (libedit)
- libsodium (optional)

- `protobuf` (optional)
- `re2` (optional)

Should **dnssdist** be run on a system with `systemd`, it is highly recommended to have the `systemd` header files (`libsystemd-dev` on Debian and `systemd-devel` on CentOS) installed to have **dnssdist** support `systemd-notify`.

2.2.1 From tarball

Release tarballs are available from the [downloads site](#), snapshot and pre-release tarballs can be found as well.

The release tarballs have detached PGP signatures, signed by on these PGP keys:

- D630 0CAB CBF4 69BB E392 E503 A208 ED4F 8AF5 8446
- FBAE 0323 821C 7706 A5CA 151B DCF5 13FA 7EED 19F3
- 1628 90D0 689D D12D D33E 4696 1C5E E990 D2E7 1575
- B76C D467 1C09 68BA A87D E61C 5E50 715B F2FF E1A7
- 16E1 2866 B773 8C73 976A 5743 6FFC 3343 9B0D 04DF

There is a PGP keyblock with these keys available on https://dnssdist.org/_static/dnssdist-keyblock.asc.

- Untar the tarball and `cd` into the source directory
- Run `./configure`
- Run `make` or `gmake` (on BSD)

2.2.2 From git

To compile from git, these additional dependencies are required:

- GNU Autoconf
- GNU Automake
- Ragel

dnssdist source code lives in the [PowerDNS git repository](#) but is independent of PowerDNS.

```
git clone https://github.com/PowerDNS/pdns.git
cd pdns/pdns/dnssdistdist
autoreconf -i
./configure
make
```

2.2.3 OS Specific Instructions

None, really.

QUICKSTART GUIDE

This guide gives an overview of dnsmdist features and operations.

3.1 Running in the Foreground

After *installing* dnsmdist, the quickest way to start experimenting is launching it on the foreground with:

```
dnsmdist -l 127.0.0.1:5300 8.8.8.8 2001:4860:4860::8888
```

This will make dnsmdist listen on IP address 127.0.0.1, port 5300 and forward all queries to the two listed IP addresses, with a sensible balancing policy.

3.2 dnsmdist Console and Configuration

Here is more complete configuration, save it to `dnsmdist.conf`:

```
newServer({address="2001:4860:4860::8888", qps=1})
newServer({address="2001:4860:4860::8844", qps=1})
newServer({address="2620:0:ccc::2", qps=10})
newServer({address="2620:0:ccd::2", name="dns1", qps=10})
newServer("192.168.1.2")
setServerPolicy(firstAvailable) -- first server within its QPS limit
```

The `newServer()` function is used to add a backend server to the configuration.

Now run dnsmdist again, reading this configuration:

```
$ dnsmdist -C dnsmdist.conf --local=0.0.0.0:5300
Marking downstream [2001:4860:4860::8888]:53 as 'up'
Marking downstream [2001:4860:4860::8844]:53 as 'up'
Marking downstream [2620:0:ccc::2]:53 as 'up'
Marking downstream [2620:0:ccd::2]:53 as 'up'
Marking downstream 192.168.1.2:53 as 'up'
Listening on 0.0.0.0:5300
>
```

You can now send queries to port 5300, and get answers:

```
$ dig -t aaaa powerdns.com @127.0.0.1 -p 5300 +short +nookie
2001:888:2000:1d::2
```

Note that dnsmdist dropped us in a prompt above, where we can get some statistics:

```
> showServers()
#   Address                               State   Qps    Qlim Ord Wt   Queries  Drops_
↪Drate  Lat Pools
0   [2001:4860:4860::8888]:53             up      0.0    1   1  1         1         0  0.
↪0      0.0
1   [2001:4860:4860::8844]:53             up      0.0    1   1  1         0         0  0.
↪0      0.0
2   [2620:0:ccc::2]:53                    up      0.0   10   1  1         0         0  0.
↪0      0.0
3   [2620:0:ccd::2]:53                    up      0.0   10   1  1         0         0  0.
↪0      0.0
4   192.168.1.2:53                        up      0.0    0   1  1         0         0  0.
↪0      0.0
All                                     0.0    1         0
```

`showServers()` is usually one of the first commands you will use when logging into the console. More advanced topics are covered in *Working with the dnsmist Console*.

Here we also see our configuration. 5 downstream servers have been configured, of which the first 4 have a QPS limit (of 1, 1, 10 and 10 queries per second, respectively).

The final server has no limit, which we can easily test:

```
$ for a in {0..1000}; do dig powerdns.com @127.0.0.1 -p 5300 +noall +nocookie > /
↪dev/null; done
```

```
> showServers()
#   Address                               State   Qps    Qlim Ord Wt   Queries  Drops_
↪Drate  Lat Pools
0   [2001:4860:4860::8888]:53             up      1.0    1   1  1         7         0  0.
↪0      1.6
1   [2001:4860:4860::8844]:53             up      1.0    1   1  1         6         0  0.
↪0      0.6
2   [2620:0:ccc::2]:53                    up     10.3   10   1  1        64         0  0.
↪0      2.4
3   [2620:0:ccd::2]:53                    up     10.3   10   1  1        63         0  0.
↪0      2.4
4   192.168.1.2:53                        up    125.8    0   1  1       671         0  0.
↪0      0.4
All                                     145.0   811         0
```

Note that the first 4 servers were all limited to near their configured QPS, and that our final server was taking up most of the traffic. No queries were dropped, and all servers remain up.

3.2.1 Changing Server Settings

The servers from `showServers()` are numbered, `getServer()` is used to get this `Server` object to manipulate it.

To force a server down, try `Server:setDown()`:

```
> getServer(0):setDown()
> showServers()
#   Address                               State   Qps    Qlim Ord Wt   Queries  Drops_
↪Drate  Lat Pools
0   [2001:4860:4860::8888]:53             DOWN    0.0    1   1  1         8         0  0.
↪0      0.0
...
```

The DOWN in all caps means it was forced down. A lower case down would've meant that dnsmist itself had concluded the server was down. Similarly, `Server:setUp()` forces a server to be up, and `Server:setAuto()` returns it to the default availability-probing.

To change the QPS for a server, use `Server:setQPS()`:

```
> getServer(0):setQPS(1000)
```

3.3 Restricting Access

By default, dnsmdist listens on 127.0.0.1 (not ::1!), port 53.

To listen on a different address, use the `-l` command line option (useful for testing in the foreground), or use `setLocal()` and `addLocal()` in the configuration file:

```
setLocal('192.0.2.53')      -- Listen on 192.0.2.53, port 53
addLocal('192.0.2.54:5300') -- Also listen on 192.0.2.54, port 5300
```

Before packets are processed they have to pass the ACL, which helpfully defaults to **RFC 1918** private IP space. This prevents us from easily becoming an open DNS resolver.

Adding network ranges to the ACL is done with the `setACL()` and `addACL()` functions:

```
setACL({'192.0.2.0/28', '2001:DB8:1::/56'}) -- Set the ACL to only allow these_
↔subnets
addACL('2001:DB8:2::/56')                -- Add this subnet to the existing ACL
```

3.4 More Information

Following this quickstart guide allowed you to set up a basic balancing dnsmdist instance. However, dnsmdist is much more powerful. See the *Guides* and/or the *Advanced Topics* sections on how to shape, shut and otherwise manipulate DNS traffic.

RUNNING AND CONFIGURING DNSDIST

`dnscatd` is meant to run as a daemon. As such, distribution native packages know how to stop/start themselves using operating system services.

It is configured with a configuration file called `dnscatd.conf`. The default path to this file is determined by the `SYSCONFDIR` variable during compilation. Most likely this path is `/etc/dnscatd`, `/etc` or `/usr/local/etc/`, `dnscatd` will tell you on startup which file it reads.

`dnscatd` is designed to (re)start almost instantly. But to prevent downtime when changing configuration, the console (see *Working with the dnscatd Console*) can be used for live configuration.

Issuing `delta()` on the console will print the changes to the configuration that have been made since startup:

```
> delta()
-- Wed Feb 22 2017 11:31:44 CET
addLocal('127.0.0.1:5301', false)
-- Wed Feb 22 2017 12:03:48 CET
addACL('2.0.0.0/8')
-- Wed Feb 22 2017 12:03:50 CET
addACL('2.0.0.0/8')
-- Wed Feb 22 2017 12:03:51 CET
addACL('2.0.0.0/8')
-- Wed Feb 22 2017 12:05:51 CET
addACL('2001:db8::1')
```

These commands can be copied to the configuration file, should they need to persist after a restart.

4.1 Running as unprivileged user

`dnscatd` can drop privileges using the `--uid` and `--gid` command line switches to ensure it does not run with root privileges. Note that `dnscatd` drops its privileges **after** parsing its startup configuration and binding its listening and initial `newServer()` sockets as user `root`. It is highly recommended to create a system user and group for `dnscatd`. Note that most packaged versions of `dnscatd` already create this user.

PACKET POLICIES

dnsmist works in essence like any other loadbalancer:

It receives packets on one or several addresses it listens on, and determines whether it will process this packet based on the *Access Control*. Should the packet be processed, dnsmist attempts to match any of the configured rules in order and when one matches, the associated action is performed.

These rule and action combinations are considered policies.

5.1 Packet Actions

Each packet can be:

- Dropped
- Turned into an answer directly
- Forwarded to a downstream server
- Modified and forwarded to a downstream and be modified back
- Be delayed

This decision can be taken at different times during the forwarding process.

5.1.1 Examples

Rules for traffic exceeding QPS limits

Traffic that exceeds a QPS limit, in total or per IP (subnet) can be matched by a rule.

For example:

```
addAction(MaxQPSIPRule(5, 32, 48), DelayAction(100))
```

This measures traffic per IPv4 address and per /48 of IPv6, and if traffic for such an address (range) exceeds 5 qps, it gets delayed by 100ms.

As another example:

```
addAction(MaxQPSIPRule(5), NoRecurseAction())
```

This strips the Recursion Desired (RD) bit from any traffic per IPv4 or IPv6 /64 that exceeds 5 qps. This means any those traffic bins is allowed to make a recursor do 'work' for only 5 qps.

If this is not enough, try:

```
addAction(MaxQPSIPRule(5), DropAction())
```

or:

```
addAction(MaxQPSIPRule(5), TCAction())
```

This will respectively drop traffic exceeding that 5 QPS limit per IP or range, or return it with TC=1, forcing clients to fall back to TCP.

To turn this per IP or range limit into a global limit, use `NotRule(MaxQPSRule(5000))` instead of `MaxQPSIPRule()`.

Regular Expressions

`RegexRule()` matches a regular expression on the query name, and it works like this:

```
addAction(RegexRule("[0-9]{5,}"), DelayAction(750)) -- milliseconds
addAction(RegexRule("[0-9]{4,}\\\\.example$"), DropAction())
```

This delays any query for a domain name with 5 or more consecutive digits in it. The second rule drops anything with more than 4 consecutive digits within a .example domain.

Note that the query name is presented without a trailing dot to the regex. The regex is applied case insensitively.

Alternatively, if compiled in, `RE2Rule()` provides similar functionality, but against `libre2`.

5.2 Rule Generators

`dnsmdist` contains several functions that make it easier to add actions and rules.

`addAnyTCRule()`

Deprecated since version 1.2.0.

Set the TC-bit (truncate) on ANY queries received over UDP, forcing a retry over TCP. This function is deprecated as of 1.2.0 and will be removed in 1.3.0. This is equivalent to doing:

```
addAction(AndRule({QTypeRule(DNSQType.ANY), TCPRule(false)}), TCAction())
```

Changed in version 1.4.0: Before 1.4.0, the QTypes were in the `dnsmdist` namespace. Use `dnsmdist.ANY` in these versions.

`addDelay(DNSRule, delay)`

Deprecated since version 1.2.0.

Delay the query for `delay` milliseconds before sending to a backend. This function is deprecated as of 1.2.0 and will be removed in 1.3.0, please use instead:

```
addAction(DNSRule, DelayAction(delay))
```

Parameters

- **DNSRule** – The DNSRule to match traffic
- **delay** (*int*) – The delay time in milliseconds.

`addDisableValidationRule(DNSRule)`

Deprecated since version 1.2.0.

Set the CD (Checking Disabled) flag to 1 for all queries matching the DNSRule. This function is deprecated as of 1.2.0 and will be removed in 1.3.0. Please use the `DisableValidationAction()` action instead.

`addDomainBlock(domain)`

Deprecated since version 1.2.0.

Drop all queries for `domain` and all names below it. Deprecated as of 1.2.0 and will be removed in 1.3.0, please use instead:

```
addAction(domain, DropAction())
```

Parameters `domain` (*string*) – The domain name to block

```
addDomainSpoof (domain, IPv4[, IPv6])
```

```
addDomainSpoof (domain, {IP[,...]})
```

Deprecated since version 1.2.0.

Generate answers for A/AAAA/ANY queries. This function is deprecated as of 1.2.0 and will be removed in 1.3.0, please use:

```
addAction(domain, SpoofAction({IP[...]}))
```

or:

```
addAction(domain, SpoofAction(IPv4[, IPv6]))
```

Parameters

- **domain** (*string*) – Domain name to spoof for
- **IPv4** (*string*) – IPv4 address to spoof in the reply
- **IPv6** (*string*) – IPv6 address to spoof in the reply
- **IP** (*string*) – IP address to spoof in the reply

```
addDomainCNAMESpoof (domain, cname)
```

Deprecated since version 1.2.0.

Generate CNAME answers for queries. This function is deprecated as of 1.2.0 and will be removed in 1.3.0, in favor of using:

```
addAction(domain, SpoofCNAMEAction(cname))
```

Parameters

- **domain** (*string*) – Domain name to spoof for
- **cname** (*string*) – Domain name to add CNAME to

```
addLuaAction (DNSRule, function[, options])
```

Changed in version 1.3.0: Added the optional parameter `options`.

Changed in version 1.3.0: The second argument returned by the `function` can be omitted. For earlier releases, simply return an empty string.

Deprecated since version 1.4.0: Removed in 1.4.0, use `LuaAction()` with `addAction()` instead.

Invoke a Lua function that accepts a `DNSQuestion`. This function works similar to using `LuaAction()`. The `function` should return both a `DNSAction` and its argument `rule`. The `rule` is used as an argument of the following `DNSAction`: `DNSAction.Spoof`, `DNSAction.Pool` and `DNSAction.Delay`. If the Lua code fails, `ServFail` is returned.

Parameters

- **DNSRule** – match queries based on this rule
- **function** (*string*) – the name of a Lua function
- **options** (*table*) – A table with key: value pairs with options.

Options:

- `uuid`: string - UUID to assign to the new rule. By default a random UUID is generated for each rule.

```

function luarule(dq)
  if(dq.qtype==dnsmdist.NAPTR)
  then
    return DNSAction.Pool, "abuse" -- send to abuse pool
  else
    return DNSAction.None, "" -- no action
    -- return DNSAction.None -- as of dnsmdist version 1.3.0
  end
end

addLuaAction(AllRule(), luarule)

```

addLuaResponseAction (*DNSRule*, *function* [, *options*])

Changed in version 1.3.0: Added the optional parameter *options*.

Changed in version 1.3.0: The second argument returned by the function can be omitted. For earlier releases, simply return an empty string.

Deprecated since version 1.4.0: Removed in 1.4.0, use *LuaResponseAction()* with *addResponseAction()* instead.

Invoke a Lua function that accepts a *DNSResponse*. This function works similar to using *LuaResponseAction()*. The function should return both a *DNSResponseAction* and its argument *rule*. The *rule* is used as an argument of the *DNSResponseAction.Delay*. If the Lua code fails, ServFail is returned.

Parameters

- **DNSRule** – match queries based on this rule
- **function** (*string*) – the name of a Lua function
- **options** (*table*) – A table with key: value pairs with options.

Options:

- **uuid**: *string* - UUID to assign to the new rule. By default a random UUID is generated for each rule.

addNoRecurseRule (*DNSRule*)

Deprecated since version 1.2.0.

Clear the RD flag for all queries matching the rule. This function is deprecated as of 1.2.0 and will be removed in 1.3.0, please use:

```
addAction(DNSRule, NoRecurseAction())
```

Parameters **DNSRule** – match queries based on this rule

addPoolRule (*DNSRule*, *pool*)

Deprecated since version 1.2.0.

Send queries matching the first argument to the pool *pool*. e.g.:

```
addPoolRule("example.com", "myPool")
```

This function is deprecated as of 1.2.0 and will be removed in 1.3.0, this is equivalent to:

```
addAction("example.com", PoolAction("myPool"))
```

Parameters

- **DNSRule** – match queries based on this rule
- **pool** (*string*) – The name of the pool to send the queries to

addQPSLimit (*DNSRule*, *limit*)

Deprecated since version 1.2.0.

Limit queries matching the *DNSRule* to *limit* queries per second. All queries over the limit are dropped. This function is deprecated as of 1.2.0 and will be removed in 1.3.0, please use:

```
addAction(DNSRule, QPSAction(limit))
```

Parameters

- **DNSRule** – match queries based on this rule
- **limit** (*int*) – QPS limit for this rule

addQPSPoolRule (*DNSRule*, *limit*, *pool*)

Deprecated since version 1.2.0.

Send at most *limit* queries/s for this pool, letting the subsequent rules apply otherwise. This function is deprecated as of 1.2.0 and will be removed in 1.3.0, as it is only a convenience function for the following syntax:

```
addAction("192.0.2.0/24", QPSPoolAction(15, "myPool"))
```

Parameters

- **DNSRule** – match queries based on this rule
- **limit** (*int*) – QPS limit for this rule
- **pool** (*string*) – The name of the pool to send the queries to

5.3 Managing Rules

Active Rules can be shown with *showRules()* and removed with *rmRule()*:

```
> addAction("h4xorbooter.xyz.", QPSAction(10))
> addAction({"130.161.0.0/16", "145.14.0.0/16"}, QPSAction(20))
> addAction({"nl.", "be."}, QPSAction(1))
> showRules()
#      Matches Rule                                     Action
0      0 h4xorbooter.xyz.                               qps limit to 10
1      0 130.161.0.0/16, 145.14.0.0/16                 qps limit to 20
2      0 nl., be.                                       qps limit to 1
```

For Rules related to the incoming query:

addAction (*DNSRule*, *action*[, *options*])

Changed in version 1.3.0: Added the optional parameter *options*.

Add a Rule and Action to the existing rules.

Parameters

- **rule** (*DNSRule*) – A *DNSRule*, e.g. an *AllRule()* or a compounded bunch of rules using e.g. *AndRule()*
- **action** – The action to take
- **options** (*table*) – A table with key: value pairs with options.

Options:

- **uuid**: string - UUID to assign to the new rule. By default a random UUID is generated for each rule.

clearRules ()

Remove all current rules.

getAction (*n*) → Action

Returns the Action associated with rule *n*.

Parameters *n* (*int*) – The rule number

mvRule (*from*, *to*)

Move rule *from* to a position where it is in front of *to*. *to* can be one larger than the largest rule, in which case the rule will be moved to the last position.

Parameters

- **from** (*int*) – Rule number to move
- **to** (*int*) – Location to move the Rule to

newRuleAction (*rule*, *action* [, *options*])

Changed in version 1.3.0: Added the optional parameter *options*.

Return a pair of DNS Rule and DNS Action, to be used with *setRules* ().

Parameters

- **rule** (*Rule*) – A Rule
- **action** (*Action*) – The *Action* to apply to the matched traffic
- **options** (*table*) – A table with key: value pairs with options.

Options:

- **uuid**: string - UUID to assign to the new rule. By default a random UUID is generated for each rule.

setRules (*rules*)

Replace the current rules with the supplied list of pairs of DNS Rules and DNS Actions (see *newRuleAction* ())

Parameters *rules* ([*RuleAction*]) – A list of RuleActions

showRules ([*options*])

Changed in version 1.3.0: *options* optional parameter added

Show all defined rules for queries, optionally displaying their UUIDs.

Parameters *options* (*table*) – A table with key: value pairs with display options.

Options:

- **showUUIDs=false**: bool - Whether to display the UUIDs, defaults to false.
- **truncateRuleWidth=-1**: int - Truncate rules output to *truncateRuleWidth* size. Defaults to -1 to display the full rule.

topRule ()

Move the last rule to the first position.

rmRule (*id*)

Changed in version 1.3.0: *id* can now be an UUID.

Remove rule *id*.

Parameters *id* (*int*) – The UUID of the rule to remove if *id* is an UUID, its position otherwise

For Rules related to responses:

addResponseAction (*DNSRule*, *action* [, *options*])

Changed in version 1.3.0: Added the optional parameter *options*.

Add a Rule and Action for responses to the existing rules.

Parameters

- **DNSRule** – A DNSRule, e.g. an *AllRule()* or a compounded bunch of rules using e.g. *AndRule()*
- **action** – The action to take
- **options** (*table*) – A table with key: value pairs with options.

Options:

- **uuid**: string - UUID to assign to the new rule. By default a random UUID is generated for each rule.

mvResponseRule (*from, to*)

Move response rule *from* to a position where it is in front of *to*. *to* can be one larger than the largest rule, in which case the rule will be moved to the last position.

Parameters

- **from** (*int*) – Rule number to move
- **to** (*int*) – Location to move the Rule to

rmResponseRule (*id*)

Changed in version 1.3.0: *id* can now be an UUID.

Remove response rule *id*.

Parameters **id** (*int*) – The UUID of the rule to remove if *id* is an UUID, its position otherwise

showResponseRules ([*options*])

Changed in version 1.3.0: *options* optional parameter added

Show all defined response rules, optionally displaying their UUIDs.

Parameters **options** (*table*) – A table with key: value pairs with display options.

Options:

- **showUUIDs=false**: bool - Whether to display the UUIDs, defaults to false.
- **truncateRuleWidth=-1**: int - Truncate rules output to *truncateRuleWidth* size. Defaults to -1 to display the full rule.

topResponseRule ()

Move the last response rule to the first position.

Functions for manipulating Cache Hit Response Rules:

addCacheHitResponseAction (*DNSRule, action*[, *options*])

New in version 1.2.0.

Changed in version 1.3.0: Added the optional parameter *options*.

Add a Rule and ResponseAction for Cache Hits to the existing rules.

Parameters

- **DNSRule** – A DNSRule, e.g. an *AllRule()* or a compounded bunch of rules using e.g. *AndRule()*
- **action** – The action to take
- **options** (*table*) – A table with key: value pairs with options.

Options:

- **uuid**: string - UUID to assign to the new rule. By default a random UUID is generated for each rule.

mvCacheHitResponseRule (*from, to*)

New in version 1.2.0.

Move cache hit response rule *from* to a position where it is in front of *to*. *to* can be one larger than the largest rule, in which case the rule will be moved to the last position.

Parameters

- **from** (*int*) – Rule number to move
- **to** (*int*) – Location to move the Rule to

rmCacheHitResponseRule (*id*)

New in version 1.2.0.

Changed in version 1.3.0: *id* can now be an UUID.

Parameters **id** (*int*) – The UUID of the rule to remove if *id* is an UUID, its position otherwise

showCacheHitResponseRules ([*options*])

New in version 1.2.0.

Changed in version 1.3.0: *options* optional parameter added

Show all defined cache hit response rules, optionally displaying their UUIDs.

Parameters **options** (*table*) – A table with key: value pairs with display options.

Options:

- **showUUIDs=false**: *bool* - Whether to display the UUIDs, defaults to false.
- **truncateRuleWidth=-1**: *int* - Truncate rules output to *truncateRuleWidth* size. Defaults to -1 to display the full rule.

topCacheHitResponseRule ()

New in version 1.2.0.

Move the last cache hit response rule to the first position.

Functions for manipulating Self-Answered Response Rules:

addSelfAnsweredResponseAction (*DNSRule*, *action*[, *options*])

New in version 1.3.0.

Add a Rule and Action for Self-Answered queries to the existing rules.

Parameters

- **DNSRule** – A *DNSRule*, e.g. an *AllRule* () or a compounded bunch of rules using e.g. *AndRule* ()
- **action** – The action to take

mvSelfAnsweredResponseRule (*from*, *to*)

New in version 1.3.0.

Move self answered response rule *from* to a position where it is in front of *to*. *to* can be one larger than the largest rule, in which case the rule will be moved to the last position.

Parameters

- **from** (*int*) – Rule number to move
- **to** (*int*) – Location to move the Rule to

rmSelfAnsweredResponseRule (*id*)

New in version 1.3.0.

Remove self answered response rule *id*.

Parameters **id** (*int*) – The UUID of the rule to remove if *id* is an UUID, its position otherwise

showSelfAnsweredResponseRules ([*options*])

New in version 1.3.0.

Show all defined self answered response rules, optionally displaying their UUIDs.

Parameters `options` (*table*) – A table with key: value pairs with display options.

Options:

- `showUUIDs=false`: `bool` - Whether to display the UUIDs, defaults to `false`.
- `truncateRuleWidth=-1`: `int` - Truncate rules output to `truncateRuleWidth` size. Defaults to `-1` to display the full rule.

topSelfAnsweredResponseRule ()

New in version 1.3.0.

Move the last self answered response rule to the first position.

Function for pool related rules

PoolAvailableRule (*poolname*)

New in version 1.3.3.

Check whether a pool has any servers available to handle queries

Parameters `poolname` (*string*) – Pool to check

5.4 Matching Packets (Selectors)

Packets can be matched by selectors, called a `DNSRule`. These `DNSRules` be one of the following items:

- A string that is either a domain name or netmask
- A list of strings that are either domain names or netmasks
- A `DNSName`
- A list of `DNSNames`
- A (compounded) `Rule`

New in version 1.2.0: A `DNSRule` can also be a `DNSName` or a list of these

AllRule ()

Matches all traffic

DNSSECRule ()

Matches queries with the DO flag set

DSTPortRule (*port*)

Matches questions received to the destination port.

Parameters `port` (*int*) – Match destination port.

EDNSOptionRule (*optcode*)

New in version 1.4.0.

Matches queries or responses with the specified EDNS option present. `optcode` is specified as an integer, or a constant such as `EDNSOptionCode.ECS`.

EDNSVersionRule (*version*)

New in version 1.4.0.

Matches queries or responses with an OPT record whose EDNS version is greater than the specified EDNS version.

Parameters `version` (*int*) – The EDNS version to match on

ERCodeRule (*rcode*)

Matches queries or responses with the specified `rcode`. `rcode` can be specified as an integer or as one of the built-in `RCode`. The full 16bit RCode will be matched. If no EDNS OPT RR is present, the upper 12 bits are treated as 0.

Parameters `rcode` (*int*) – The RCODE to match on

MaxQPSIPRule (*qps* [, *v4Mask* [, *v6Mask* [, *burst* [, *expiration* [, *cleanupDelay* [, *scanFraction*]]]]]])
 .. versionchanged:: 1.3.1

Added the optional parameters `expiration`, `cleanupDelay` and `scanFraction`.

Matches traffic for a subnet specified by `v4Mask` or `v6Mask` exceeding `qps` queries per second up to `burst` allowed. This rule keeps track of QPS by netmask or source IP. This state is cleaned up regularly if `cleanupDelay` is greater than zero, removing existing netmasks or IP addresses that have not been seen in the last `expiration` seconds.

Parameters

- **qps** (*int*) – The number of queries per second allowed, above this number traffic is matched
- **v4Mask** (*int*) – The IPv4 netmask to match on. Default is 32 (the whole address)
- **v6Mask** (*int*) – The IPv6 netmask to match on. Default is 64
- **burst** (*int*) – The number of burstable queries per second allowed. Default is same as `qps`
- **expiration** (*int*) – How long to keep netmask or IP addresses after they have last been seen, in seconds. Default is 300
- **cleanupDelay** (*int*) – The number of seconds between two cleanups. Default is 60
- **scanFraction** (*int*) – The maximum fraction of the store to scan for expired entries, for example 5 would scan at most 20% of it. Default is 10 so 10%

MaxQPSRule (*qps*)

Matches traffic **not** exceeding this `qps` limit. If e.g. this is set to 50, starting at the 51st query of the current second traffic stops being matched. This can be used to enforce a global QPS limit.

Parameters `qps` (*int*) – The number of queries per second allowed, above this number the traffic is **not** matched anymore

NetmaskGroupRule (*nmg* [, *src*])

Matches traffic from/to the network range specified in `nmg`.

Set the `src` parameter to false to match `nmg` against destination address instead of source address. This can be used to differentiate between clients

Parameters

- **nmg** (*NetMaskGroup*) – The NetMaskGroup to match on
- **src** (*bool*) – Whether to match source or destination address of the packet. Defaults to true (matches source)

OpcodeRule (*code*)

Matches queries with opcode `code`. `code` can be directly specified as an integer, or one of the *built-in DNSOpCodes*.

Parameters `code` (*int*) – The opcode to match

ProbaRule (*probability*)

New in version 1.3.0.

Matches queries with a given probability. 1.0 means “always”

Parameters `probability` (*double*) – Probability of a match

QClassRule (*qclass*)

Matches queries with the specified `qclass`. `class` can be specified as an integer or as one of the built-in DNSQClass.

Parameters `qclass` (*int*) – The Query Class to match on

QNameRule (*qname*)

New in version 1.2.0: Matches queries with the specified *qname* exactly.

param string qname Qname to match

QNameSetRule (*set*)

Matches if the set contains exact *qname*.

To match subdomain names, see *SuffixMatchNodeRule* ().

param DNSNameSet set Set with qnames.

QNameLabelsCountRule (*min*, *max*)

Matches if the *qname* has less than *min* or more than *max* labels.

Parameters

- **min** (*int*) – Minimum number of labels
- **max** (*int*) – Maximum number of labels

QNameWireLengthRule (*min*, *max*)

Matches if the *qname*'s length on the wire is less than *min* or more than *max* bytes.

Parameters

- **min** (*int*) – Minimum number of bytes
- **max** (*int*) – Maximum number of bytes

QTypeRule (*qtype*)

Matches queries with the specified *qtype* *qtype* may be specified as an integer or as one of the built-in QTypes. For instance *dnsmist.A*, *dnsmist.TXT* and *dnsmist.ANY*.

Parameters qtype (*int*) – The QType to match on

RCODERule (*rcode*)

Matches queries or responses with the specified *rcode*. *rcode* can be specified as an integer or as one of the built-in *RCODE*. Only the non-extended *RCODE* is matched (lower 4bits).

Parameters rcode (*int*) – The *RCODE* to match on

RDRule ()

New in version 1.2.0.

Matches queries with the RD flag set.

RegexRule (*regex*)

Matches the query name against the *regex*.

```
addAction(RegexRule("[0-9]{5,}"), DelayAction(750)) -- milliseconds
addAction(RegexRule("[0-9]{4,}\\..example$"), DropAction())
```

This delays any query for a domain name with 5 or more consecutive digits in it. The second rule drops anything with more than 4 consecutive digits within a *.EXAMPLE* domain.

Note that the query name is presented without a trailing dot to the *regex*. The *regex* is applied case insensitively.

Parameters regex (*string*) – A regular expression to match the traffic on

RecordsCountRule (*section*, *minCount*, *maxCount*)

Matches if there is at least *minCount* and at most *maxCount* records in the section *section*. *section* can be specified as an integer or as a *DNS Packet Sections*.

Parameters

- **section** (*int*) – The section to match on
- **minCount** (*int*) – The minimum number of entries

- **maxCount** (*int*) – The maximum number of entries

RecordsTypeCountRule (*section, qtype, minCount, maxCount*)

Matches if there is at least `minCount` and at most `maxCount` records of type `qtype` in the section `section`. `section` can be specified as an integer or as a ref:`DNSSection`. `qtype` may be specified as an integer or as one of the *built-in QTypes*, for instance `DNSQType.A` or `DNSQType.TXT`.

Parameters

- **section** (*int*) – The section to match on
- **qtype** (*int*) – The QTYPE to match on
- **minCount** (*int*) – The minimum number of entries
- **maxCount** (*int*) – The maximum number of entries

RE2Rule (*regex*)

Matches the query name against the supplied regex using the RE2 engine.

For an example of usage, see *RegexRule()*.

Note Only available when dnsmdist was built with libre2 support.

Parameters **regex** (*str*) – The regular expression to match the QNAME.

SuffixMatchNodeRule (*smn[, quiet]*)

Matches based on a group of domain suffixes for rapid testing of membership. Pass true as second parameter to prevent listing of all domains matched.

To match domain names exactly, see *QNameSetRule()*.

Parameters

- **smb** (*SuffixMatchNode*) – The SuffixMatchNode to match on
- **quiet** (*bool*) – Do not return the list of matched domains. Default is false.

TagRule (*name[, value]*)

New in version 1.3.0.

Matches question or answer with a tag named `name` set. If `value` is specified, the existing tag value should match too.

Parameters

- **name** (*bool*) – The name of the tag that has to be set
- **value** (*bool*) – If set, the value the tag has to be set to. Default is unset

TCPRule (*[tcp]*)

Matches question received over TCP if `tcp` is true, over UDP otherwise.

Parameters **tcp** (*bool*) – Match TCP traffic. Default is true.

TrailingDataRule ()

Matches if the query has trailing data.

5.4.1 Combining Rules

AndRule (*selectors*)

Matches traffic if all `selectors` match.

Parameters **selectors** (*{Rule}*) – A table of Rules

NotRule (*selector*)

Matches the traffic if the `selector` rule does not match;

Parameters **selector** (*Rule*) – A Rule

OrRule (*selectors*)

Matches the traffic if one or more of the the *selectors* Rules does match.

Parameters *selector* (*{Rule}*) – A table of Rules

5.4.2 Convenience Functions

makeRule (*rule*)

Make a *NetmaskGroupRule*() or a *SuffixMatchNodeRule*(), depending on it is called. `makeRule("0.0.0.0/0")` will for example match all IPv4 traffic, `makeRule({"be", "nl", "lu"})` will match all Benelux DNS traffic.

Parameters *rule* (*string*) – A string to convert to a rule.

5.5 Actions

Matching Packets (Selectors) need to be combined with an action for them to actually do something with the matched packets. Some actions allow further processing of rules, this is noted in their description. The following actions exist.

AllowAction ()

Let these packets go through.

AllowResponseAction ()

Let these packets go through.

DelayAction (*milliseconds*)

Delay the response by the specified amount of milliseconds (UDP-only). Subsequent rules are processed after this rule.

Parameters *milliseconds* (*int*) – The amount of milliseconds to delay the response

DelayResponseAction (*milliseconds*)

Delay the response by the specified amount of milliseconds (UDP-only). Subsequent rules are processed after this rule.

Parameters *milliseconds* (*int*) – The amount of milliseconds to delay the response

DisableECSAction ()

Disable the sending of ECS to the backend. Subsequent rules are processed after this rule.

DisableValidationAction ()

Set the CD bit in the query and let it go through.

DnstapLogAction (*identity*, *logger* [, *alterFunction*])

New in version 1.3.0.

Send the the current query to a remote logger as a *dnstap* message. *alterFunction* is a callback, receiving a *DNSQuestion* and a *DnstapMessage*, that can be used to modify the message.

Parameters

- **identity** (*string*) – Server identity to store in the dnstap message
- **logger** – The *FrameStreamLogger* or *RemoteLogger* object to write to
- **alterFunction** – A Lua function to alter the message before sending

DnstapLogResponseAction (*identity*, *logger* [, *alterFunction*])

New in version 1.3.0.

Send the the current response to a remote logger as a *dnstap* message. *alterFunction* is a callback, receiving a *DNSQuestion* and a *DnstapMessage*, that can be used to modify the message.

Parameters

- **identity** (*string*) – Server identity to store in the dnstap message
- **logger** – The *FrameStreamLogger* or *RemoteLogger* object to write to
- **alterFunction** – A Lua function to alter the message before sending

DropAction ()

Drop the packet.

DropResponseAction ()

Drop the packet.

ECSOverrideAction (*override*)

Whether an existing EDNS Client Subnet value should be overridden (true) or not (false). Subsequent rules are processed after this rule.

Parameters **override** (*bool*) – Whether or not to override ECS value

ECSPrefixLengthAction (*v4, v6*)

Set the ECS prefix length. Subsequent rules are processed after this rule.

Parameters

- **v4** (*int*) – The IPv4 netmask length
- **v6** (*int*) – The IPv6 netmask length

ERCodeAction (*rcode*)

New in version 1.4.0.

Reply immediately by turning the query into a response with the specified EDNS extended *rcode*. *rcode* can be specified as an integer or as one of the built-in *RCode*.

Parameters **rcode** (*int*) – The extended RCODE to respond with.

LogAction (*[filename[, binary[, append[, buffered]]]]*)

Log a line for each query, to the specified *file* if any, to the console (require verbose) otherwise. When logging to a file, the *binary* optional parameter specifies whether we log in binary form (default) or in textual form. The *append* optional parameter specifies whether we open the file for appending or truncate each time (default). The *buffered* optional parameter specifies whether writes to the file are buffered (default) or not. Subsequent rules are processed after this rule.

Parameters

- **filename** (*string*) – File to log to. Set to an empty string to log to the normal stdout log, this only works when *-v* is set on the command line.
- **binary** (*bool*) – Do binary logging. Default true
- **append** (*bool*) – Append to the log. Default false
- **buffered** (*bool*) – Use buffered I/O. default true

LuaAction (*function*)

Invoke a Lua function that accepts a *DNSQuestion*.

The function should return a *DNSAction*. If the Lua code fails, ServFail is returned.

Parameters **function** (*string*) – the name of a Lua function

LuaResponseAction (*function*)

Invoke a Lua function that accepts a *DNSResponse*.

The function should return a *DNSResponseAction*. If the Lua code fails, ServFail is returned.

Parameters **function** (*string*) – the name of a Lua function

MacAddrAction (*option*)

Add the source MAC address to the query as EDNS0 option *option*. This action is currently only supported on Linux. Subsequent rules are processed after this rule.

Parameters **option** (*int*) – The EDNS0 option number

NoneAction ()

Does nothing. Subsequent rules are processed after this rule.

NoRecurseAction ()

Strip RD bit from the question, let it go through. Subsequent rules are processed after this rule.

PoolAction (*poolname*)

Send the packet into the specified pool.

Parameters *poolname* (*string*) – The name of the pool

QPSAction (*maxqps*)

Drop a packet if it does exceed the *maxqps* queries per second limits. Letting the subsequent rules apply otherwise.

Parameters *maxqps* (*int*) – The QPS limit

QPSPoolAction (*maxqps*, *poolname*)

Send the packet into the specified pool only if it does not exceed the *maxqps* queries per second limits. Letting the subsequent rules apply otherwise.

Parameters

- **maxqps** (*int*) – The QPS limit for that pool
- **poolname** (*string*) – The name of the pool

RCodeAction (*rcode*)

Reply immediately by turning the query into a response with the specified *rcode*. *rcode* can be specified as an integer or as one of the built-in *RCode*.

Parameters *rcode* (*int*) – The RCODE to respond with.

RemoteLogAction (*remoteLogger* [, *alterFunction* [, *options*]])

Changed in version 1.3.0: *options* optional parameter added.

Changed in version 1.4.0: *ipEncryptKey* optional key added to the options table.

Send the content of this query to a remote logger via Protocol Buffer. *alterFunction* is a callback, receiving a *DNSQuestion* and a *DNSDistProtoBufMessage*, that can be used to modify the Protocol Buffer content, for example for anonymization purposes

Parameters

- **remoteLogger** (*string*) – The *remoteLogger* object to write to
- **alterFunction** (*string*) – Name of a function to modify the contents of the logs before sending
- **options** (*table*) – A table with key: value pairs.

Options:

- *serverID=""*: str - Set the Server Identity field.
- *ipEncryptKey=""*: str - A key, that can be generated via the *makeIPCipherKey* function, to encrypt the IP address of the requestor for anonymization purposes. The encryption is done using *ipcrypt* for IPv4 and a 128-bit AES ECB operation for IPv6.

RemoteLogResponseAction (*remoteLogger* [, *alterFunction* [, *includeCNAME* [, *options*]]])

Changed in version 1.3.0: *options* optional parameter added.

Changed in version 1.4.0: *ipEncryptKey* optional key added to the options table.

Send the content of this response to a remote logger via Protocol Buffer. *alterFunction* is the same callback that receiving a *DNSQuestion* and a *DNSDistProtoBufMessage*, that can be used to modify the Protocol Buffer content, for example for anonymization purposes *includeCNAME* indicates whether CNAME records inside the response should be parsed and exported. The default is to only exports A and AAAA records

Parameters

- **remoteLogger** (*string*) – The *remoteLogger* object to write to
- **alterFunction** (*string*) – Name of a function to modify the contents of the logs before sending
- **includeCNAME** (*bool*) – Whether or not to parse and export CNAMEs. Default false
- **options** (*table*) – A table with key: value pairs.

Options:

- `serverID=""`: str - Set the Server Identity field.
- `ipEncryptKey=""`: str - A key, that can be generated via the `makeIPCipherKey` function, to encrypt the IP address of the requestor for anonymization purposes. The encryption is done using `ipcrypt` for IPv4 and a 128-bit AES ECB operation for IPv6.

SetECSAction (*v4*[, *v6*])

New in version 1.3.1.

Set the ECS prefix and prefix length sent to backends to an arbitrary value. If both IPv4 and IPv6 masks are supplied the IPv4 one will be used for IPv4 clients and the IPv6 one for IPv6 clients. Otherwise the first mask is used for both, and can actually be an IPv6 mask. Subsequent rules are processed after this rule.

Parameters

- **v4** (*string*) – The IPv4 netmask, for example “192.0.2.1/32”
- **v6** (*string*) – The IPv6 netmask, if any

SkipCacheAction ()

Don’t lookup the cache for this query, don’t store the answer.

SNMPTrapAction ([*message*])

Send an SNMP trap, adding the optional *message* string as the query description. Subsequent rules are processed after this rule.

Parameters **message** (*string*) – The message to include

SNMPTrapResponseAction ([*message*])

Send an SNMP trap, adding the optional *message* string as the query description. Subsequent rules are processed after this rule.

Parameters **message** (*string*) – The message to include

SpoofAction (*ip*[, *ip*[...]])

SpoofAction (*ips*)

Forge a response with the specified IPv4 (for an A query) or IPv6 (for an AAAA) addresses. If you specify multiple addresses, all that match the query type (A, AAAA or ANY) will get spoofed in.

Parameters

- **ip** (*string*) – An IPv4 and/or IPv6 address to spoof
- **ips** (*{string}*) – A table of IPv4 and/or IPv6 addresses to spoof

SpoofCNAMEAction (*cname*)

Forge a response with the specified CNAME value.

Parameters **cname** (*string*) – The name to respond with

TagAction (*name*, *value*)

New in version 1.3.0.

Associate a tag named *name* with a value of *value* to this query, that will be passed on to the response.

Parameters

- **name** (*string*) – The name of the tag to set
- **cname** (*string*) – The value of the tag

TagResponseAction (*name*, *value*)

New in version 1.3.0.

Associate a tag named *name* with a value of *value* to this response.

Parameters

- **name** (*string*) – The name of the tag to set
- **cname** (*string*) – The value of the tag

TCAction ()

Create answer to query with TC and RD bits set, to force the client to TCP.

TeeAction (*remote* [, *addECS*])

Send copy of query to *remote*, keep stats on responses. If *addECS* is set to true, EDNS Client Subnet information will be added to the query.

Parameters

- **remote** (*string*) – An IP:PORT combination to send the copied queries to
- **addECS** (*bool*) – Whether or not to add ECS information. Default false

TempFailureCacheTTLAction (*tll*)

Set the cache TTL to use for ServFail and Refused replies. TTL is not applied for successful replies.

Parameters **tll** (*int*) – Cache TTL for temporary failure replies

STATISTICS

dnsmasq keeps statistics on the queries it receives and sends out. They can be accessed in different ways:

- via the console (see *Working with the dnsmasq Console*), using `dumpStats()` for the general ones, `showServers()` for the ones related to the backends, `showBinds()` for the frontends, `getPool("pool name"):getCache():printStats()` for the ones related to a specific cache and so on
- via the internal webserver (see *Built-in webserver*)
- via Carbon / Graphite / Metronome export (see *Exporting statistics via Carbon*)
- via SNMP (see *SNMP support*)

To make sense of the statistics, the following relation should hold:

$$\text{queries} - \text{noncompliant-queries} = \text{responses} - \text{noncompliant-responses} + \text{cache-hits} + \text{downstream-timeouts} + \text{self-answered} + \text{no-policy} + \text{rule-drop}$$

Note that packets dropped by eBPF (see *eBPF Socket Filtering*) are accounted for in the eBPF statistics, and do not show up in the metrics described on this page.

6.1 acl-drops

The number of packets (or TCP messages) dropped because of the *ACL*. If a packet or message is dropped, it is not counted in the *queries* statistic.

6.2 cache-hits

Number of times a response was sent using data found in the *packet cache*.

6.3 cache-misses

Number of times an answer was not found in the *packet cache*. Only counted if a packet cache was setup for the selected pool.

6.4 cpu-sys-msec

Milliseconds spent by **dnsmasq** in the “system” state.

6.5 cpu-user-msec

Milliseconds spent by **dnsmasq** in the “user” state.

6.6 downstream-send-errors

Number of errors when sending a query to a backend.

6.7 downstream-timeouts

Number of queries not answer in time by a backend.

6.8 dyn-block-nmg-size

Number of dynamic blocks entries.

6.9 dyn-blocked

Number of queries dropped because of a dynamic block.

6.10 empty-queries

Number of empty queries received from clients. Every empty-query is also counted as a *query*.

6.11 fd-usage

Number of currently used file descriptors.

6.12 frontend-noerror

Number of NoError answers sent to clients.

6.13 frontend-nxdomain

Number of NXDomain answers sent to clients.

6.14 frontend-servfail

Number of ServFail answers sent to clients.

6.15 latency-avg100

Average response latency in microseconds of the last 100 packets

6.16 latency-avg1000

Average response latency in microseconds of the last 1000 packets.

6.17 latency-avg10000

Average response latency in microseconds of the last 10000 packets.

6.18 latency-avg1000000

Average response latency in microseconds of the last 1000000 packets.

6.19 latency-slow

Number of queries answered in more than 1 second.

6.20 latency0-1

Number of queries answered in less than 1 ms.

6.21 latency1-10

Number of queries answered in 1-10 ms.

6.22 latency10-50

Number of queries answered in 10-50 ms.

6.23 latency50-100

Number of queries answered in 50-100 ms.

6.24 latency100-1000

Number of queries answered in 100-1000 ms.

6.25 no-policy

Number of queries dropped because no server was available.

6.26 noncompliant-queries

Number of queries dropped as non-compliant.

6.27 noncompliant-responses

Number of answers from a backend dropped as non-compliant.

6.28 queries

Number of received queries.

6.29 rdqueries

Number of received queries with the recursion desired bit set.

6.30 real-memory-usage

Current memory usage.

6.31 responses

Number of responses received from backends. Note! This is not the number of responses sent to clients. To get that number, add 'cache-hits' and 'responses'.

6.32 rule-drop

Number of queries dropped because of a rule.

6.33 rule-nxdomain

Number of NXDomain answers returned because of a rule.

6.34 rule-refused

Number of Refused answers returned because of a rule.

6.35 rule-servfail

Number of ServFail answers returned because of a rule.

6.36 security-status

New in version 1.3.4.

The security status of **dnscat**. This is regularly polled.

- 0 = Unknown status or unreleased version
- 1 = OK
- 2 = Upgrade recommended
- 3 = Upgrade required (most likely because there is a known security issue)

6.37 self-answered

Number of self-answered responses.

6.38 servfail-responses

Number of servfail answers received from backends.

6.39 trunc-failures

Number of errors encountered while truncating an answer.

6.40 uptime

Uptime of the dnscat process, in seconds.

CACHING RESPONSES

dnscache implements a simple but effective packet cache, not enabled by default. It is enabled per-pool, but the same cache can be shared between several pools. The first step is to define a cache with `newPacketCache()`, then to assign that cache to the chosen pool, the default one being represented by the empty string:

```
pc = newPacketCache(10000, {maxTTL=86400, minTTL=0, temporaryFailureTTL=60, ↵  
↵staleTTL=60, dontAge=false})  
getPool(""):setCache(pc)
```

+ The first parameter (10000) **is** the maximum number of entries stored **in** the cache, ↵
↵ **and is** the only one required. All the other parameters are optional **and in** ↵
↵ seconds, **except** the last one which **is** a boolean.

- The second one (86400) is the maximum lifetime of an entry in the cache.
- The third one (0) is the minimum TTL an entry should have to be considered for insertion in the cache.
- The fourth one (60) is the TTL used for a Server Failure or a Refused response.
- The fifth one (60) is the TTL that will be used when a stale cache entry is returned.
- The sixth one is a boolean that when set to true, avoids reducing the TTL of cached entries.

For performance reasons the cache will pre-allocate buckets based on the maximum number of entries, so be careful to set the first parameter to a reasonable value. Something along the lines of a dozen bytes per pre-allocated entry can be expected on 64-bit. That does not mean that the memory is completely allocated up-front, the final memory usage depending mostly on the size of cached responses and therefore varying during the cache's lifetime. Assuming an average response size of 512 bytes, a cache size of 10000000 entries on a 64-bit host with 8GB of dedicated RAM would be a safe choice.

The `setStaleCacheEntriesTTL()` directive can be used to allow dnscache to use expired entries from the cache when no backend is available. Only entries that have expired for less than n seconds will be used, and the returned TTL can be set when creating a new cache with `newPacketCache()`.

A reference to the cache affected to a specific pool can be retrieved with:

```
getPool("poolname"):getCache()
```

And removed with:

```
getPool("poolname"):unsetCache()
```

Cache usage stats (hits, misses, deferred inserts and lookups, collisions) can be displayed by using the `PacketCache:printStats()` method:

```
getPool("poolname"):getCache():printStats()
```

The same values can also be returned as a Lua table, which is easier to work with from a script, using the `PacketCache:getStats()` method.

Expired cached entries can be removed from a cache using the `PacketCache:purgeExpired()` method, which will remove expired entries from the cache until at most `n` entries remain in the cache. For example, to remove all expired entries:

```
getPool("poolname"):getCache():purgeExpired(0)
```

Specific entries can also be removed using the `PacketCache:expungeByName()` method:

```
getPool("poolname"):getCache():expungeByName(newDNSName("powerdns.com"), DNSQType.  
↪A)
```

Changed in version 1.4.0: Before 1.4.0, the QTypes were in the `dnsdist` namespace. Use `dnsdist.A` in these versions.

Finally, the `PacketCache:expunge()` method will remove all entries until at most `n` entries remain in the cache:

```
getPool("poolname"):getCache():expunge(0)
```

EXPORTING STATISTICS VIA CARBON

8.1 Setting up a carbon export

To emit metrics to Graphite, or any other software supporting the Carbon protocol, use:

```
carbonServer('ip-address-of-carbon-server', 'ourname', 30, 'dnsdist', 'main')
```

Where `ourname` can be used to override your hostname, and `30` is the reporting interval in seconds. `dnsdist` and `main` are used as namespace and instance variables. For `querycount` statistics these two variables are currently ignored. The last four arguments can be omitted. The latest version of [PowerDNS Metronome](#) comes with attractive graphs for `dnsdist` by default.

8.2 Query counters

In addition to other metrics, it is possible to send per-records statistics of the amount of queries by using `setQueryCount()`. With query counting enabled, `dnsdist` will increase a counter for every unique record or the behaviour you define in a custom Lua function by setting `setQueryCountFilter()`. This filter can decide whether to keep count on a query at all or rewrite for which query the counter will be increased. An example of a `QueryCountFilter` would be:

```
function filter(dq)
    qname = dq.qname:toString()

    -- don't count PTRs at all
    if(qname:match('in%-addr.arpa$')) then
        return false, ""
    end

    -- count these queries as if they were queried without leading www.
    if(qname:match('^www.')) then
        qname = qname:gsub('^www.', '')
    end

    -- count queries by default
    return true, qname
end

setQueryCountFilter(filter)
```

Valid return values for `QueryCountFilter` functions are:

- `true`: count the specified query
- `false`: don't count the query

Note that the query counters are buffered and flushed each time statistics are sent to the carbon server. The current content of the buffer can be inspected with `:getQueryCounters()`. If you decide to enable query counting

without `carbonServer()`, make sure you implement clearing the log from `maintenance()` by issuing `clearQueryCounters()`.

WORKING WITH THE DNSDIST CONSOLE

dnscat can expose a commandline console over an encrypted tcp connection for controlling it, debugging DNS issues and retrieving statistics.

The console can be enabled with `controlSocket()`:

```
controlSocket('192.0.2.53:5199')
```

Enabling the console without encryption enabled is not recommended. Note that encryption requires building dnscat with libsodium support enabled.

Once you have a libsodium-enabled dnscat, the first step to enable encryption is to generate a key with `makeKey()`:

```
$ ./dnscat -l 127.0.0.1:5300
[..]
> makeKey()
setKey("ENCODED KEY")
```

Then add the generated `setKey()` line to your dnscat configuration file, along with a `controlSocket()`:

```
controlSocket('192.0.2.53:5199') -- Listen on this IP and port for client_
↳connections
setKey("ENCODED KEY")           -- Shared secret for the console
```

Now you can run `dnscat -c` to connect to the console. This makes dnscat read its configuration file and use the `controlSocket()` and `setKey()` statements to set up its connection to the server.

If you want to connect over the network, create a configuration file with the same two statements and run `dnscat -C /path/to/configfile -c`.

Alternatively, you can specify the address and key on the client commandline:

```
dnscat -k "ENCODED KEY" -c 192.0.2.53:5199
```

Warning: This will leak the key into your shell's history and is **not** recommended.

Since 1.3.0, dnscat supports restricting which client can connect to the console with an ACL:

```
controlSocket('192.0.2.53:5199')
setConsoleACL('192.0.2.0/24')
```

The default value is '127.0.0.1', restricting the use of the console to local users. Please make sure that encryption is enabled before using `addConsoleACL()` or `setConsoleACL()` to allow connection from remote clients. Even if the console is restricted to local users, the use of encryption is still strongly advised to prevent unauthorized local users from connecting to the console.

DNS-OVER-TLS

Since version 1.3.0, **dnscat** supports experimental DNS-over-TLS support. To see if the installation supports this, run `dnscat --version`. If the output shows `dns-over-tls` with one or more SSL libraries in brackets, DNS-over-TLS is supported.

Adding a listen port for DNS-over-TLS can be done with the `addTLSTLocal()` function, e.g.:

```
addTLSTLocal('192.0.2.55', '/etc/ssl/certs/example.com.pem', '/etc/ssl/private/  
↪example.com.key')
```

This will make **dnscat** listen on 192.0.2.55:853 on TCP, and will use the provided certificate and key to serve incoming TLS connections.

In order to support multiple certificates and keys, for example an ECDSA and an RSA one, the following syntax may be used instead:

```
addTLSTLocal('192.0.2.55', {'/etc/ssl/certs/example.com.rsa.pem', '/etc/ssl/certs/  
↪example.com.ecdsa.pem'}, {'/etc/ssl/private/example.com.rsa.key', '/etc/ssl/  
↪private/example.com.ecdsa.key'})
```

The certificate chain presented by the server to an incoming client will then be selected based on the algorithms this client advertised support for.

DNSCRYPT

dnscrypt, when compiled with `--enable-dnscrypt`, can be used as a DNSCrypt server, uncurving queries before forwarding them to downstream servers and curving responses back. To make **dnscrypt** listen to incoming DNSCrypt queries on 127.0.0.1 port 8443, with a provider name of "2.providername", using a resolver certificate and associated key stored respectively in the `resolver.cert` and `resolver.key` files, the `addDNSCryptBind()` directive can be used:

```
addDNSCryptBind("127.0.0.1:8443", "2.providername", "/path/to/resolver.cert", "/  
↳path/to/resolver.key")
```

To generate the provider and resolver certificates and keys, you can simply do:

```
> generateDNSCryptProviderKeys("/path/to/providerPublic.key", "/path/to/  
↳providerPrivate.key")  
Provider fingerprint is:↳  
↳E1D7:2108:9A59:BF8D:F101:16FA:ED5E:EA6A:9F6C:C78F:7F91:AF6B:027E:62F4:69C3:B1AA  
> generateDNSCryptCertificate("/path/to/providerPrivate.key", "/path/to/resolver.  
↳cert", "/path/to/resolver.key", serial, validFrom, validUntil)
```

Ideally, the certificates and keys should be generated on an offline dedicated hardware and not on the resolver. The resolver key should be regularly rotated and should never touch persistent storage, being stored in a tmpfs with no swap configured.

You can display the currently configured DNSCrypt binds with:

```
> showDNSCryptBinds()  
# Address Provider Name Serial Validity P.↳  
↳Serial P. Validity  
0 127.0.0.1:8443 2.name 14 2016-04-10 08:14:15 0 ↳  
↳ -
```

If you forgot to write down the provider fingerprint value after generating the provider keys, you can use `printDNSCryptProviderFingerprint()` to retrieve it later:

```
> printDNSCryptProviderFingerprint("/path/to/providerPublic.key")  
Provider fingerprint is:↳  
↳E1D7:2108:9A59:BF8D:F101:16FA:ED5E:EA6A:9F6C:C78F:7F91:AF6B:027E:62F4:69C3:B1A
```


CONFIGURING DOWNSTREAM SERVERS

As `dnscat` is a loadbalancer and does not do any DNS resolving or serving by itself, it needs downstream servers. To add downstream servers, either include them on the command line:

```
dnscat -l 130.161.252.29 -a 130.161.0.0/16 8.8.8.8 208.67.222.222 2620:0:ccc::2 ↵  
↵2620:0:ccd::2
```

Or add them to the configuration file:

```
setLocal ("130.161.252.29:53")  
setACL ("130.161.0.0/16")  
newServer ("8.8.8.8")  
newServer ("208.67.222.222")  
newServer ("2620:0:ccc::2")  
newServer ("2620:0:ccd::2")
```

These two equivalent configurations give you sane load balancing using a very sensible distribution policy. Many users will simply be done with this configuration. It works as well for authoritative as for recursive servers.

12.1 Healthcheck

`dnscat` uses a health check, sent once every second, to determine the availability of a backend server.

By default, an A query for “a.root-servers.net.” is sent. A different query type, class and target can be specified by passing, respectively, the `checkType`, `checkClass` and `checkName` parameters to `newServer()`.

The default behavior is to consider any valid response with an RCODE different from `ServFail` as valid. If the `mustResolve` parameter of `newServer()` is set to `true`, a response will only be considered valid if its RCODE differs from `NXDomain`, `ServFail` and `Refused`.

The number of health check failures before a server is considered down is configurable via the `maxCheckFailures` parameter, defaulting to 1. The CD flag can be set on the query by setting `setCD` to `true`. e.g.:

```
newServer({address="192.0.2.1", checkType="AAAA", checkType=DNSClass.CHAOS, ↵  
↵checkName="a.root-servers.net.", mustResolve=true})
```

You can turn on logging of health check errors using the `setVerboseHealthChecks()` function.

Since the 1.3.0 release, the `checkFunction` option is also supported, taking a Lua function as parameter. This function receives a `DNSName`, two integers and a `DNSHeader` object (*DNSHeader (dh) object*) representing the QName, QType and QClass of the health check query as well as the DNS header, as they are defined before the function was called. The function must return a `DNSName` and two integers representing the new QName, QType and QClass, and can directly modify the `DNSHeader` object.

The following example sets the CD flag to true and change the QName to “powerdns.com.” and the QType to AAAA while keeping the initial QClass.

```
function myHealthCheck(qname, qtype, qclass, dh)
  dh:setCD(true)

  return newDNSName("powerdns.com."), dnssdist.AAAA, qclass
end

newServer("2620:0:0ccd::2")
```

12.2 Source address selection

In multi-homed setups, it can be useful to be able to select the source address or the outgoing interface used by dnssdist to contact a downstream server. This can be done by using the *source* parameter:

```
newServer({address="192.0.2.1", source="192.0.2.127"})
newServer({address="192.0.2.1", source="eth1"})
newServer({address="192.0.2.1", source="192.0.2.127@eth1"})
```

The supported values for source are: - an IPv4 or IPv6 address, which must exist on the system - an interface name - an IPv4 or IPv6 address followed by '@' then an interface name

Please note that specifying the interface name is only supported on system having *IP_PKTINFO*.

DYNAMIC RULE GENERATION

To set dynamic rules, based on recent traffic, define a function called `maintenance()` in Lua. It will get called every second, and from this function you can set rules to block traffic based on statistics. More exactly, the thread handling the `maintenance()` function will sleep for one second between each invocation, so if the function takes several seconds to complete it will not be invoked exactly every second.

As an example:

```
function maintenance()
    addDynBlocks(exceedQRate(20, 10), "Exceeded query rate", 60)
end
```

This will dynamically block all hosts that exceeded 20 queries/s as measured over the past 10 seconds, and the dynamic block will last for 60 seconds.

Dynamic blocks in force are displayed with `showDynBlocks()` and can be cleared with `clearDynBlocks()`. They return a table whose key is a `ComboAddress` object, representing the client's source address, and whose value is an integer representing the number of queries matching the corresponding condition (for example the `qtype` for `exceedQTypeRate()`, `rcode` for `exceedServFails()`).

All exceed-functions are documented in the *Configuration Reference*.

Dynamic blocks drop matched queries by default, but this behavior can be changed with `setDynBlocksAction()`. For example, to send a REFUSED code instead of dropping the query:

```
setDynBlocksAction(DNSAction.Refused)
```

Please see the documentation for `setDynBlocksAction()` to confirm which actions are supported.

13.1 DynBlockRulesGroup

Starting with dnsmdist 1.3.0, a new `DynBlockRulesGroup` function can be used to return a `DynBlockRulesGroup` instance, designed to make the processing of multiple rate-limiting rules faster by walking the query and response buffers only once for each invocation, instead of once per existing `exceed*()` invocation.

For example, instead of having something like:

```
function maintenance()
    addDynBlocks(exceedQRate(30, 10), "Exceeded query rate", 60)
    addDynBlocks(exceedNXDOMAINs(20, 10), "Exceeded NXD rate", 60)
    addDynBlocks(exceedServFails(20, 10), "Exceeded ServFail rate", 60)
    addDynBlocks(exceedQTypeRate(dnsmdist.ANY, 5, 10), "Exceeded ANY rate", 60)
    addDynBlocks(exceedRespByterate(1000000, 10), "Exceeded resp BW rate", 60)
end
```

The new syntax would be:

```
local dbr = dynBlockRulesGroup()
dbr:setQueryRate(30, 10, "Exceeded query rate", 60)
dbr:setRCodeRate(dnsmasq.NXDOMAIN, 20, 10, "Exceeded NXD rate", 60)
dbr:setRCodeRate(dnsmasq.SERVFAIL, 20, 10, "Exceeded ServFail rate", 60)
dbr:setQTypeRate(dnsmasq.ANY, 5, 10, "Exceeded ANY rate", 60)
dbr:setResponseByteRate(10000, 10, "Exceeded resp BW rate", 60)

function maintenance()
    dbr:apply()
end
```

The old syntax would walk the query buffer 2 times and the response one 3 times, while the new syntax does it only once for each. It also reuses the same internal table to keep track of the source IPs, reducing the CPU usage.

DynBlockRulesGroup also offers the ability to specify that some network ranges should be excluded from dynamic blocking:

```
-- do not add dynamic blocks for hosts in the 192.0.2.0/24 and 2001:db8::/32 ranges
dbr:excludeRange({"192.0.2.0/24", "2001:db8::/32" })
-- except for 192.0.2.1
dbr:includeRange("192.0.2.1/32")
```

Since 1.3.3, it's also possible to define a warning rate. When the query or response rate raises above the warning level but below the trigger level, a warning message will be issued along with a no-op block. If the rate reaches the trigger level, the regular action is applied.

```
local dbr = dynBlockRulesGroup()
-- generate a warning above 100 qps for 10s, and start dropping incoming queries
↪above 300 qps for 10s
dbr:setQueryRate(300, 10, "Exceeded query rate", 60, DNSAction.Drop, 100)
```


GUIDES

These chapters contain several guides and nuggets of information regarding dnsmasq operation and accomplishing specific goals.

14.1 Built-in webserver

To visually interact with dnsmasq, try add `webserver()` to the configuration:

```
webserver("127.0.0.1:8083", "supersecretpassword", "supersecretAPIkey")
```

Now point your browser at <http://127.0.0.1:8083> and log in with any username, and that password. Enjoy!

14.1.1 Security of the Webserver

The built-in webserver serves its content from inside the binary, this means it will not and cannot read from disk.

By default, our web server sends some security-related headers:

```
X-Content-Type-Options: nosniff
X-Frame-Options: deny
X-Permitted-Cross-Domain-Policies: none
X-XSS-Protection: 1; mode=block
Content-Security-Policy: default-src 'self'; style-src 'self' 'unsafe-inline'
```

You can override those headers, or add custom headers by using the last parameter to `webserver()`. For example, to remove the X-Frame-Options header and add a X-Custom one:

```
webserver("127.0.0.1:8080", "supersecret", "apikey", [{"X-Frame-Options"}= "", [{"X-
↪Custom"}="custom"])
```

Credentials can be changed over time using the `setWebserverConfig()` function.

14.1.2 dnsmasq API

To access the API, the `apikey` must be set in the `webserver()` function. Use the API, this key will need to be sent to dnsmasq in the X-API-Key request header. An HTTP 401 response is returned when a wrong or no API key is received. A 404 response is generated if the requested endpoint does not exist. And a 405 response is returned when the HTTP method is not allowed.

URL Endpoints

GET /jsonstat

Get statistics from dnsmasq in JSON format. The Accept request header is ignored. This endpoint accepts a command query for different statistics:

- stats: Get all *Statistics* as a JSON dict
- dynblocklist: Get all current *dynamic blocks*, keyed by netmask
- ebpfblocklist: Idem, but for *eBPF* blocks

Example request:

```
GET /jsonstat?command=stats HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
```

Example response:

```
HTTP/1.1 200 OK
Transfer-Encoding: chunked
Connection: close
Content-Security-Policy: default-src 'self'; style-src 'self' 'unsafe-
↪inline'
Content-Type: application/json
X-Content-Type-Options: nosniff
X-Frame-Options: deny
X-Permitted-Cross-Domain-Policies: none
X-Xss-Protection: 1; mode=block

{"acl-drops": 0, "block-filter": 0, "cache-hits": 0, "cache-misses": 0,
↪ "cpu-sys-msec": 633, "cpu-user-msec": 499, "downstream-send-errors": 0,
↪ "downstream-timeouts": 0, "dyn-block-nmg-size": 1, "dyn-blocked": 3,
↪ "empty-queries": 0, "fd-usage": 17, "latency-avg100": 7651.3982737482893,
↪ "latency-avg1000": 860.05142763680249, "latency-avg10000": 87.
↪032142373878372, "latency-avg1000000": 0.87146026426551759, "latency-slow
↪": 0, "latency0-1": 0, "latency1-10": 0, "latency10-50": 22, "latency100-
↪1000": 1, "latency50-100": 0, "no-policy": 0, "noncompliant-queries": 0,
↪ "noncompliant-responses": 0, "over-capacity-drops": 0, "packetcache-hits
↪": 0, "packetcache-misses": 0, "queries": 26, "rdqueries": 26, "real-
↪memory-usage": 6078464, "responses": 23, "rule-drop": 0, "rule-nxdomain
↪": 0, "rule-refused": 0, "self-answered": 0, "server-policy":
↪ "leastOutstanding", "servfail-responses": 0, "too-old-drops": 0, "trunc-
↪failures": 0, "uptime": 412}
```

Example request:

```
GET /jsonstat?command=dynblocklist HTTP/1.1
Host: example.com
Accept: application/json, text/javascript
```

Example response:

```
HTTP/1.1 200 OK
Transfer-Encoding: chunked
Connection: close
Content-Security-Policy: default-src 'self'; style-src 'self' 'unsafe-
↪inline'
Content-Type: application/json
X-Content-Type-Options: nosniff
X-Frame-Options: deny
X-Permitted-Cross-Domain-Policies: none
X-Xss-Protection: 1; mode=block

{"127.0.0.1/32": {"blocks": 3, "reason": "Exceeded query rate", "seconds": 10}}
```

Query Parameters

- **command** – one of stats, dynblocklist or ebpfblocklist

GET /metrics

Get statistics from dnsdist in [Prometheus](#) format.

Example request:

```
GET /metrics HTTP/1.1
```

Example response:

```
HTTP/1.1 200 OK
Transfer-Encoding: chunked
Content-Security-Policy: default-src 'self'; style-src 'self' 'unsafe-
↳inline'
Content-Type: text/plain
X-Content-Type-Options: nosniff
X-Frame-Options: deny
X-Permitted-Cross-Domain-Policies: none
X-Xss-Protection: 1; mode=block

# HELP dnsdist_responses Number of responses received from backends
# TYPE dnsdist_responses counter
dnsdist_responses 0
# HELP dnsdist_servfail_responses Number of SERVFAIL answers received from
↳backends
# TYPE dnsdist_servfail_responses counter
dnsdist_servfail_responses 0
# HELP dnsdist_queries Number of received queries
# TYPE dnsdist_queries counter
dnsdist_queries 0
# HELP dnsdist_acl_drops Number of packets dropped because of the ACL
# TYPE dnsdist_acl_drops counter
dnsdist_acl_drops 0
# HELP dnsdist_rule_drop Number of queries dropped because of a rule
# TYPE dnsdist_rule_drop counter
dnsdist_rule_drop 0
# HELP dnsdist_rule_nxdomain Number of NXDomain answers returned because
↳of a rule
# TYPE dnsdist_rule_nxdomain counter
dnsdist_rule_nxdomain 0
# HELP dnsdist_rule_refused Number of Refused answers returned because of
↳a rule
# TYPE dnsdist_rule_refused counter
dnsdist_rule_refused 0
# HELP dnsdist_rule_servfail Number of SERVFAIL answers received because
↳of a rule
# TYPE dnsdist_rule_servfail counter
dnsdist_rule_servfail 0
# HELP dnsdist_self_answered Number of self-answered responses
# TYPE dnsdist_self_answered counter
dnsdist_self_answered 0
# HELP dnsdist_downstream_timeouts Number of queries not answered in time
↳by a backend
# TYPE dnsdist_downstream_timeouts counter
dnsdist_downstream_timeouts 0
# HELP dnsdist_downstream_send_errors Number of errors when sending a
↳query to a backend
# TYPE dnsdist_downstream_send_errors counter
dnsdist_downstream_send_errors 0
```

(continues on next page)

(continued from previous page)

```

# HELP dnssdist_trunc_failures Number of errors encountered while
↳truncating an answer
# TYPE dnssdist_trunc_failures counter
dnssdist_trunc_failures 0
# HELP dnssdist_no_policy Number of queries dropped because no server was
↳available
# TYPE dnssdist_no_policy counter
dnssdist_no_policy 0
# HELP dnssdist_latency0_1 Number of queries answered in less than 1ms
# TYPE dnssdist_latency0_1 counter
dnssdist_latency0_1 0
# HELP dnssdist_latency1_10 Number of queries answered in 1-10 ms
# TYPE dnssdist_latency1_10 counter
dnssdist_latency1_10 0
# HELP dnssdist_latency10_50 Number of queries answered in 10-50 ms
# TYPE dnssdist_latency10_50 counter
dnssdist_latency10_50 0
# HELP dnssdist_latency50_100 Number of queries answered in 50-100 ms
# TYPE dnssdist_latency50_100 counter
dnssdist_latency50_100 0
# HELP dnssdist_latency100_1000 Number of queries answered in 100-1000 ms
# TYPE dnssdist_latency100_1000 counter
dnssdist_latency100_1000 0
# HELP dnssdist_latency_slow Number of queries answered in more than 1
↳second
# TYPE dnssdist_latency_slow counter
dnssdist_latency_slow 0
# HELP dnssdist_latency_avg100 Average response latency in microseconds of
↳the last 100 packets
# TYPE dnssdist_latency_avg100 gauge
dnssdist_latency_avg100 0
# HELP dnssdist_latency_avg1000 Average response latency in microseconds of
↳the last 1000 packets
# TYPE dnssdist_latency_avg1000 gauge
dnssdist_latency_avg1000 0
# HELP dnssdist_latency_avg10000 Average response latency in microseconds
↳of the last 10000 packets
# TYPE dnssdist_latency_avg10000 gauge
dnssdist_latency_avg10000 0
# HELP dnssdist_latency_avg1000000 Average response latency in microseconds
↳of the last 1000000 packets
# TYPE dnssdist_latency_avg1000000 gauge
dnssdist_latency_avg1000000 0
# HELP dnssdist_uptime Uptime of the dnssdist process in seconds
# TYPE dnssdist_uptime gauge
dnssdist_uptime 39
# HELP dnssdist_real_memory_usage Current memory usage in bytes
# TYPE dnssdist_real_memory_usage gauge
dnssdist_real_memory_usage 10276864
# HELP dnssdist_noncompliant_queries Number of queries dropped as non-
↳compliant
# TYPE dnssdist_noncompliant_queries counter
dnssdist_noncompliant_queries 0
# HELP dnssdist_noncompliant_responses Number of answers from a backend
↳dropped as non-compliant
# TYPE dnssdist_noncompliant_responses counter
dnssdist_noncompliant_responses 0
# HELP dnssdist_rdqueries Number of received queries with the recursion
↳desired bit set
# TYPE dnssdist_rdqueries counter
dnssdist_rdqueries 0

```

(continues on next page)

(continued from previous page)

```

# HELP dnsmist_empty_queries Number of empty queries received from clients
# TYPE dnsmist_empty_queries counter
dnsmist_empty_queries 0
# HELP dnsmist_cache_hits Number of times an answer was retrieved from
↪cache
# TYPE dnsmist_cache_hits counter
dnsmist_cache_hits 0
# HELP dnsmist_cache_misses Number of times an answer not found in the
↪cache
# TYPE dnsmist_cache_misses counter
dnsmist_cache_misses 0
# HELP dnsmist_cpu_user_msec Milliseconds spent by dnsmist in the user
↪state
# TYPE dnsmist_cpu_user_msec counter
dnsmist_cpu_user_msec 28
# HELP dnsmist_cpu_sys_msec Milliseconds spent by dnsmist in the system
↪state
# TYPE dnsmist_cpu_sys_msec counter
dnsmist_cpu_sys_msec 32
# HELP dnsmist_fd_usage Number of currently used file descriptors
# TYPE dnsmist_fd_usage gauge
dnsmist_fd_usage 17
# HELP dnsmist_dyn_blocked Number of queries dropped because of a dynamic
↪block
# TYPE dnsmist_dyn_blocked counter
dnsmist_dyn_blocked 0
# HELP dnsmist_dyn_block_nmg_size Number of dynamic blocks entries
# TYPE dnsmist_dyn_block_nmg_size gauge
dnsmist_dyn_block_nmg_size 0
dnsmist_server_queries{server="1_1_1_1",address="1.1.1.1:53"} 0
dnsmist_server_drops{server="1_1_1_1",address="1.1.1.1:53"} 0
dnsmist_server_latency{server="1_1_1_1",address="1.1.1.1:53"} 0
dnsmist_server_senderrors{server="1_1_1_1",address="1.1.1.1:53"} 0
dnsmist_server_outstanding{server="1_1_1_1",address="1.1.1.1:53"} 0
dnsmist_server_order{server="1_1_1_1",address="1.1.1.1:53"} 1
dnsmist_server_weight{server="1_1_1_1",address="1.1.1.1:53"} 1
dnsmist_server_queries{server="1_0_0_1",address="1.0.0.1:53"} 0
dnsmist_server_drops{server="1_0_0_1",address="1.0.0.1:53"} 0
dnsmist_server_latency{server="1_0_0_1",address="1.0.0.1:53"} 0
dnsmist_server_senderrors{server="1_0_0_1",address="1.0.0.1:53"} 0
dnsmist_server_outstanding{server="1_0_0_1",address="1.0.0.1:53"} 0
dnsmist_server_order{server="1_0_0_1",address="1.0.0.1:53"} 1
dnsmist_server_weight{server="1_0_0_1",address="1.0.0.1:53"} 2
dnsmist_frontend_queries{frontend="127.0.0.1:1153",proto="udp"} 0
dnsmist_frontend_queries{frontend="127.0.0.1:1153",proto="tcp"} 0
dnsmist_pool_servers{pool="_default_"} 2
dnsmist_pool_cache_size{pool="_default_"} 200000
dnsmist_pool_cache_entries{pool="_default_"} 0
dnsmist_pool_cache_hits{pool="_default_"} 0
dnsmist_pool_cache_misses{pool="_default_"} 0
dnsmist_pool_cache_deferred_inserts{pool="_default_"} 0
dnsmist_pool_cache_deferred_lookups{pool="_default_"} 0
dnsmist_pool_cache_lookup_collisions{pool="_default_"} 0
dnsmist_pool_cache_insert_collisions{pool="_default_"} 0
dnsmist_pool_cache_ttl_too_shorts{pool="_default_"} 0

```

Example prometheus configuration:

This is just the scrape job description, for details see the prometheus documentation.

```

job_name: dnssdist
scrape_interval: 10s
scrape_timeout: 2s
metrics_path: /metrics
basic_auth:
  username: dontcare
  password: yoursecret

```

GET /api/v1/servers/localhost

Get a quick overview of several parameters.

Response JSON Object

- **acl** (*string*) – A string of comma-separated netmasks currently allowed by the *ACL*.
- **cache-hit-response-rules** (*list*) – A list of *ResponseRule* objects applied on cache hits
- **self-answered-response-rules** (*list*) – A list of *ResponseRule* objects applied on self-answered queries
- **daemon_type** (*string*) – The type of daemon, always “dnssdist”
- **frontends** (*list*) – A list of *Frontend* objects
- **pools** (*list*) – A list of *Pool* objects
- **response-rules** (*list*) – A list of *ResponseRule* objects
- **rules** (*list*) – A list of *Rule* objects
- **servers** (*list*) – A list of *Server* objects
- **version** (*string*) – The running version of dnssdist

GET /api/v1/servers/localhost/statistics

Returns a list of all statistics as *StatisticItem*.

GET /api/v1/servers/localhost/config

Returns a list of *ConfigSetting* objects.

GET /api/v1/servers/localhost/config/allow-from

Gets you the allow-from *ConfigSetting*, who’s value is a list of strings of all the netmasks in the *ACL*.

Example request:

```

GET /api/v1/servers/localhost/config/allow-from HTTP/1.1
X-API-Key: supersecretAPIkey

```

Example response:

```

HTTP/1.1 200 OK
Connection: close
Content-Security-Policy: default-src 'self'; style-src 'self' 'unsafe-
↪inline'
Content-Type: application/json
Transfer-Encoding: chunked
X-Content-Type-Options: nosniff
X-Frame-Options: deny
X-Permitted-Cross-Domain-Policies: none
X-Xss-Protection: 1; mode=block

{
  "name": "allow-from",
  "type": "ConfigSetting",

```

(continues on next page)

(continued from previous page)

```

    "value": [
      "fc00::/7",
      "169.254.0.0/16",
      "100.64.0.0/10",
      "fe80::/10",
      "10.0.0.0/8",
      "127.0.0.0/8",
      "::1/128",
      "172.16.0.0/12",
      "192.168.0.0/16"
    ]
  }
}

```

PUT /api/v1/servers/localhost/config/allow-from
 Allows you to update the `allow-from` *ACL* with a list of netmasks.

Make sure you made the API writable using `setAPIWritable()`.

Example request:

```

PUT /api/v1/servers/localhost/config/allow-from HTTP/1.1
Content-Length: 37
Content-Type: application/json
X-API-Key: supersecretAPIkey

{
  "value": [
    "127.0.0.0/8",
    "::1/128"
  ]
}

```

Example response:

```

HTTP/1.1 200 OK
Connection: close
Content-Security-Policy: default-src 'self'; style-src 'self' 'unsafe-
↪inline'
Content-Type: application/json
Transfer-Encoding: chunked
X-Content-Type-Options: nosniff
X-Frame-Options: deny
X-Permitted-Cross-Domain-Policies: none
X-Xss-Protection: 1; mode=block

{
  "name": "allow-from",
  "type": "ConfigSetting",
  "value": [
    "127.0.0.0/8",
    "::1/128"
  ]
}

```

JSON Objects

ConfigSetting

An object representing a global configuration element. The following configuration are returned:

- `acl` The currently configured *ACLs*

- `control-socket` The currently configured *console address*
- `ecs-override`
- `ecs-source-prefix-v4` The currently configured `setECSSourcePrefixV4()`
- `ecs-source-prefix-v6` The currently configured `setECSSourcePrefixV6()`
- `fixup-case`
- `max-outstanding`
- `server-policy` The currently set *Loadbalancing and Server Policies*
- `stale-cache-entries-ttl`
- `tcp-recv-timeout`
- `tcp-send-timeout`
- `truncate-tc`
- `verbose`
- `verbose-health-checks` The currently configured `setVerboseHealthChecks()`

Object Properties

- **name** (*string*) – The name of the setting
- **type** (*string*) – “ConfigSetting”
- **value** (*string*) – The value for this setting

Frontend

A description of a bind dnsmdist is listening on.

Object Properties

- **address** (*string*) – IP and port that is listened on
- **id** (*integer*) – Internal identifier
- **queries** (*integer*) – The number of received queries on this bind
- **udp** (*boolean*) – true if this is a UDP bind
- **tcp** (*boolean*) – true if this is a TCP bind

Pool

A description of a pool of backend servers.

Object Properties

- **id** (*integer*) – Internal identifier
- **cacheDeferredInserts** (*integer*) – The number of times an entry could not be inserted in the associated cache, if any, because of a lock
- **cacheDeferredLookups** (*integer*) – The number of times an entry could not be looked up from the associated cache, if any, because of a lock
- **cacheEntries** (*integer*) – The current number of entries in the associated cache, if any
- **cacheHits** (*integer*) – The number of cache hits for the associated cache, if any
- **cacheLookupCollisions** (*integer*) – The number of times an entry retrieved from the cache based on the query hash did not match the actual query
- **cacheInsertCollisions** (*integer*) – The number of times an entry could not be inserted into the cache because a different entry with the same hash already existed

- **cacheMisses** (*integer*) – The number of cache misses for the associated cache, if any
- **cacheSize** (*integer*) – The maximum number of entries in the associated cache, if any
- **cacheTTLTooShorts** (*integer*) – The number of times an entry could not be inserted into the cache because its TTL was set below the minimum threshold
- **name** (*string*) – Name of the pool
- **serversCount** (*integer*) – Number of backends in this pool

Rule

This represents a policy that is applied to queries

Object Properties

- **action** (*string*) – The action taken when the rule matches (e.g. “to pool abuse”)
- **action-stats** (*dict*) – A list of statistics whose content varies depending on the kind of rule
- **id** (*integer*) – The position of this rule
- **matches** (*integer*) – How many times this rule was hit
- **rule** (*string*) – The matchers for the packet (e.g. “qname==bad-domain1.example., bad-domain2.example.”)
- **uuid** (*string*) – The UUID of this rule

ResponseRule

This represents a policy that is applied to responses

Object Properties

- **action** (*string*) – The action taken when the rule matches (e.g. “drop”)
- **id** (*integer*) – The identifier (or order) of this rule
- **matches** (*integer*) – How many times this rule was hit
- **rule** (*string*) – The matchers for the packet (e.g. “qname==bad-domain1.example., bad-domain2.example.”)

Server

This object represents a backend server.

Changed in version 1.3.1: The `dropRate` property was added

Object Properties

- **address** (*string*) – The remote IP and port
- **id** (*integer*) – Internal identifier
- **latency** (*integer*) – The current latency of this backend server
- **name** (*string*) – The name of this server
- **order** (*integer*) – Order number
- **outstanding** (*integer*) – Number of currently outstanding queries
- **pools** (*[string]*) – The pools this server belongs to
- **qps** (*integer*) – The current number of queries per second to this server
- **qpsLimit** (*integer*) – The configured maximum number of queries per second
- **queries** (*integer*) – Total number of queries sent to this backend

- **reuseds** (*integer*) – Number of queries for which a response was not received in time
- **sendErrors** (*integer*) – Number of network errors while sending a query to this server
- **state** (*string*) – The state of the server (e.g. “DOWN” or “up”)
- **weight** (*integer*) – The weight assigned to this server
- **dropRate** (*float*) – The amount of packets dropped per second by this server

StatisticItem

This represents a statistics element.

Object Properties

- **name** (*string*) – The name of this statistic. See *Statistics*
- **type** (*string*) – “StatisticItem”
- **value** (*integer*) – The value for this item

14.2 Server pools

dnsmdist has the concept to “server pools”, any number of servers can belong to a group.

Let’s say we know we’re getting a whole bunch of traffic for a domain used in DoS attacks, for example ‘example.com’. We can do two things with this kind of traffic. Either we block it outright, like this:

```
addAction("bad-domain.example.", DropAction())
```

Or we configure a server pool dedicated to receiving the nasty stuff:

```
newServer({address="192.0.2.3", pool="abuse"})           -- Add a backend server
↪with address 192.0.2.3 and assign it to the "abuse" pool
addAction({'bad-domain1.example', 'bad-domain2.example.'}, PoolAction("abuse")) --
↪Send all queries for "bad-domain1.example." and "bad-domain2.example" to the
↪"abuse" pool
```

The wonderful thing about this last solution is that it can also be used for things where a domain might possibly be legit, but it is still causing load on the system and slowing down the internet for everyone. With such an abuse server, ‘bad traffic’ still gets a chance of an answer, but without impacting the rest of the world (too much).

We can similarly add clients to the abuse server:

```
addAction({"192.168.12.0/24", "192.168.13.14"}, PoolAction("abuse"))
```

To define a pool that should receive only a *QPS*-limited amount of traffic, do:

```
addAction("com.", QPSPoolAction(10000, "gtld-cluster"))
```

Traffic exceeding the *QPS* limit will not match that rule, and subsequent rules will apply normally.

Servers can be added to or removed from pools with the *Server:addPool()* and *Server:rmPool()* functions respectively:

```
getServer(4):addPool("abuse")
getServer(4):rmPool("abuse")
```

14.3 Loadbalancing and Server Policies

dnsmist selects the server (if there are multiple eligible) to send queries to based on the configured policy. Only servers that are marked as ‘up’, either forced so by the administrator or as the result of the last health check, might be selected.

14.3.1 Built-in Policies

leastOutstanding

The default load balancing policy is called `leastOutstanding`, which means the server with the least queries ‘in the air’ is picked. The exact selection algorithm is:

- pick the server with the least queries ‘in the air’ ;
- in case of a tie, pick the one with the lowest configured ‘order’ ;
- in case of a tie, pick the one with the lowest measured latency (over an average on the last 128 queries answered by that server).

firstAvailable

The `firstAvailable` policy, picks the first available server that has not exceeded its QPS limit, ordered by increasing ‘order’. If all servers are above their QPS limit, a server is selected based on the `leastOutstanding` policy. For now this is the only policy using the QPS limit.

wrandom

A further policy, `wrandom` assigns queries randomly, but based on the `weight` parameter passed to `newServer()`.

For example, if two servers are available, the first one with a weight of 2 and the second one with a weight of 1 (the default), the first one should get two-thirds of the incoming queries and the second one the remaining third.

whashed

`whashed` is a similar weighted policy, but assigns questions with identical hash to identical servers, allowing for better cache concentration (‘sticky queries’). The current hash algorithm is based on the `qname` of the query.

setWHashedPerturbation (*value*)

Set the hash perturbation value to be used in the `whashed` policy instead of a random one, allowing to have consistent `whashed` results on different instances.

chashed

`chashed` is a consistent hashing distribution policy. Identical questions with identical hashes will be distributed to the same servers. But unlike the `whashed` policy, this distribution will keep consistent over time. Adding or removing servers will only remap a small part of the queries.

You can also set the hash perturbation value, see `setWHashedPerturbation()`. To achieve consistent distribution over **dnsmist** restarts, you will also need to explicitly set the backend’s UUIDs with the `id` option of `newServer()`. You can get the current UUIDs of your backends by calling `showServers()` with the `showUUIDs=true` option.

roundrobin

The last available policy is `roundrobin`, which indiscriminately sends each query to the next server that is up. If all servers are down, the policy will still select one server by default. Setting `setRoundRobinFailOnNoServer()` to `true` will change this behavior.

14.3.2 Lua server policies

If you don't like the default policies you can create your own, like this for example:

```
counter=0
function luaroundrobin(servers, dq)
    counter=counter+1
    return servers[1+(counter % #servers)]
end

setServerPolicyLua("luaroundrobin", luaroundrobin)
```

Incidentally, this is similar to setting: `setServerPolicy(roundrobin)` which uses the C++ based `roundrobin` policy.

Or:

```
newServer("192.168.1.2")
newServer({address="8.8.4.4", pool="numbered"})

function splitSetup(servers, dq)
    if(string.match(dq.qname:toString(), "%d"))
    then
        print("numbered pool")
        return leastOutstanding.policy(getPoolServers("numbered"), dq)
    else
        print("standard pool")
        return leastOutstanding.policy(servers, dq)
    end
end

setServerPolicyLua("splitsetup", splitSetup)
```

14.3.3 ServerPolicy Objects

class ServerPolicy

This represents a server policy. The built-in policies are of this type

`ServerPolicy.policy(servers, dq) → Server`

Run the policy to receive the server it has selected.

Parameters

- **servers** – A list of `Server` objects
- **dq** (`DNSQuestion`) – The incoming query

14.3.4 Functions

`newServerPolicy(name, function) → ServerPolicy`

Create a policy object from a Lua function. `function` must match the prototype for `ServerPolicy.policy()`.

Parameters

- **name** (*string*) – Name of the policy
- **function** (*string*) – The function to call for this policy

setServerPolicy (*policy*)

Set server selection policy to *policy*.

Parameters **policy** (*ServerPolicy*) – The policy to use

setServerPolicyLua (*name, function*)

Set server selection policy to one named *name* and provided by *function*.

Parameters

- **name** (*string*) – name for this policy
- **function** (*string*) – name of the function

setServFailWhenNoServer (*value*)

If set, return a ServFail when no servers are available, instead of the default behaviour of dropping the query.

Parameters **value** (*bool*) – whether to return a servfail instead of dropping the query

setPoolServerPolicy (*policy, pool*)

Set the server selection policy for *pool* to *policy*.

Parameters

- **policy** (*ServerPolicy*) – The policy to apply
- **pool** (*string*) – Name of the pool

setPoolServerPolicyLua (*name, function, pool*)

Set the server selection policy for *pool* to one named *name* and provided by *function*.

Parameters

- **name** (*string*) – name for this policy
- **function** (*string*) – name of the function
- **pool** (*string*) – Name of the pool

setRoundRobinFailOnNoServer (*value*)

New in version 1.4.0.

By default the roundrobin load-balancing policy will still try to select a backend even if all backends are currently down. Setting this to true will make the policy fail and return that no server is available instead.

Parameters **value** (*bool*) – whether to fail when all servers are down

showPoolServerPolicy (*pool*)

Print server selection policy for *pool*.

Parameters **pool** (*string*) – The pool to print the policy for

ADVANCED TOPICS

These chapters contain information on the advanced features of dnsmasq

15.1 Access Control

dnsmasq can be used to front traditional recursive nameservers, these usually come with a way to limit the network ranges that may query it to prevent becoming an *open resolver*. To be a good internet citizen, dnsmasq by default listens on the loopback address (*127.0.0.1:53*) and limits queries to these loopback, [RFC 1918](#) and other local addresses:

- 127.0.0.0/8
- 10.0.0.0/8
- 100.64.0.0/10
- 169.254.0.0/16
- 192.168.0.0/16
- 172.16.0.0/12
- ::1/128
- fc00::/7
- fe80::/10

The ACL applies to queries received over UDP, TCP, DNS over TLS and DNS over HTTPS.

Further more, dnsmasq only listens for queries on the local-loopback interface by default.

15.1.1 Listening on different addresses

To listen on other addresses than just the local addresses, use `setLocal()` and `addLocal()`.

`setLocal()` resets the list of current listen addresses to the specified address and `addLocal()` adds an additional listen address. To listen on `127.0.0.1:5300`, `192.0.2.1:53` and UDP-only on `[2001:db8::15::47]:53`, configure the following:

```
setLocal('127.0.0.1:5300')
addLocal('192.0.2.1') -- Port 53 is default is none is specified
addLocal('2001:db8::15::47', false)
```

Listen addresses cannot be modified at runtime and must be specified in the configuration file.

As dnsmasq is IPv4 and IPv6 agnostic, this means that dnsmasq internally does not know the difference. So feel free to listen on the magic `0.0.0.0` or `::` addresses, dnsmasq does the right thing to set the return address of queries, but set your *ACL* properly.

15.1.2 Modifying the ACL

ACLs can be modified at runtime from the *Working with the dnsmdist Console*. To inspect the currently active ACL, run `showACL()`.

To add a new network range to the existing ACL, use `addACL()`:

```
addACL('192.0.2.0/25')
addACL('2001:db8::1') -- No netmask specified, only allow this address
```

dnsmdist also has the `setACL()` function that accepts a list of netmasks and resets the ACL to that list:

```
setACL({'192.0.2.0/25', '2001:db8:15::bea/64'})
```

15.2 TeeAction: copy the DNS traffic stream

This action sends off a copy of a UDP query to another server, and keeps statistics on the responses received. Sample use:

```
> addAction(AllRule(), TeeAction("192.0.2.54"))
> getAction():printStats()
refuseds      0
nxdomains    0
noerrors     0
servfails    0
recv-errors  0
tcp-drops    0
responses    0
other-rcode  0
send-errors  0
queries      0
```

It is also possible to share a `TeeAction()` between several rules. Statistics will be combined in that case.

15.3 Lua actions in rules

While we can pass every packet through the `blockFilter()` functions, it is also possible to configure **dnsmdist** to only hand off some packets for Lua inspection. If you think Lua is too slow for your query load, or if you are doing heavy processing in Lua, this may make sense.

To select specific packets for Lua attention, use `addAction()` with `LuaAction()`, or `addResponseAction()` with `LuaResponseAction()`.

A sample configuration could look like this:

```
function luarule(dq)
  if(dq.qtype==35) -- NAPTR
  then
    return DNSAction.Pool, "abuse" -- send to abuse pool
  else
    return DNSAction.None, "" -- no action
  end
end

addAction(AllRule(), LuaAction(luarule))
```


15.4 Runtime-modifiable IP address sets

New in version 1.2.0.

From within `maintenance()` or other places, we may find that certain IP addresses must be treated differently for a certain time.

This may be used to temporarily shunt traffic to another pool for example.

`TimedIPSetRule()` creates an object to which native IP addresses can be added in `ComboAddress` form.

TimedIPSetRule() → `TimedIPSetRule`

Returns a `TimedIPSetRule`.

class TimedIPSetRule

Can be used to handle IP addresses differently for a certain time.

:add(*address, seconds*)

Add an IP address to the set for the next `second` seconds.

Parameters

- **address** (`ComboAddress`) – The address to add
- **seconds** (`int`) – Time to keep the address in the Rule

:cleanup()

Purge the set from expired IP addresses

:clear()

Clear the entire set

:slice()

Convert the `TimedIPSetRule` into a `DNSRule` that can be passed to `addAction()`

A working example:

```
tisrElGoog=TimedIPSetRule()
tisrRest=TimedIPSetRule()
addAction(tisrElGoog:slice(), PoolAction("elgoog"))
addAction(tisrRest:slice(), PoolAction(""))

elgoogPeople=newNMG()
elgoogPeople:addMask("192.168.5.0/28")

function pickPool(dq)
    if(elgoogPeople:match(dq.remoteaddr) -- in real life, this would be
→external
    then
        print("Lua caught query for a googlePerson")
        tisrElGoog:add(dq.remoteaddr, 10)
        return DNSAction.Pool, "elgoog"
    else
        print("Lua caught query for restPerson")
        tisrRest:add(dq.remoteaddr, 60)
        return DNSAction.None, ""
    end
end

addAction(AllRule(), LuaAction(pickPool))
```

15.5 Using EDNS Client Subnet

In order to provide the downstream server with the address of the real client, or at least the one talking to dnsmdist, the `useClientSubnet` parameter can be used when creating a *new server*. This parameter indicates whether an EDNS Client Subnet option should be added to the request. If the incoming request already contains an EDNS Client Subnet value, it will not be overridden unless `setECSSourcePrefixV4()` is set to `true`. The default source prefix-length is 24 for IPv4 and 56 for IPv6, meaning that for a query received from 192.0.2.42, the EDNS Client Subnet value sent to the backend will be 192.0.2.0. This can be changed with `setECSSourcePrefixV4()` and `setECSSourcePrefixV6()`.

In addition to the global settings, rules and Lua bindings can alter this behavior per query:

- calling `DisableECSAction()` or setting `dq.useECS` to `false` prevents the sending of the ECS option.
- calling `ECSOverrideAction()` or setting `dq.ecsOverride` will override the global `setECSSourcePrefixV4()` value.
- calling `ECSPrefixLengthAction(v4, v6)` or setting `dq.ecsPrefixLength` will override the global `setECSSourcePrefixV4()` and `setECSSourcePrefixV6()` values.

In effect this means that for the EDNS Client Subnet option to be added to the request, `useClientSubnet` should be set to `true` for the backend used (default to `false`) and ECS should not have been disabled by calling `DisableECSAction()` or setting `dq.useECS` to `false` (default to `true`).

Note that any trailing data present in the incoming query is removed by default when an OPT (or XPF) record has to be inserted. This behaviour can be modified using `setPreserveTrailingData()`.

15.6 Rules for traffic exceeding QPS limits

Traffic that exceeds a QPS limit, in total or per IP (subnet) can be matched by the `MaxQPSIPRule()`-rule. For example:

```
addAction(MaxQPSIPRule(5, 32, 48), DelayAction(100))
```

This measures traffic per IPv4 address and per /48 of IPv6, and if traffic for such an address (range) exceeds 5 *qps*, it gets delayed by 100ms.

As another example:

```
addAction(MaxQPSIPRule(5), NoRecurseAction())
```

This strips the Recursion Desired (RD) bit from any traffic per IPv4 or IPv6 /64 that exceeds 5 *qps*. This means any those traffic bins is allowed to make a recursor do ‘work’ for only 5 *qps*.

If this is not enough, try:

```
addAction(MaxQPSIPRule(5), DropAction())
-- or
addAction(MaxQPSIPRule(5), TCAction())
```

This will respectively drop traffic exceeding that 5 QPS limit per IP or range, or return it with TC=1, forcing clients to fall back to TCP.

To turn this per IP or range limit into a global limit, use `NotRule(MaxQPSRule(5000))` instead of `MaxQPSIPRule()`.

15.7 eBPF Socket Filtering

dnscat can use eBPF socket filtering on recent Linux kernels (4.1+) built with eBPF support (CONFIG_BPF, CONFIG_BPF_SYSCALL, ideally CONFIG_BPF_JIT). This feature might require an increase of the memory limit associated to a socket, via the sysctl setting `net.core.optmem_max`. When attaching an eBPF program to a socket, the size of the program is checked against this limit, and the default value might not be enough. Large map sizes might also require an increase of `RLIMIT_MEMLOCK`.

This feature allows dnscat to ask the kernel to discard incoming packets in kernel-space instead of them being copied to userspace just to be dropped, thus being a lot of faster.

The BPF filter can be used to block incoming queries manually:

```
> bpf = newBPFFilter(1024, 1024, 1024)
> bpf:attachToAllBinds()
> bpf:block(newCA("2001:DB8::42"))
> bpf:blockQName(newDNSName("evildomain.com"), 255)
> bpf:getStats()
[2001:DB8::42]: 0
evildomain.com. 255: 0
> bpf:unblock(newCA("2001:DB8::42"))
> bpf:unblockQName(newDNSName("evildomain.com"), 255)
> bpf:getStats()
```

The `BPFFilter:blockQName()` method can be used to block queries based on the exact qname supplied, in a case-insensitive way, and an optional qtype. Using the 255 (ANY) qtype will block all queries for the qname, regardless of the qtype. Contrary to source address filtering, qname filtering only works over UDP. TCP qname filtering can be done the usual way:

```
addAction(AndRule({TCPRule(true), makeRule("evildomain.com")}), DropAction())
```

The `BPFFilter:attachToAllBinds()` method attaches the filter to every existing bind at runtime, but it's also possible to define a default BPF filter at configuration time, so it's automatically attached to every bind:

```
bpf = newBPFFilter(1024, 1024, 1024)
setDefaultBPFFilter(bpf)
```

Finally, it's also possible to attach it to specific binds at runtime:

```
> bpf = newBPFFilter(1024, 1024, 1024)
> showBinds()
#   Address                Protocol  Queries
0   [::]:53                 UDP       0
1   [::]:53                 TCP       0
> bd = getBind(0)
> bd:attachFilter(bpf)
```

dnscat also supports adding dynamic, expiring blocks to a BPF filter:

```
bpf = newBPFFilter(1024, 1024, 1024)
setDefaultBPFFilter(bpf)
dbpf = newDynBPFFilter(bpf)
function maintenance()
    addBPFFilterDynBlocks(exceedQRate(20, 10), dbpf, 60)
    dbpf:purgeExpired()
end
```

This will dynamically block all hosts that exceeded 20 queries/s as measured over the past 10 seconds, and the dynamic block will last for 60 seconds.

The dynamic eBPF blocks and the number of queries they blocked can be seen in the web interface and retrieved from the API. Note however that eBPF dynamic objects need to be registered before they appear in the web

interface or the API, using the `registerDynBPFFilter()` function:

```
registerDynBPFFilter(dbpf)
```

They can be unregistered at a later point using the `unregisterDynBPFFilter()` function.

This feature has been successfully tested on Arch Linux, Arch Linux ARM, Fedora Core 23 and Ubuntu Xenial

15.8 Performance Tuning

First, a few words about **dnscdist** architecture:

- Each local bind has its own thread listening for incoming UDP queries
- and its own thread listening for incoming TCP connections, dispatching them right away to a pool of threads
- Each backend has its own thread listening for UDP responses
- A maintenance thread calls the `maintenance()` Lua function every second if any, and is responsible for cleaning the cache
- A health check thread checks the backends availability
- A control thread handles console connections
- A carbon thread exports statistics to carbon servers if needed
- One or more webservice threads handle queries to the internal webservice

The maximum number of threads in the TCP pool is controlled by the `setMaxTCPClientThreads()` directive, and defaults to 10. This number can be increased to handle a large number of simultaneous TCP connections. If all the TCP threads are busy, new TCP connections are queued while they wait to be picked up. Before 1.4.0, a TCP thread could only handle a single incoming connection at a time. Starting with 1.4.0 the handling of TCP connections is now event-based, so a single TCP worker can handle a large number of TCP incoming connections simultaneously.

The maximum number of queued connections can be configured with `setMaxTCPQueuedConnections()` and defaults to 1000. Any value larger than 0 will cause new connections to be dropped if there are already too many queued. By default, every TCP worker thread has its own queue, and the incoming TCP connections are dispatched to TCP workers on a round-robin basis. This might cause issues if some connections are taking a very long time, since incoming ones will be waiting until the TCP worker they have been assigned to has finished handling its current query, while other TCP workers might be available.

The experimental `setTCPUseSinglePipe()` directive can be used so that all the incoming TCP connections are put into a single queue and handled by the first TCP worker available.

When dispatching UDP queries to backend servers, dnscdist keeps track of at most **n** outstanding queries for each backend. This number **n** can be tuned by the `setMaxUDPOutstanding()` directive, defaulting to 10240, with a maximum value of 65535. Large installations are advised to increase the default value at the cost of a slightly increased memory usage.

Most of the query processing is done in C++ for maximum performance, but some operations are executed in Lua for maximum flexibility:

- Rules added by `addLuaAction()`
- Server selection policies defined via `setServerPolicyLua()` or `newServerPolicy()`

While Lua is fast, its use should be restricted to the strict necessary in order to achieve maximum performance, it might be worth considering using LuaJIT instead of Lua. When Lua inspection is needed, the best course of action is to restrict the queries sent to Lua inspection by using `addLuaAction()` with a selector.

dnscdist design choices mean that the processing of UDP queries is done by only one thread per local bind. This is great to keep lock contention to a low level, but might not be optimal for setups using a lot of processing power, caused for example by a large number of complicated rules. To be able to use more CPU cores for UDP queries

processing, it is possible to use the `reusePort` parameter of the `addLocal()` and `setLocal()` directives to be able to add several identical local binds to dnscat:

```
addLocal("192.0.2.1:53", {reusePort=true})
addLocal("192.0.2.1:53", {reusePort=true})
addLocal("192.0.2.1:53", {reusePort=true})
addLocal("192.0.2.1:53", {reusePort=true})
```

dnscat will then add four identical local binds as if they were different IPs or ports, start four threads to handle incoming queries and let the kernel load balance those randomly to the threads, thus using four CPU cores for rules processing. Note that this requires `SO_REUSEPORT` support in the underlying operating system (added for example in Linux 3.9). Please also be aware that doing so will increase lock contention and might not therefore scale linearly. This is especially true for Lua-intensive setups, because Lua processing in dnscat is serialized by a unique lock for all threads.

Another possibility is to use the `reuseport` option to run several dnscat processes in parallel on the same host, thus avoiding the lock contention issue at the cost of having to deal with the fact that the different processes will not share information, like statistics or DDoS offenders.

The UDP threads handling the responses from the backends do not use a lot of CPU, but if needed it is also possible to add the same backend several times to the dnscat configuration to distribute the load over several responder threads:

```
newServer({address="192.0.2.127:53", name="Backend1"})
newServer({address="192.0.2.127:53", name="Backend2"})
newServer({address="192.0.2.127:53", name="Backend3"})
newServer({address="192.0.2.127:53", name="Backend4"})
```

15.9 SNMP support

dnscat supports exporting statistics and sending traps over SNMP when compiled with Net-SNMP support, acting as an AgentX subagent. SNMP support is enabled via the `snmpAgent()` directive.

By default, the only traps sent when Traps are enabled, are backend status change notifications. But custom traps can also be sent:

- from Lua, with `sendCustomTrap()` and `DNSQuestion:sendTrap()`
- For selected queries and responses, using `SNMPTrapAction()` and `SNMPTrapResponseAction()`

Net-SNMP `snmpd` doesn't accept subagent connections by default, so to use the SNMP features of **dnscat** the following line should be added to the `snmpd.conf` configuration file:

```
master agentx
```

In addition to that, the permissions on the resulting socket might need to be adjusted so that the dnscat user can write to it. This can be done with the following lines in `snmpd.conf` (assuming dnscat is running as `dnscat:dnscat`):

```
agentxperms 0700 0700 dnscat dnscat
```

In order to allow the retrieval of statistics via SNMP, `snmpd`'s access control has to be configured. A very simple SNMPv2c setup only needs the configuration of a read-only community in `snmpd.conf`:

```
rocommunity dnscat42
```

`snmpd` also supports more secure SNMPv3 setup, using for example the `createUser` and `rouser` directives:

```
createUser myuser SHA "my auth key" AES "my enc key"
rouser myuser
```

snmpd can be instructed to send SNMPv2 traps to a remote SNMP trap receiver by adding the following directive to the `snmpd.conf` configuration file:

```
trap2sink 192.0.2.1
```

The description of **dnsdist**'s SNMP MIB is as follows:

```
-- *- snmpv2 *-
-----
-- MIB file for dnsdist
-----

DNSDIST-MIB DEFINITIONS ::= BEGIN

IMPORTS
    OBJECT-TYPE, MODULE-IDENTITY, enterprises,
    Counter64, Unsigned32, NOTIFICATION-TYPE
        FROM SNMPv2-SMI
    CounterBasedGauge64
        FROM HCNUM-TC
    Float64TC
        FROM FLOAT-TC-MIB
    OBJECT-GROUP, MODULE-COMPLIANCE, NOTIFICATION-GROUP
        FROM SNMPv2-CONF
    InetAddressType
        FROM INET-ADDRESS-MIB
    TEXTUAL-CONVENTION, DisplayString
        FROM SNMPv2-TC;

dnsdist MODULE-IDENTITY
    LAST-UPDATED "201611080000Z"
    ORGANIZATION "PowerDNS BV"
    CONTACT-INFO "support@powerdns.com"
    DESCRIPTION
        "This MIB module describes information gathered through dnsdist."

    REVISION "201611080000Z"
    DESCRIPTION "Initial revision."

    ::= { powerdns 3 }

powerdns          OBJECT IDENTIFIER ::= { enterprises 43315 }

stats OBJECT IDENTIFIER ::= { dnsdist 1 }

queries OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries received"
    ::= { stats 1 }

responses OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of responses received"
    ::= { stats 2 }

servfailResponses OBJECT-TYPE
```

(continues on next page)

(continued from previous page)

```
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Number of servfail responses received"
 ::= { stats 3 }

aclDrops OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries dropped because of the ACL"
    ::= { stats 4 }

-- stats 5 was a BlockFilter Counter, removed in 1.2.0

ruleDrop OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries dropped because of a rule"
    ::= { stats 6 }

ruleNXDomain OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of NXDomain responses returned because of a rule"
    ::= { stats 7 }

ruleRefused OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of Refused responses returned because of a rule"
    ::= { stats 8 }

selfAnswered OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of self-answered responses"
    ::= { stats 9 }

downstreamTimeouts OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of downstream timeouts"
    ::= { stats 10 }

downstreamSendErrors OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
```

(continues on next page)

```
DESCRIPTION
    "Number of downstream send errors"
    ::= { stats 11 }

truncFailures OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of errors while truncating a response"
    ::= { stats 12 }

noPolicy OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries dropped because no server was available"
    ::= { stats 13 }

latency01 OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries answered in less than 1 ms"
    ::= { stats 14 }

latency110 OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries answered in 1-10 ms"
    ::= { stats 15 }

latency1050 OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries answered in 10-50 ms"
    ::= { stats 16 }

latency50100 OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries answered in 50-100 ms"
    ::= { stats 17 }

latency1001000 OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries answered in 100-1000 ms"
    ::= { stats 18 }

latencySlow OBJECT-TYPE
```

(continues on next page)

(continued from previous page)

```
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Number of queries answered in more than 1s"
 ::= { stats 19 }

latencyAVG100 OBJECT-TYPE
SYNTAX Float64TC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Average latency over the last 100 queries"
 ::= { stats 20 }

latencyAVG1000 OBJECT-TYPE
SYNTAX Float64TC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Average latency over the last 1000 queries"
 ::= { stats 21 }

latencyAVG10000 OBJECT-TYPE
SYNTAX Float64TC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Average latency over the last 10000 queries"
 ::= { stats 22 }

latencyAVG100000 OBJECT-TYPE
SYNTAX Float64TC
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Average latency over the last 100000 queries"
 ::= { stats 23 }

uptime OBJECT-TYPE
SYNTAX CounterBasedGauge64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Uptime of the dnsmist process, in seconds"
 ::= { stats 24 }

realMemoryUsage OBJECT-TYPE
SYNTAX CounterBasedGauge64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Memory usage"
 ::= { stats 25 }

nonCompliantQueries OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "Number of queries dropped as non-compliant"
```

(continues on next page)

```
 ::= { stats 26 }

nonCompliantResponses OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of responses dropped as non-compliant"
    ::= { stats 27 }

rdQueries OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries with the RD flag set"
    ::= { stats 28 }

emptyQueries OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of empty queries received"
    ::= { stats 29 }

cacheHits OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of cache hits"
    ::= { stats 30 }

cacheMisses OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of cache misses"
    ::= { stats 31 }

cpuUserMSec OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "CPU Usage (user)"
    ::= { stats 32 }

cpuSysMSec OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "CPU Usage (sys)"
    ::= { stats 33 }

fdUsage OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
```

(continues on next page)

(continued from previous page)

```

STATUS current
DESCRIPTION
    "Number of file descriptors"
 ::= { stats 34 }

dynBlocked OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries dropped because of a dynamic block"
    ::= { stats 35 }

dynBlockNMGSize OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Dynamic blocks (NMG) size"
    ::= { stats 36 }

ruleServFail OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of ServFail responses returned because of a rule"
    ::= { stats 37 }

specialMemoryUsage OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Memory usage (more precise but expensive to retrieve)"
    ::= { stats 38 }

securityStatus OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Security status of this software. 0=unknown, 1=OK, 2=upgrade recommended,
        ↪3=upgrade mandatory"
    ::= { stats 38 }

backendStatTable OBJECT-TYPE
    SYNTAX SEQUENCE OF BackendStatEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION "Statistics for backends"
    ::= { dnsdist 2 }

backendStatEntry OBJECT-TYPE
    SYNTAX BackendStatEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION "Statistics for one backend"
    INDEX { backendId }
    ::= { backendStatTable 1 }

```

(continues on next page)

```
BackendStatEntry ::= SEQUENCE {
    backendId          Unsigned32,
    backendName        DisplayString,
    backendLatency     CounterBasedGauge64,
    backendWeight      CounterBasedGauge64,
    backendOutstanding CounterBasedGauge64,
    backendQPSLimit    CounterBasedGauge64,
    backendReused      Counter64,
    backendState       DisplayString,
    backendAddress     OCTET STRING,
    backendPools       DisplayString,
    backendQPS         CounterBasedGauge64,
    backendQueries     Counter64,
    backendOrder       CounterBasedGauge64
}
```

```
backendId OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Backend ID"
    ::= { backendStatEntry 1 }
```

```
backendName OBJECT-TYPE
    SYNTAX DisplayString
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend name"
    ::= { backendStatEntry 2 }
```

```
backendLatency OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend latency"
    ::= { backendStatEntry 3 }
```

```
backendWeight OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend weight"
    ::= { backendStatEntry 4 }
```

```
backendOutstanding OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend outstanding queries"
    ::= { backendStatEntry 5 }
```

```
backendQPSLimit OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
```

(continued from previous page)

```

    "Backend QPS limit"
    ::= { backendStatEntry 6 }

backendReused OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend reused slots"
    ::= { backendStatEntry 7 }

backendState OBJECT-TYPE
    SYNTAX DisplayString
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend state"
    ::= { backendStatEntry 8 }

backendAddress OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (2..24))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend address"
    ::= { backendStatEntry 9 }

backendPools OBJECT-TYPE
    SYNTAX DisplayString
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "List of pools this backend belongs to"
    ::= { backendStatEntry 10 }

backendQPS OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend QPS"
    ::= { backendStatEntry 11 }

backendQueries OBJECT-TYPE
    SYNTAX Counter64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of queries sent to this backend"
    ::= { backendStatEntry 12 }

backendOrder OBJECT-TYPE
    SYNTAX CounterBasedGauge64
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Backend order"
    ::= { backendStatEntry 13 }

---
--- Textual Conventions

```

(continues on next page)

```
---
SocketProtocolType ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "A value that represents a type of socket protocol."
    SYNTAX      INTEGER {
                unknown(0),
                udp(1),
                tcp(2)
                }

DNSQueryType ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "A value that represents a type of DNS query (question or response)."
    SYNTAX      INTEGER {
                unknown(0),
                question(1),
                response(2)
                }

---
--- Traps / Notifications
---

trap OBJECT IDENTIFIER ::= { dnsdist 10 }
traps OBJECT IDENTIFIER ::= { trap 0 } --- reverse-mappable
trapObjects OBJECT IDENTIFIER ::= { dnsdist 11 }

socketFamily OBJECT-TYPE
    SYNTAX InetAddressType
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Socket family type"
    ::= { trapObjects 1 }

socketProtocol OBJECT-TYPE
    SYNTAX SocketProtocolType
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Socket protocol type"
    ::= { trapObjects 2 }

fromAddress OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (2..24))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Requestor address"
    ::= { trapObjects 3 }

toAddress OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (2..24))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Responder address"
    ::= { trapObjects 4 }
```

(continues on next page)

(continued from previous page)

```
queryType OBJECT-TYPE
    SYNTAX DNSQueryType
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Query / Response"
    ::= { trapObjects 5 }

querySize OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Size in bytes"
    ::= { trapObjects 6 }

queryID OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "DNS query ID"
    ::= { trapObjects 7 }

qName OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE (0..255))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "DNS qname"
    ::= { trapObjects 8 }

qClass OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "DNS query class"
    ::= { trapObjects 9 }

qType OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "DNS query type"
    ::= { trapObjects 10 }

trapReason OBJECT-TYPE
    SYNTAX OCTET STRING
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Reason for this trap"
    ::= { trapObjects 11 }

backendStatusChangeTrap NOTIFICATION-TYPE
    OBJECTS {
        backendName,
        backendAddress,
```

(continues on next page)

```

        backendState
    }
    STATUS current
    DESCRIPTION "Backend status changed"
    ::= { traps 1 }

actionTrap NOTIFICATION-TYPE
    OBJECTS {
        socketFamily,
        socketProtocol,
        fromAddress,
        toAddress,
        queryType,
        querySize,
        queryID,
        qName,
        qClass,
        qType,
        trapReason
    }
    STATUS current
    DESCRIPTION "Trap sent by SNMPTrapAction"
    ::= { traps 2 }

customTrap NOTIFICATION-TYPE
    OBJECTS {
        trapReason
    }
    STATUS current
    DESCRIPTION "Trap sent by sendCustomTrap"
    ::= { traps 3 }

---
--- Conformance
---

dnsdistConformance OBJECT IDENTIFIER ::= { dnsdist 100 }

dnsdistCompliances MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION "dnsdist compliance statement"
    MODULE
    MANDATORY-GROUPS {
        dnsdistGroup,
        dnsdistTrapsGroup
    }
    ::= { dnsdistConformance 1 }

dnsdistGroup OBJECT-GROUP
    OBJECTS {
        queries,
        responses,
        servfailResponses,
        aclDrops,
        ruleDrop,
        ruleNXDomain,
        ruleRefused,
        selfAnswered,
        downstreamTimeouts,
        downstreamSendErrors,
        truncFailures,

```


(continued from previous page)

```

noPolicy,
latency01,
latency110,
latency1050,
latency50100,
latency1001000,
latencySlow,
latencyAVG100,
latencyAVG1000,
latencyAVG10000,
latencyAVG1000000,
uptime,
realMemoryUsage,
specialMemoryUsage,
nonCompliantQueries,
nonCompliantResponses,
rdQueries,
emptyQueries,
cacheHits,
cacheMisses,
cpuUserMSec,
cpuSysMSec,
fdUsage,
dynBlocked,
dynBlockNMGSize,
securityStatus,
backendName,
backendLatency,
backendWeight,
backendOutstanding,
backendQPSPLimit,
backendReused,
backendState,
backendAddress,
backendPools,
backendQPS,
backendQueries,
backendOrder,
socketFamily,
socketProtocol,
fromAddress,
toAddress,
queryType,
querySize,
queryID,
qName,
qClass,
qType,
trapReason
}
STATUS current
DESCRIPTION "Objects conformance group for dnsmist"
::= { dnsmistConformance 2 }

dnsmistTrapsGroup NOTIFICATION-GROUP
NOTIFICATIONS {
    actionTrap,
    customTrap,
    backendStatusChangeTrap
}
STATUS current

```

(continues on next page)

```
DESCRIPTION "Traps conformance group for dnssdist"
::= { dnssdistConformance 3 }

END
```

15.10 AXFR, IXFR and NOTIFY

When **dnssdist** is deployed in front of a master authoritative server, it might receive AXFR or IXFR queries destined to this master. There are two issues that can arise in this kind of setup:

- If the master is part of a pool of servers, the first SOA query can be directed by **dnssdist** to a different server than the following AXFR/IXFR one, which might fail if the servers are not perfectly synchronised.
- If the master only allows AXFR/IXFR based on the source address of the requestor, it might be confused by the fact that the source address will be the one from the **dnssdist** server.

The first issue can be solved by routing SOA, AXFR and IXFR requests explicitly to the master:

```
newServer({address="192.168.1.2", name="master", pool={"master", "otherpool"}})
addAction(OrRule({QTypeRule(DNSQType.SOA), QTypeRule(DNSQType.AXFR), ↵
↵QTypeRule(DNSQType.IXFR)}), PoolAction("master"))
```

The second one might require allowing AXFR/IXFR from the **dnssdist** source address and moving the source address check to **dnssdist**'s side:

```
addAction(AndRule({OrRule({QTypeRule(DNSQType.AXFR), QTypeRule(DNSQType.IXFR)}), ↵
↵NotRule(makeRule("192.168.1.0/24"))}), RCodeAction(DNSRCode.REFUSED))
```

Changed in version 1.4.0: Before 1.4.0, the QTypes were in the **dnssdist** namespace. Use **dnssdist.AXFR** and **dnssdist.IXFR** in these versions. Before 1.4.0, the RCodes were in the **dnssdist** namespace. Use **dnssdist.REFUSED** in these versions.

When **dnssdist** is deployed in front of slaves, however, an issue might arise with NOTIFY queries, because the slave will receive a notification coming from the **dnssdist** address, and not the master's one. One way to fix this issue is to allow NOTIFY from the **dnssdist** address on the slave side (for example with PowerDNS's *trusted-notification-proxy*) and move the address check to **dnssdist**'s side:

```
addAction(AndRule({OpcodeRule(DNSOpcode.Notify), NotRule(makeRule("192.168.1.0/24 ↵
↵"))}), RCodeAction(DNSRCode.REFUSED))
```

Changed in version 1.4.0: Before 1.4.0, the RCodes were in the **dnssdist** namespace. Use **dnssdist.REFUSED** in these versions.

15.11 Running multiple instances

Sometimes, it can be advantageous to run multiple instances of **dnssdist**. Usecases can be:

- Multiple inbound IP addresses with different rulesets
- Taking advantage of more processes, using **SO_REUSEPORT**

dnssdist supports loading a different configuration file with the `--config` command line switch.

By default, `SYSCONFDIR/dnssdist.conf` is loaded. `SYSCONFDIR` is usually `/etc` or `/etc/dnssdist`.

15.11.1 Using systemd

New in version 1.3.0.

On systems with systemd, instance services can be used. To create a dnstest service named `foo`, create a `dnstest-foo.conf` in `SYSCONFDIR`, then run `systemctl enable dnstest@foo.service` and `systemctl start dnstest@foo.service`.

REFERENCE GUIDES

These chapters contain extensive information on all functions and object available in dnsmdist.

16.1 Configuration Reference

This page lists all configuration options for dnsmdist.

Note: When an IPv6 IP:PORT combination is needed, the bracketed syntax from [RFC 3986](#) should be used. e.g. “[2001:DB8:14::COFF:FEE]:5300”.

16.1.1 Functions and Types

Within dnsmdist several core object types exist:

- *Server*: generated with `newServer()`, represents a downstream server
- *ComboAddress*: represents an IP address and port
- *DNSName*: represents a domain name
- *NetmaskGroup*: represents a group of netmasks
- *QPSLimiter*: implements a QPS-based filter
- *SuffixMatchNode*: represents a group of domain suffixes for rapid testing of membership
- *DNSHeader*: represents the header of a DNS packet, see *DNSHeader (dh) object*
- *ClientState*: sometimes also called Bind or Frontend, represents the addresses and ports dnsmdist is listening on

The existence of most of these objects can mostly be ignored, unless you plan to write your own hooks and policies, but it helps to understand an expressions like:

```
getServer(0).order=12          -- set order of server 0 to 12
getServer(0):addPool("abuse") -- add this server to the abuse pool
```

The `.` means `order` is a data member, while the `:` means `addPool` is a member function.

16.1.2 Global configuration

includeDirectory (*path*)

Include configuration files from *path*.

Parameters *path* (*str*) – The directory to load configuration files from. Each file must end in `.conf`.

reloadAllCertificates ()

New in version 1.4.0.

Reload all DNSCrypt and TLS certificates, along with their associated keys.

setSyslogFacility (facility)

New in version 1.4.0.

Set the syslog logging facility to *facility*.

Parameters *facility* (*int*) – The new facility as a numeric value. Defaults to LOG_DAEMON.

Listen Sockets

addLocal (address[, options])

New in version 1.2.0.

Changed in version 1.3.0: Added *cpus* to the options.

Add to the list of listen addresses.

Parameters

- **address** (*str*) – The IP Address with an optional port to listen on. The default port is 53.
- **options** (*table*) – A table with key: value pairs with listen options.

Options:

- **doTCP=true**: *bool* - Also bind on TCP on *address*.
- **reusePort=false**: *bool* - Set the SO_REUSEPORT socket option.
- **tcpFastOpenSize=0**: *int* - Set the TCP Fast Open queue size, enabling TCP Fast Open when available and the value is larger than 0.
- **interface=""**: *str* - Set the network interface to use.
- **cpus={}**: *table* - Set the CPU affinity for this listener thread, asking the scheduler to run it on a single CPU id, or a set of CPU ids. This parameter is only available if the OS provides the `pthread_setaffinity_np()` function.

```
addLocal('0.0.0.0:5300', { doTCP=true, reusePort=true })
```

This will bind to both UDP and TCP on port 5300 with SO_REUSEPORT enabled.

addLocal (address[[[do_tcp], so_reuseport], tcp_fast_open_qsize])

Deprecated since version 1.2.0.

Add to the list of addresses listened on.

Parameters

- **address** (*str*) – The IP Address with an optional port to listen on. The default port is 53.
- **do_tcp** (*bool*) – Also bind a TCP port on *address*, defaults to true.
- **so_reuseport** (*bool*) – Use SO_REUSEPORT if it is available, defaults to false
- **tcp_fast_open_qsize** (*int*) – The size of the TCP Fast Open queue. Set to a number higher than 0 to enable TCP Fast Open when available. Default is 0.

addDOHLocal (address, certFile(s), keyFile(s)[, urls[, options]])

New in version 1.4.0.

Listen on the specified address and TCP port for incoming DNS over HTTPS connections, presenting the specified X.509 certificate.

Parameters

- **address** (*str*) – The IP Address with an optional port to listen on. The default port is 443.
- **certFile(s)** (*str*) – The path to a X.509 certificate file in PEM format, or a list of paths to such files.
- **keyFile(s)** (*str*) – The path to the private key file corresponding to the certificate, or a list of paths to such files, whose order should match the certFile(s) ones.
- **or list urls** (*str*) – A base URL, or a list of base URLs, to accept queries on. Any query with a path under one of these will be treated as a DoH query. The default is `/`.
- **options** (*table*) – A table with key: value pairs with listen options.

Options:

- `reusePort=false`: `bool` - Set the `SO_REUSEPORT` socket option.
- `tcpFastOpenSize=0`: `int` - Set the TCP Fast Open queue size, enabling TCP Fast Open when available and the value is larger than 0.
- `interface=""`: `str` - Set the network interface to use.
- `cpus={}`: `table` - Set the CPU affinity for this listener thread, asking the scheduler to run it on a single CPU id, or a set of CPU ids. This parameter is only available if the OS provides the `pthread_setaffinity_np()` function.
- `idleTimeout=30`: `int` - Set the idle timeout, in seconds.
- `ciphers`: `str` - The TLS ciphers to use, in OpenSSL format. Ciphers for TLS 1.3 must be specified via `ciphersTLS13`.
- `ciphersTLS13`: `str` - The TLS ciphers to use for TLS 1.3, in OpenSSL format.
- `serverTokens`: `str` - The content of the Server: HTTP header returned by dnsmdist. The default is "h2o/dnsmdist".

addTLSTLocal (*address, certFile(s), keyFile(s)*[, *options*])

New in version 1.3.0.

Changed in version 1.3.1: `certFile(s)` and `keyFile(s)` parameters accept a list of files. `sessionTickets` option added.

Changed in version 1.3.3: `numberOfStoredSessions` option added.

Changed in version 1.4.0: `ciphersTLS13` option added.

Listen on the specified address and TCP port for incoming DNS over TLS connections, presenting the specified X.509 certificate.

Parameters

- **address** (*str*) – The IP Address with an optional port to listen on. The default port is 853.
- **certFile(s)** (*str*) – The path to a X.509 certificate file in PEM format, or a list of paths to such files.
- **keyFile(s)** (*str*) – The path to the private key file corresponding to the certificate, or a list of paths to such files, whose order should match the certFile(s) ones.
- **options** (*table*) – A table with key: value pairs with listen options.

Options:

- `reusePort=false`: `bool` - Set the `SO_REUSEPORT` socket option.
- `tcpFastOpenSize=0`: `int` - Set the TCP Fast Open queue size, enabling TCP Fast Open when available and the value is larger than 0.

- `interface=""`: str - Set the network interface to use.
- `cpus={}`: table - Set the CPU affinity for this listener thread, asking the scheduler to run it on a single CPU id, or a set of CPU ids. This parameter is only available if the OS provides the `pthread_setaffinity_np()` function.
- `provider`: str - The TLS library to use between GnuTLS and OpenSSL, if they were available and enabled at compilation time.
- `ciphers`: str - The TLS ciphers to use. The exact format depends on the provider used. When the OpenSSL provider is used, ciphers for TLS 1.3 must be specified via `ciphersTLS13`.
- `ciphersTLS13`: str - The ciphers to use for TLS 1.3, when the OpenSSL provider is used. When the GnuTLS provider is used, `ciphers` applies regardless of the TLS protocol and this setting is not used.
- `numberOfTicketsKeys`: int - The maximum number of tickets keys to keep in memory at the same time, if the provider supports it (GnuTLS doesn't, OpenSSL does). Only one key is marked as active and used to encrypt new tickets while the remaining ones can still be used to decrypt existing tickets after a rotation. Default to 5.
- `ticketKeyFile`: str - The path to a file from where TLS tickets keys should be loaded, to support RFC 5077. These keys should be rotated often and never written to persistent storage to preserve forward secrecy. The default is to generate a random key. The OpenSSL provider supports several tickets keys to be able to decrypt existing sessions after the rotation, while the GnuTLS provider only supports one key.
- `ticketsKeysRotationDelay`: int - Set the delay before the TLS tickets key is rotated, in seconds. Default is 43200 (12h).
- `sessionTickets`: bool - Whether session resumption via session tickets is enabled. Default is true, meaning tickets are enabled.
- `numberOfStoredSessions`: int - The maximum number of sessions kept in memory at the same time. At this time this is only supported by the OpenSSL provider, as stored sessions are not supported with the GnuTLS one. Default is 20480. Setting this value to 0 disables stored session entirely.

setLocal (*address*[, *options*])

New in version 1.2.0.

Remove the list of listen addresses and add a new one.

Parameters

- **address** (*str*) – The IP Address with an optional port to listen on. The default port is 53.
- **options** (*table*) – A table with key: value pairs with listen options.

The options that can be set are the same as `addLocal()`.

setLocal (*address*[[, *do_tcp*], *so_reuseport*], *tcp_fast_open_qsize*)

Deprecated since version 1.2.0.

Remove the list of listen addresses and add a new one.

Parameters

- **address** (*str*) – The IP Address with an optional port to listen on. The default port is 53.
- **do_tcp** (*bool*) – Also bind a TCP port on address, defaults to true.
- **so_reuseport** (*bool*) – Use SO_REUSEPORT if it is available, defaults to false
- **tcp_fast_open_qsize** (*int*) – The size of the TCP Fast Open queue. Set to a number higher than 0 to enable TCP Fast Open when available. Default is 0.

Control Socket, Console and Webserver

addConsoleACL (*netmask*)

New in version 1.3.0.

Add a netmask to the existing console ACL, allowing remote clients to connect to the console. Please make sure that encryption has been enabled with *setKey()* before doing so. The default is to only allow 127.0.0.1/8 and ::1/128.

Parameters **netmask** (*str*) – A CIDR netmask, e.g. "192.0.2.0/24". Without a subnetmask, only the specific address is allowed.

controlSocket (*address*)

Bind to *addr* and listen for a connection for the console. Since 1.3.0 only connections from local users are allowed by default, *addConsoleACL()* and *setConsoleACL()* can be used to enable remote connections. Please make sure that encryption has been enabled with *setKey()* before doing so. Enabling encryption is also strongly advised for local connections, since not enabling it allows any local user to connect to the console.

Parameters **address** (*str*) – An IP address with optional port. By default, the port is 5199.

inClientStartup ()

Returns true while the console client is parsing the configuration.

makeKey ()

Generate and print an encryption key.

setConsoleConnectionsLogging (*enabled*)

New in version 1.2.0.

Whether to log the opening and closing of console connections.

Parameters **enabled** (*bool*) – Default to true.

setKey (*key*)

Use *key* as shared secret between the client and the server

Parameters **key** (*str*) – An encoded key, as generated by *makeKey()*

setConsoleACL (*netmasks*)

New in version 1.3.0.

Remove the existing console ACL and add the netmasks from the table, allowing remote clients to connect to the console. Please make sure that encryption has been enabled with *setKey()* before doing so.

Parameters **netmasks** (*{str}*) – A table of CIDR netmask, e.g. {"192.0.2.0/24", "2001:DB8:14::/56"}. Without a subnetmask, only the specific address is allowed.

showConsoleACL ()

Print a list of all netmasks allowed to connect to the console.

testCrypto ()

Test the crypto code, will report errors when something is not ok.

setConsoleOutputMaxMsgSize (*size*)

New in version 1.3.3.

Set the maximum size in bytes of a single console message, default set to 10 MB.

Parameters **size** (*int*) – The new maximum size.

Webserver configuration

webserver (*listen_address*, *password*[, *apikey*[, *custom_headers*]])

Launch the *Built-in webserver* with statistics and the API.

Parameters

- **listen_address** (*str*) – The IP address and Port to listen on
- **password** (*str*) – The password required to access the webserver
- **apikey** (*str*) – The key required to access the API
- **custom_headers** (*{ [str]=str, ... }*) – Allows setting custom headers and removing the defaults

setAPIWritable (*allow* [, *dir*])

Allow modifications via the API. Optionally saving these changes to disk. Modifications done via the API will not be written to the configuration by default and will not persist after a reload

Parameters

- **allow** (*bool*) – Set to true to allow modification through the API
- **dir** (*str*) – A valid directory where the configuration files will be written by the API.

setWebserverConfig (*options*)

New in version 1.3.3.

Setup webserver configuration. See *webserver()*.

Parameters options (*table*) – A table with key: value pairs with webserver options.

Options:

- **password=newPassword**: string - Changes the API password
- **apikey=newKey**: string - Changes the API Key (set to an empty string do disable it)
- **custom_headers={ [str]=str, ... }**: map of string - Allows setting custom headers and removing the defaults.

Access Control Lists

addACL (*netmask*)

Add a netmask to the existing ACL controlling which clients can send UDP, TCP, DNS over TLS and DNS over HTTPS queries. See *Access Control* for more information.

Parameters netmask (*str*) – A CIDR netmask, e.g. "192.0.2.0/24". Without a subnetmask, only the specific address is allowed.

setACL (*netmasks*)

Remove the existing ACL and add the netmasks from the table of those allowed to send UDP, TCP, DNS over TLS and DNS over HTTPS queries. See *Access Control* for more information.

Parameters netmasks (*{str}*) – A table of CIDR netmask, e.g. {"192.0.2.0/24", "2001:DB8:14::/56"}. Without a subnetmask, only the specific address is allowed.

showACL ()

Print a list of all netmasks allowed to send queries over UDP, TCP, DNS over TLS and DNS over HTTPS. See *Access Control* for more information.

EDNS Client Subnet

setECSOverride (*bool*)

When useClientSubnet in *newServer()* is set and dnsmdist adds an EDNS Client Subnet Client option to the query, override an existing option already present in the query, if any

Parameters bool – Whether to override an existing EDNS Client Subnet option present in the query. Defaults to false

setECSSourcePrefixV4 (*prefix*)

When useClientSubnet in *newServer()* is set and dnsmdist adds an EDNS Client Subnet Client option to the query, truncate the requestors IPv4 address to *prefix* bits

Parameters `prefix (int)` – The prefix length

setECSSourcePrefixV6 (*prefix*)

When `useClientSubnet` in `newServer()` is set and dnscat adds an EDNS Client Subnet Client option to the query, truncate the requestor's IPv6 address to bits

Parameters `prefix (int)` – The prefix length

Ringbuffers

setRingBuffersLockRetries (*num*)

New in version 1.3.0.

Set the number of shards to attempt to lock without blocking before giving up and simply blocking while waiting for the next shard to be available

Parameters `num (int)` – The maximum number of attempts. Defaults to 5 if there is more than one shard, 0 otherwise.

setRingBuffersSize (*num* [, *numberOfShards*])

Changed in version 1.3.0: `numberOfShards` optional parameter added.

Set the capacity of the ringbuffers used for live traffic inspection to `num`, and the number of shards to `numberOfShards` if specified.

Parameters

- **num** (*int*) – The maximum amount of queries to keep in the ringbuffer. Defaults to 10000
- **numberOfShards** (*int*) – the number of shards to use to limit lock contention. Defaults to 1

16.1.3 Servers

newServer (*server_string*)

newServer (*server_table*)

Changed in version 1.3.0: Added `checkClass`, `sockets` and `checkFunction` to `server_table`.

Changed in version 1.4.0: Added `checkInterval`, `checkTimeout` and `rise` to `server_table`.

Add a new backend server. Call this function with either a string:

```
newServer (
  "IP:PORT" -- IP and PORT of the backend server
)
```

or a table:

```
newServer({
  address="IP:PORT",      -- IP and PORT of the backend server (mandatory)
  id=STRING,              -- Use a pre-defined UUID instead of a random one
  qps=NUM,                -- Limit the number of queries per second to NUM,
  ↪when using the `firstAvailable` policy
  order=NUM,              -- The order of this server, used by the
  ↪`leastOustanding` and `firstAvailable` policies
  weight=NUM,             -- The weight of this server, used by the `wrandom`,
  ↪`whashed` and `chashed` policies, default: 1
                          -- Supported values are a minimum of 1, and a maximum
  ↪of 2147483647.
  pool=STRING|{STRING},  -- The pools this server belongs to (unset or empty
  ↪string means default pool) as a string or table of strings
  retries=NUM,           -- The number of TCP connection attempts to the
  ↪backend, for a given query
```

(continues on next page)

(continued from previous page)

```

tcpConnectTimeout=NUM, -- The timeout (in seconds) of a TCP connection,
↳attempt
tcpSendTimeout=NUM,    -- The timeout (in seconds) of a TCP write attempt
tcpRecvTimeout=NUM,   -- The timeout (in seconds) of a TCP read attempt
tcpFastOpen=BOOL,     -- Whether to enable TCP Fast Open
ipBindAddrNoPort=BOOL, -- Whether to enable IP_BIND_ADDRESS_NO_PORT if,
↳available, default: true
name=STRING,          -- The name associated to this backend, for display,
↳purpose
checkClass=NUM,       -- Use NUM as QCLASS in the health-check query,
↳default: DNSClass.IN
checkName=STRING,     -- Use STRING as QNAME in the health-check query,
↳default: "a.root-servers.net."
checkType=STRING,     -- Use STRING as QTYPE in the health-check query,
↳default: "A"
checkFunction=FUNCTION, -- Use this function to dynamically set the QNAME,
↳QTYPE and QCLASS to use in the health-check query (see :ref:`Healthcheck`)
checkTimeout=NUM,     -- The timeout (in milliseconds) of a health-check,
↳query, default: 1000 (1s)
setCD=BOOL,           -- Set the CD (Checking Disabled) flag in the health-
↳check query, default: false
maxCheckFailures=NUM, -- Allow NUM check failures before declaring the,
↳backend down, default: 1
checkInterval=NUM     -- The time in seconds between health checks
mustResolve=BOOL,     -- Set to true when the health check MUST return a,
↳NOERROR RCODE and an answer
useClientSubnet=BOOL, -- Add the client's IP address in the EDNS Client,
↳Subnet option when forwarding the query to this backend
source=STRING,        -- The source address or interface to use for queries,
↳to this backend, by default this is left to the kernel's address selection
-- The following formats are supported:
-- "address", e.g. "192.0.2.2"
-- "interface name", e.g. "eth0"
-- "address@interface", e.g. "192.0.2.2@eth0"
addXPF=NUM,           -- Add the client's IP address and port to the query,
↳along with the original destination address and port,
-- using the experimental XPF record from `draft-
↳bellis-dnsop-xpf <https://datatracker.ietf.org/doc/draft-bellis-dnsop-xpf/>`_
↳and the specified option code. Default is disabled (0)
sockets=NUM,          -- Number of sockets (and thus source ports) used,
↳toward the backend server, defaults to a single one
disableZeroScope=BOOL, -- Disable the EDNS Client Subnet 'zero scope',
↳feature, which does a cache lookup for an answer valid for all subnets (ECS,
↳scope of 0) before adding ECS information to the query and doing the regular,
↳lookup
rise=NUM              -- Require NUM consecutive successful checks before,
↳declaring the backend up, default: 1
})

```

Parameters

- **server_string** (*str*) – A simple IP:PORT string.
- **server_table** (*table*) – A table with at least a 'name' key

getServer (*index*) → *Server*

Get a *Server*

Parameters *index* (*int*) – The number of the server (as seen in *showServers*()).

Returns The *Server* object or nil

getServers ()

Returns a table with all defined servers.

rmServer (index)**rmServer (server)**

Remove a backend server.

Parameters

- **index** (*int*) – The number of the server (as seen in `showServers ()`).
- **server** (*Server*) – A *Server* object as returned by e.g. `getServer ()`.

Server Functions

A server object returned by `getServer ()` can be manipulated with these functions.

class Server

This object represents a backend server. It has several methods.

:addPool (pool)

Add this server to a pool.

Parameters **pool** (*str*) – The pool to add the server to

:getName () → string

Get the name of this server.

Returns The name of the server, or an empty string if it does not have one

:getNameWithAddr () → string

Get the name plus IP address and port of the server

Returns A string containing the server name if any plus the server address and port

:getOutstanding () → int

Get the number of outstanding queries for this server.

Returns The number of outstanding queries

:isUp () → bool

Returns the up status of the server

Returns true when the server is up, false otherwise

:rmPool (pool)

Removes the server from the named pool

Parameters **pool** (*str*) – The pool to remove the server from

:setAuto ([status])

Changed in version 1.3.0: *status* optional parameter added.

Set the server in the default auto state. This will enable health check queries that will set the server up and down appropriately.

Parameters **status** (*bool*) – Set the initial status of the server to up (true) or down (false) instead of using the last known status

:setQPS (limit)

Limit the queries per second for this server.

Parameters **limit** (*int*) – The maximum number of queries per second

:setDown ()

Set the server in an DOWN state. The server will not receive queries and the health checks are disabled

:setUp ()

Set the server in an UP state. This server will still receive queries and health checks are disabled

Apart from the functions, a *Server* object has these attributes:

name

The name of the server

upStatus

Whether or not this server is up or down

order

The order of the server

weight

The weight of the server

16.1.4 Pools

Servers can be part of any number of pools. Pools are automatically created when a server is added to a pool (with *newServer()*), or can be manually created with *addPool()*.

addPool (*name*) → *ServerPool*

Returns a *ServerPool*.

Parameters *name* (*string*) – The name of the pool to create

getPool (*name*) → *ServerPool*

Returns a *ServerPool* or nil.

Parameters *name* (*string*) – The name of the pool

getPoolServers (*name*) → [*Server*]

Returns a list of *Servers* or nil.

Parameters *name* (*string*) – The name of the pool

showPools ()

Display the name, associated cache, server policy and associated servers for every pool.

class ServerPool

This represents the pool where zero or more servers are part of.

:getCache () → *PacketCache*

Returns the *PacketCache* for this pool or nil.

:getECS ()

New in version 1.3.0.

Whether dnssdist will add EDNS Client Subnet information to the query before looking up into the cache, when all servers from this pool are down. For more information see *ServerPool:setECS()*.

:setCache (*cache*)

Adds cache as the pool's cache.

Parameters *cache* (*PacketCache*) – The new cache to add to the pool

:unsetCache ()

Removes the cache from this pool.

:setECS ()

New in version 1.3.0.

Set to true if dnssdist should add EDNS Client Subnet information to the query before looking up into the cache, when all servers from this pool are down. If at least one server is up, the preference of the selected server is used, this parameter is only useful if all the backends in this pool are down and have EDNS Client Subnet enabled, since the queries in the cache will have been inserted with ECS information. Default is false.

PacketCache

A Pool can have a packet cache to answer queries directly in stead of going to the backend. See [Caching Responses](#) for a how to.

newPacketCache (*maxEntries*[, *maxTTL=86400*[, *minTTL=0*[, *temporaryFailureTTL=60*[, *staleTTL=60*[, *dontAge=false*[, *numberOfShards=1*[, *deferrableInsertLock=true*[, *maxNegativeTTL=3600*[, *parseECS=false*]]]]]]) → PacketCache

Changed in version 1.3.0: *numberOfShards* and *deferrableInsertLock* parameters added.

Changed in version 1.3.1: *maxNegativeTTL* and *parseECS* parameters added.

Deprecated since version 1.4.0.

Creates a new *PacketCache* with the settings specified.

Parameters

- **maxEntries** (*int*) – The maximum number of entries in this cache
- **maxTTL** (*int*) – Cap the TTL for records to his number
- **minTTL** (*int*) – Don't cache entries with a TTL lower than this
- **temporaryFailureTTL** (*int*) – On a SERVFAIL or REFUSED from the backend, cache for this amount of seconds
- **staleTTL** (*int*) – When the backend servers are not reachable, and global configuration *setStaleCacheEntriesTTL* is set appropriately, TTL that will be used when a stale cache entry is returned
- **dontAge** (*bool*) – Don't reduce TTLs when serving from the cache. Use this when **dnsmdist** fronts a cluster of authoritative servers
- **numberOfShards** (*int*) – Number of shards to divide the cache into, to reduce lock contention
- **deferrableInsertLock** (*bool*) – Whether the cache should give up insertion if the lock is held by another thread, or simply wait to get the lock
- **maxNegativeTTL** (*int*) – Cache a NXDomain or NoData answer from the backend for at most this amount of seconds, even if the TTL of the SOA record is higher
- **parseECS** (*bool*) – Whether any EDNS Client Subnet option present in the query should be extracted and stored to be able to detect hash collisions involving queries with the same qname, qtype and qclass but a different incoming ECS value. Enabling this option adds a parsing cost and only makes sense if at least one backend might send different responses based on the ECS value, so it's disabled by default

newPacketCache (*maxEntries*[, *options*]) → PacketCache

New in version 1.4.0.

Creates a new *PacketCache* with the settings specified.

Parameters **maxEntries** (*int*) – The maximum number of entries in this cache

Options:

- **deferrableInsertLock=true**: *bool* - Whether the cache should give up insertion if the lock is held by another thread, or simply wait to get the lock.
- **dontAge=false**: *bool* - Don't reduce TTLs when serving from the cache. Use this when **dnsmdist** fronts a cluster of authoritative servers.
- **keepStaleData=false**: *bool* - Whether to suspend the removal of expired entries from the cache when there is no backend available in at least one of the pools using this cache.
- **maxNegativeTTL=3600**: *int* - Cache a NXDomain or NoData answer from the backend for at most this amount of seconds, even if the TTL of the SOA record is higher.

- `maxTTL=86400`: int - Cap the TTL for records to this number.
- `minTTL=0`: int - Don't cache entries with a TTL lower than this.
- `numberOfShards=1`: int - Number of shards to divide the cache into, to reduce lock contention.
- `parseECS=false`: bool - Whether any EDNS Client Subnet option present in the query should be extracted and stored to be able to detect hash collisions involving queries with the same `qname`, `qtype` and `qclass` but a different incoming ECS value. Enabling this option adds a parsing cost and only makes sense if at least one backend might send different responses based on the ECS value, so it's disabled by default.
- `staleTTL=60`: int - When the backend servers are not reachable, and global configuration `setStaleCacheEntriesTTL` is set appropriately, TTL that will be used when a stale cache entry is returned.
- `temporaryFailureTTL=60`: int - On a SERVFAIL or REFUSED from the backend, cache for this amount of seconds..

class PacketCache

Represents a cache that can be part of *ServerPool*.

:dump (fname)

New in version 1.3.1.

Dump a summary of the cache entries to a file.

Parameters `fname` (*str*) – The path to a file where the cache summary should be dumped.
Note that if the target file already exists, it will not be overwritten.

:expunge (n)

Remove entries from the cache, leaving at most `n` entries

Parameters `n` (*int*) – Number of entries to keep

:expungeByName (name[, qtype=DNSQType.ANY[, suffixMatch=false]])

Changed in version 1.2.0: `suffixMatch` parameter added.

Remove entries matching `name` and type from the cache.

Parameters

- **name** (*DNSName*) – The name to expunge
- **qtype** (*int*) – The type to expunge, can be a pre-defined *DNSQType*
- **suffixMatch** (*bool*) – When set to true, remove all entries under `name`

:getStats ()

New in version 1.4.0.

Return the cache stats (number of entries, hits, misses, deferred lookups, deferred inserts, lookup collisions, insert collisions and TTL too shorts) as a Lua table.

:isFull () → bool

Return true if the cache has reached the maximum number of entries.

:printStats ()

Print the cache stats (number of entries, hits, misses, deferred lookups, deferred inserts, lookup collisions, insert collisions and TTL too shorts).

:purgeExpired (n)

Remove expired entries from the cache until there is at most `n` entries remaining in the cache.

Parameters `n` (*int*) – Number of entries to keep

:toString () → string

Return the number of entries in the Packet Cache, and the maximum number of entries

16.1.5 Client State

Also called frontend or bind, the Client State object returned by `getBind()` and listed with `showBinds()` represents an address and port dnsmasq is listening on.

getBind (*index*) → ClientState

Return a *ClientState* object.

Parameters **index** (*int*) – The object index

ClientState functions

class ClientState

This object represents an address and port dnsmasq is listening on. When `reuseport` is in use, several ClientState objects can be present for the same address and port.

:attachFilter (*filter*)

Attach a BPF filter to this frontend.

Parameters **filter** (*BPFFilter*) – The filter to attach to this frontend

:detachFilter ()

Remove the BPF filter associated to this frontend, if any.

:toString () → string

Return the address and port this frontend is listening on.

Returns The address and port this frontend is listening on

muted

If set to true, queries received on this frontend will be normally processed and sent to a backend if needed, but no response will be ever be sent to the client over UDP. TCP queries are processed normally and responses sent to the client.

16.1.6 Status, Statistics and More

dumpStats ()

Print all statistics dnsmasq gathers

getDOHFrontend (*idx*)

New in version 1.4.0.

Return the DOHFrontend object for the DNS over HTTPS bind of index *idx*.

getTLSContext (*idx*)

New in version 1.3.0.

Return the TLSContext object for the context of index *idx*.

getTLSEndpoint (*idx*)

New in version 1.3.1.

Return the TLSEndpoint object for the TLS bind of index *idx*.

grepq (*selector* [, *num*])

grepq (*selectors* [, *num*])

Prints the last *num* queries matching *selector* or *selectors*.

The selector can be:

- a netmask (e.g. '192.0.2.0/24')
- a DNS name (e.g. 'dnsmasq.org')
- a response time (e.g. '100ms')

Parameters

- **selector** (*str*) – Select queries based on this property.
- **selectors** (*{str}*) – A lua table of selectors. Only queries matching all selectors are shown
- **num** (*int*) – Show a maximum of *num* recent queries, default is 10.

setVerboseHealthChecks (*verbose*)

Set whether health check errors should be logged. This is turned off by default.

Parameters **verbose** (*bool*) – Set to true if you want to enable health check errors logging

showBinds ()

Print a list of all the current addresses and ports dnssdist is listening on, also called *frontends*

showDOHFrontends ()

New in version 1.4.0.

Print the list of all availables DNS over HTTPS frontends.

showResponseLatency ()

Show a plot of the response time latency distribution

showServers (*[options]*)

Changed in version 1.4.0: *options* optional parameter added

This function shows all backend servers currently configured and some statistics. These statistics have the following fields:

- # - The number of the server, can be used as the argument for *getServer()*
- UUID - The UUID of the backend. Can be set with the *id* option of *newServer()*
- Address - The IP address and port of the server
- State - The current state of the server
- Qps - Current number of queries per second
- Qlim - Configured maximum number of queries per second
- Ord - The order number of the server
- Wt - The weight of the server
- Queries - Total amount of queries sent to this server
- Drops - Number of queries that were dropped by this server
- Drate - Number of queries dropped per second by this server
- Lat - The latency of this server in milliseconds
- Pools - The pools this server belongs to

Parameters **options** (*table*) – A table with key: value pairs with display options.

Options:

- *showUUIDs=false*: *bool* - Whether to display the UUIDs, defaults to false.

showTCPStats ()

Show some statistics regarding TCP

showTLSContexts ()

New in version 1.3.0.

Print the list of all availables DNS over TLS contexts.

showVersion()

Print the version of dnsmdist

topBandwidth([num])

Print the top `num` clients that consume the most bandwidth.

Parameters `num (int)` – Number to show, defaults to 10.

topClients([num])

Print the top `num` clients sending the most queries over length of ringbuffer

Parameters `num (int)` – Number to show, defaults to 10.

topQueries([num[, labels]])

Print the `num` most popular QNAMES from queries. Optionally grouped by the rightmost `labels` DNS labels.

Parameters

- **num** (`int`) – Number to show, defaults to 10
- **label** (`int`) – Number of labels to cut down to

topResponses([num[, rcode[, labels]])

Print the `num` most seen responses with an RCODE of `rcode`. Optionally grouped by the rightmost `labels` DNS labels.

Parameters

- **num** (`int`) – Number to show, defaults to 10
- **rcode** (`int`) – *Response code*, defaults to 0 (No Error)
- **label** (`int`) – Number of labels to cut down to

topSlow([num[, limit[, labels]])

Print the `num` slowest queries that are slower than `limit` milliseconds. Optionally grouped by the rightmost `labels` DNS labels.

Parameters

- **num** (`int`) – Number to show, defaults to 10
- **limit** (`int`) – Show queries slower than this amount of milliseconds, defaults to 2000
- **label** (`int`) – Number of labels to cut down to

16.1.7 Dynamic Blocks

addDynBlocks(addresses, message[, seconds=10[, action]])

Changed in version 1.2.0: `action` parameter added.

Block a set of addresses with `message` for (optionally) a number of seconds. The default number of seconds to block for is 10.

Parameters

- **addresses** – set of Addresses as returned by an `exceed` function
- **message** (`string`) – The message to show next to the blocks
- **seconds** (`int`) – The number of seconds this block to expire
- **action** (`int`) – The action to take when the dynamic block matches, see [here](#). (default to `DNSAction.None`, meaning the one set with `setDynBlocksAction()` is used)

Please see the documentation for `setDynBlocksAction()` to confirm which actions are supported by the action parameter.

clearDynBlocks ()

Remove all current dynamic blocks.

showDynBlocks ()

List all dynamic blocks in effect.

setDynBlocksAction (action)

Changed in version 1.3.3: `DNSAction.NXDomain` action added.

Set which action is performed when a query is blocked. Only `DNSAction.Drop` (the default), `DNSAction.NoOp`, `DNSAction.NXDomain`, `DNSAction.Refused`, `DNSAction.Truncate` and `DNSAction.NoRecurse` are supported.

Getting addresses that exceeded parameters

exceedServFails (rate, seconds)

Get set of addresses that exceed `rate` servfails/s over `seconds` seconds

Parameters

- **rate** (*int*) – Number of Servfails per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded

exceedNXDOMAINs (rate, seconds)

get set of addresses that exceed `rate` NXDOMAIN/s over `seconds` seconds

Parameters

- **rate** (*int*) – Number of NXDOMAIN per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded

exceedRespByterate (rate, seconds)

get set of addresses that exceeded `rate` bytes/s answers over `seconds` seconds

Parameters

- **rate** (*int*) – Number of bytes per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded

exceedQRate (rate, seconds)

Get set of address that exceed `rate` queries/s over `seconds` seconds

Parameters

- **rate** (*int*) – Number of queries per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded

exceedQTypeRate (type, rate, seconds)

Get set of address that exceed `rate` queries/s for queries of QType `type` over `seconds` seconds

Parameters

- **type** (*int*) – QType
- **rate** (*int*) – Number of QType queries per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded

DynBlockRulesGroup

Instead of using several `exceed*()` lines, dnsmdist 1.3.0 introduced a new `DynBlockRulesGroup` object which can be used to group dynamic block rules.

See [Dynamic Rule Generation](#) for more information about the case where using a `DynBlockRulesGroup` might be faster than the existing rules.

dynBlockRulesGroup () → DynBlockRulesGroup

New in version 1.3.0.

Creates a new *DynBlockRulesGroup* object.

class DynBlockRulesGroup

Represents a group of dynamic block rules.

:setQueryRate (*rate*, *seconds*, *reason*, *blockingTime* [, *action* [, *warningRate*]])

Changed in version 1.3.3: *warningRate* parameter added.

Adds a query rate-limiting rule, equivalent to: `addDynBlocks(exceedQRate(rate, seconds), reason, blockingTime, action)`

Parameters

- **rate** (*int*) – Number of queries per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded
- **reason** (*string*) – The message to show next to the blocks
- **blockingTime** (*int*) – The number of seconds this block to expire
- **action** (*int*) – The action to take when the dynamic block matches, see [here](#). (default to the one set with `setDynBlocksAction()`)
- **warningRate** (*int*) – If set to a non-zero value, the rate above which a warning message will be issued and a no-op block inserted

:setRCodeRate (*rcode*, *rate*, *seconds*, *reason*, *blockingTime* [, *action* [, *warningRate*]])

Changed in version 1.3.3: *warningRate* parameter added.

Adds a rate-limiting rule for responses of code *rcode*, equivalent to: `addDynBlocks(exceedServfails(rcode, rate, seconds), reason, blockingTime, action)`

Parameters

- **rcode** (*int*) – The response code
- **rate** (*int*) – Number of responses per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded
- **reason** (*string*) – The message to show next to the blocks
- **blockingTime** (*int*) – The number of seconds this block to expire
- **action** (*int*) – The action to take when the dynamic block matches, see [here](#). (default to the one set with `setDynBlocksAction()`)
- **warningRate** (*int*) – If set to a non-zero value, the rate above which a warning message will be issued and a no-op block inserted

:setQueryRate (*qtype*, *rate*, *seconds*, *reason*, *blockingTime* [, *action* [, *warningRate*]])

Changed in version 1.3.3: *warningRate* parameter added.

Adds a rate-limiting rule for queries of type *qtype*, equivalent to: `addDynBlocks(exceedQTypeRate(type, rate, seconds), reason, blockingTime, action)`

Parameters

- **qtype** (*int*) – The *qtype*
- **rate** (*int*) – Number of queries per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded
- **reason** (*string*) – The message to show next to the blocks
- **blockingTime** (*int*) – The number of seconds this block to expire

- **action** (*int*) – The action to take when the dynamic block matches, see [here](#). (default to the one set with `setDynBlocksAction()`)
- **warningRate** (*int*) – If set to a non-zero value, the rate above which a warning message will be issued and a no-op block inserted

:setResponseByteRate (*rate, seconds, reason, blockingTime*[, *action*[, *warningRate*]])

Changed in version 1.3.3: `warningRate` parameter added.

Adds a bandwidth rate-limiting rule for responses, equivalent to:
`addDynBlocks(exceedRespByteRate(rate, seconds), reason, blockingTime, action)`

Parameters

- **rate** (*int*) – Number of bytes per second to exceed
- **seconds** (*int*) – Number of seconds the rate has been exceeded
- **reason** (*string*) – The message to show next to the blocks
- **blockingTime** (*int*) – The number of seconds this block to expire
- **action** (*int*) – The action to take when the dynamic block matches, see [here](#). (default to the one set with `setDynBlocksAction()`)
- **warningRate** (*int*) – If set to a non-zero value, the rate above which a warning message will be issued and a no-op block inserted

:apply ()

Walk the in-memory query and response ring buffers and apply the configured rate-limiting rules, adding dynamic blocks when the limits have been exceeded.

:excludeRange (*netmasks*)

New in version 1.3.1.

Exclude this range, or list of ranges, meaning that no dynamic block will ever be inserted for clients in that range. Default to empty, meaning rules are applied to all ranges. When used in combination with `DynBlockRulesGroup:includeRange()`, the more specific entry wins.

Parameters netmasks (*int*) – A netmask, or list of netmasks, as strings, like for example “192.0.2.1/24”

:includeRange (*netmasks*)

New in version 1.3.1.

Include this range, or list of ranges, meaning that rules will be applied to this range. When used in combination with `DynBlockRulesGroup:excludeRange()`, the more specific entry wins.

Parameters netmasks (*int*) – A netmask, or list of netmasks, as strings, like for example “192.0.2.1/24”

:toString ()

New in version 1.3.1.

Return a string describing the rules and range exclusions of this `DynBlockRulesGroup`.

16.1.8 Other functions

maintenance ()

If this function exists, it is called every second to so regular tasks. This can be used for e.g. *Dynamic Blocks*.

DOHFrontend

class DOHFrontend

New in version 1.4.0.

This object represents an address and port dnscat is listening on for DNS over HTTPS queries.

:reloadCertificates ()
Reload the current TLS certificate and key pairs.

TLSContext

class TLSContext

New in version 1.3.0.

This object represents an address and port dnscat is listening on for DNS over TLS queries.

:rotateTicketsKey ()
Replace the current TLS tickets key by a new random one.

:loadTicketsKeys (ticketsKeysFile)

Load new tickets keys from the selected file, replacing the existing ones. These keys should be rotated often and never written to persistent storage to preserve forward secrecy. The default is to generate a random key. The OpenSSL provider supports several tickets keys to be able to decrypt existing sessions after the rotation, while the GnuTLS provider only supports one key.

Parameters ticketsKeysFile (str) – The path to a file from where TLS tickets keys should be loaded.

TLSEndpoint

class TLSEndpoint

New in version 1.3.1.

This object represents the configuration of a listening frontend for DNS over TLS queries. To each frontend is associated a TLSContext.

TLSContext: **loadNewCertificatesAndKeys (certFile(s), keyFile(s))**

Create and switch to a new TLS context using the same options than were passed to the corresponding *addTLSLocal()* directive, but loading new certificates and keys from the selected files, replacing the existing ones.

Parameters

- **certFile(s) (str)** – The path to a X.509 certificate file in PEM format, or a list of paths to such files.
- **keyFile(s) (str)** – The path to the private key file corresponding to the certificate, or a list of paths to such files, whose order should match the certFile(s) ones.

EDNS on Self-generated answers

There are several mechanisms in dnscat that turn an existing query into an answer right away, without reaching out to the backend, including *SpoofAction()*, *RCodeAction()*, *TCAction()* and returning a response from Lua. Those responses should, according to **RFC 6891**, contain an OPT record if the received request had one, which is the case by default and can be disabled using *setAddEDNSToSelfGeneratedResponses()*.

We must, however, provide a responder's maximum payload size in this record, and we can't easily know the maximum payload size of the actual backend so we need to provide one. The default value is 1500 and can be overridden using *setPayloadSizeOnSelfGeneratedAnswers()*.

setAddEDNSToSelfGeneratedResponses (add)

New in version 1.3.3.

Whether to add EDNS to self-generated responses, provided that the initial query had EDNS.

Parameters `add` (*bool*) – Whether to add EDNS, default is true.

setPayloadSizeOnSelfGeneratedAnswers (*payloadSize*)

New in version 1.3.3.

Set the UDP payload size advertised via EDNS on self-generated responses. In accordance with [RFC 6891](#), values lower than 512 will be treated as equal to 512.

Parameters `payloadSize` (*int*) – The responder’s maximum UDP payload size, in bytes.

Default is 1500.

Security Polling

PowerDNS products can poll the security status of their respective versions. This polling, naturally, happens over DNS. If the result is that a given version has a security problem, the software will report this at level ‘Error’ during startup, and repeatedly during operations, every `setSecurityPollInterval()` seconds.

By default, security polling happens on the domain ‘secpoll.powerdns.com’, but this can be changed with the `setSecurityPollSuffix()` function. If this setting is made empty, no polling will take place. Organizations wanting to host their own security zones can do so by changing this setting to a domain name under their control.

To enable distributors of PowerDNS to signal that they have backported versions, the `PACKAGEVERSION` compilation-time macro can be used to set a distributor suffix.

setSecurityPollInterval (*interval*)

New in version 1.3.3.

Set the interval, in seconds, between two security pollings.

Parameters `interval` (*int*) – The interval, in seconds, between two pollings. Default is 3600.

setSecurityPollSuffix (*suffix*)

New in version 1.3.3.

Domain name from which to query security update notifications. Setting this to an empty string disables secpoll.

Parameters `suffix` (*string*) – The suffix to use, default is ‘secpoll.powerdns.com.’.

16.2 Constants

There are many constants in `dnscat`.

16.2.1 OpCode

These constants represent the `OpCode` of a query.

- `DNSOpcode.Query`
- `DNSOpcode.IQuery`
- `DNSOpcode.Status`
- `DNSOpcode.Notify`
- `DNSOpcode.Update`

Reference: <https://www.iana.org/assignments/dns-parameters/dns-parameters.xhtml#dns-parameters-5>

16.2.2 DNSClass

These constants represent the **CLASS** of a DNS record.

- `DNSClass.IN`
- `DNSClass.CHAOS`
- `DNSClass.NONE`
- `DNSClass.ANY`

Reference: <https://www.iana.org/assignments/dns-parameters/dns-parameters.xhtml#dns-parameters-2>

16.2.3 RCode

These constants represent the different **RCODEs** for DNS messages.

Changed in version 1.4.0: The prefix is changed from `dnsdist` to `DNSRCode`.

- `DNSRCode.NOERROR`
- `DNSRCode.FORMERR`
- `DNSRCode.SERVFAIL`
- `DNSRCode.NXDOMAIN`
- `DNSRCode.NOTIMP`
- `DNSRCode.REFUSED`
- `DNSRCode.YXDOMAIN`
- `DNSRCode.YXRRSET`
- `DNSRCode.NXRRSET`
- `DNSRCode.NOTAUTH`
- `DNSRCode.NOTZONE`

RCodes below are extended RCodes that can only be matched using `ERCodeRule()`.

- `DNSRCode.BADVERS`
- `DNSRCode.BADSIG`
- `DNSRCode.BADKEY`
- `DNSRCode.BADTIME`
- `DNSRCode.BADMODE`
- `DNSRCode.BADNAME`
- `DNSRCode.BADALG`
- `DNSRCode.BADTRUNC`
- `DNSRCode.BADCOOKIE`

16.2.4 EDNSOptionCode

- `EDNSOptionCode.DHU`
- `EDNSOptionCode.ECS`
- `EDNSOptionCode.N3U`
- `EDNSOptionCode.DAU`

- `EDNSOptionCode.TCPKEEPALIVE`
- `EDNSOptionCode.COOKIE`
- `EDNSOptionCode.PADDING`
- `EDNSOptionCode.KEYTAG`
- `EDNSOptionCode.NSID`
- `EDNSOptionCode.CHAIN`
- `EDNSOptionCode.EXPIRE`

Reference: <https://www.iana.org/assignments/dns-parameters/dns-parameters.xhtml#dns-parameters-11>

16.2.5 DNS Packet Sections

These constants represent the section in the DNS Packet.

- `DNSSection.Question`
- `DNSSection.Answer`
- `DNSSection.Authority`
- `DNSSection.Additional`

16.2.6 DNSAction

These constants represent an Action that can be returned from `LuaAction()` functions.

- `DNSAction.Allow`: let the query pass, skipping other rules
- `DNSAction.Delay`: delay the response for the specified milliseconds (UDP-only), continue to the next rule
- `DNSAction.Drop`: drop the query
- `DNSAction.HeaderModify`: indicate that the query has been turned into a response
- `DNSAction.None`: continue to the next rule
- `DNSAction.NoOp`: continue to the next rule (used for Dynamic Block actions where None has a different meaning)
- `DNSAction.Nxdomain`: return a response with a NXDomain rcode
- `DNSAction.Pool`: use the specified pool to forward this query
- `DNSAction.Refused`: return a response with a Refused rcode
- `DNSAction.ServFail`: return a response with a ServFail rcode
- `DNSAction.Spoof`: spoof the response using the supplied IPv4 (A), IPv6 (AAAA) or string (CNAME) value
- `DNSAction.Truncate`: truncate the response
- `DNSAction.NoRecurse`: set rd=0 on the query

16.2.7 DNSQType

Changed in version 1.3.0: The prefix is changed from `dnsdist.` to `DNSQType.`

All named QTypes are available as constants, prefixed with `DNSQType.`, e.g.:

- `DNSQType.AAAA`

- `DNSQType.AXFR`
- `DNSQType.A`
- `DNSQType.NS`
- `DNSQType.SOA`
- etc.

16.2.8 DNSResponseAction

These constants represent an Action that can be returned from `LuaResponseAction()` functions.

- `DNSResponseAction.Allow`: let the response pass, skipping other rules
- `DNSResponseAction.Delay`: delay the response for the specified milliseconds (UDP-only), continue to the next rule
- `DNSResponseAction.Drop`: drop the response
- `DNSResponseAction.HeaderModify`: indicate that the query has been turned into a response
- `DNSResponseAction.None`: continue to the next rule
- `DNSResponseAction.ServFail`: return a response with a ServFail rcode

16.3 ComboAddress

IP addresses are moved around in a native format, called a ComboAddress. ComboAddresses can be IPv4 or IPv6, and unless you want to know, you don't need to.

newCA (*address*) → :class:'ComboAddress'
Returns a *ComboAddress* based on *address*

Parameters *address* (*string*) – The IP address, with optional port, to represent.

class ComboAddress

A *ComboAddress* represents an IP address with possibly a port number. The object can be an IPv4 or an IPv6 address. It has these methods:

:getPort () → int
Returns the port number.

:ipdecrypt (*key*) → ComboAddress
Decrypt this IP address as described in <https://powerdns.org/ipcipher>

Parameters *key* (*string*) – A 16 byte key. Note that this can be derived from a passphrase with the standalone function *makeIPCipherKey*

:ipencrypt (*key*) → ComboAddress
Encrypt this IP address as described in <https://powerdns.org/ipcipher>

Parameters *key* (*string*) – A 16 byte key. Note that this can be derived from a passphrase with the standalone function *makeIPCipherKey*

:isIPv4 () → bool
Returns true if the address is an IPv4, false otherwise

:isIPv6 () → bool
Returns true if the address is an IPv6, false otherwise

:isMappedIPv4 () → bool
Returns true if the address is an IPv4 mapped into an IPv6, false otherwise

:mapToIPv4 () → ComboAddress
Convert an IPv4 address mapped in a v6 one into an IPv4. Returns a new ComboAddress

```

:toString () → string
:toString () → string
    Returns in human-friendly format

:toStringWithPort () → string
:toStringWithPort () → string
    Returns in human-friendly format, with port number

:truncate (bits)
    Truncate the ComboAddress to the specified number of bits. This essentially zeroes all bits after
    bits.

    Parameters bits (int) – Amount of bits to truncate to
    
```

16.4 NetmaskGroup

```

newNMG () → NetmaskGroup
    Returns a NetmaskGroup
    
```

class NetmaskGroup

Represents a group of netmasks that can be used to match *ComboAddresses* against.

```

:addMask (mask)
:addMask (masks)
    Add one or more masks to the NMG.

    Parameters
    • mask (string) – Add this mask, prefix with ! to exclude this mask from matching.
    • masks (table) – Adds the keys of the table to the NetmaskGroup. It should be a
      table whose keys are ComboAddress objects and values are integers, as returned by
      exceed* functions.

:match (address) → bool
    Checks if address is matched by this NetmaskGroup.

    Parameters address (ComboAddress) – The address to match.

:clear ()
    Clears the NetmaskGroup.

:size () → int
    Returns number of netmasks in this NetmaskGroup.
    
```

16.5 DNSName objects

A *DNSName* object represents a name in the DNS. It has several functions that can manipulate it without conversions to strings. Creating a *DNSName* is done with the *newDNSName* ():

```

myname = newDNSName ("www.example.com")
    
```

dnsdist will complain loudly if the name is invalid (e.g. too long, dot in the wrong place).

The *myname* variable has several functions to get information from it

```

print (myname:countLabels ()) -- prints "3"
print (myname:wirelength ()) -- prints "17"
name2 = newDNSName ("example.com")
if myname:isPartOf (name2) then -- prints "it is"
    
```

(continues on next page)

(continued from previous page)

```
print('it is')
end
```

16.5.1 Functions and methods of a `DNSName`

newDNSName (*name*) → `DNSName`

Returns the `DNSName` object of *name*.

Parameters *name* (*string*) – The name to create a `DNSName` for

class `DNSName`

A `DNSName` object represents a name in the DNS. It is returned by several functions and has several functions to programmatically interact with it.

:chopoff () → bool

New in version 1.2.0.

Removes the left-most label and returns `true`. `false` is returned if no label was removed

:countLabels () → int

Returns the number of `DNSLabels` in the name

:isPartOf (*name*) → bool

Returns true if the `DNSName` is part of the DNS tree of *name*.

Parameters *name* (`DNSName`) – The name to check against

:toString () → string

:tostring () → string

Returns a human-readable form of the `DNSName`.

:wirelength () → int

Returns the length in bytes of the `DNSName` as it would be on the wire.

16.6 `DNSNameSet` objects

A `DNSNameSet` object is a set of `DNSName` objects. Based on `std::unordered_set` (hash table). Creating a `DNSNameSet` is done with the `newDNSNameSet` ():

```
myset = newDNSNameSet ()
```

The set can be filled by func:`DNSNameSet:add`:

```
myset.add(newDNSName ("domain1.tld"))
myset.add(newDNSName ("domain2.tld"))
```

16.6.1 Functions and methods of a `DNSNameSet`

newDNSNameSet (*name*) → `DNSNameSet`

Returns the `DNSNameSet`.

class `DNSNameSet`

A `DNSNameSet` object is a set of `DNSName` objects.

:add (*name*)

Adds the name to the set.

:param `DNSName` *name* The name to add.

:empty () → bool
Returns true if the DNSNameSet is empty.

:clear ()
Clean up the set.

:toString () → string
Returns a human-readable form of the DNSName.

:size () → int
Returns the number of names in the set.

:delete (*name*) → int
Removes the name from the set. Returns the number of deleted elements.
:param DNSName name The name to remove.

:check (*name*) → bool
Returns true if the set contains the name.
:param DNSName name The name.

16.7 The DNSQuestion (dq) object

A DNSQuestion or dq object is available in several hooks and Lua actions. This object contains details about the current state of the question. This state can be modified from the various hooks.

class DNSQuestion

The DNSQuestion object has several attributes, many of them read-only:

dh

The *DNSHeader (dh) object* of this query.

ecsOverride

Whether an existing ECS value should be overridden, settable.

ecsPrefixLength

The ECS prefix length to use, settable.

len

The length of the data starting at *DNSQuestion.dh*, including any trailing bytes following the DNS message.

localaddr

ComboAddress of the local bind this question was received on.

opcode

Integer describing the OPCODE of the packet. Can be matched against *OPCode*.

qclass

QClass (as an unsigned integer) of this question. Can be compared against DNSQClass.

qname

DNSName of this question.

qtype

QType (as an unsigned integer) of this question. Can be compared against the pre-defined *constants* like *DNSQType.A*, *DNSQType.AAAA*“.

remoteaddr

ComboAddress of the remote client.

rcode

RCode (as an unsigned integer) of this question. Can be compared against *RCode*

size

The total size of the buffer starting at *DNSQuestion.dh*.

skipCache

Whether to skip cache lookup / storing the answer for this question, settable.

tcp

Whether the query was received over TCP.

useECS

Whether to send ECS to the backend, settable.

It also supports the following methods:

:getDO () → bool

New in version 1.2.0.

Get the value of the DNSSEC OK bit.

Returns true if the DO bit was set, false otherwise

:getEDNSOptions () → table

New in version 1.3.3.

Return the list of EDNS Options, if any.

Returns A table of EDNSOptionView objects, indexed on the ECS Option code

:getTag (key) → string

New in version 1.2.0.

Get the value of a tag stored into the DNSQuestion object.

Parameters **key** (*string*) – The tag's key

Returns The tag's value if it was set, an empty string otherwise

:getTagArray () → table

New in version 1.2.0.

Get all the tags stored into the DNSQuestion object.

Returns A table of tags, using strings as keys and values

:getTrailingData () → string

New in version 1.4.0.

Get all data following the DNS message.

Returns The trailing data as a null-safe string

:sendTrap (reason)

New in version 1.2.0.

Send an SNMP trap.

Parameters **reason** (*string*) – An optional string describing the reason why this trap was sent

:setTag (key, value)

New in version 1.2.0.

Set a tag into the DNSQuestion object.

Parameters

- **key** (*string*) – The tag's key
- **value** (*string*) – The tag's value

:setTagArray (*tags*)

New in version 1.2.0.

Set an array of tags into the DNSQuestion object.

Parameters **tags** (*table*) – A table of tags, using strings as keys and values

:setTrailingData (*tail*) → bool

New in version 1.4.0.

Set the data following the DNS message, overwriting anything already present.

Parameters **tail** (*string*) – The new data

Returns true if the operation succeeded, false otherwise

16.8 DNSResponse object

class DNSResponse

This object has all the functions and members of a *DNSQuestion* and some more

:editTTLs (*func*)

The function *func* is invoked for every entry in the answer, authority and additional section.

func points to a function with the following prototype: `myFunc(section, qclass, qtype, ttl)`

All parameters to *func* are integers:

- *section* is the section in the packet and can be compared to *DNS Packet Sections*
- *qclass* is the QClass of the record. Can be compared to *DNSQClass*
- *qtype* is the QType of the record. Can be e.g. compared to *DNSQType.A*, *DNSQType.AAAA constants* and the like.
- *ttl* is the current TTL

This function must return an integer with the new TTL. Setting this TTL to 0 to leaves it unchanged

Parameters **func** (*string*) – The function to call to edit TTLs.

16.9 DNSHeader (dh) object

class DNSHeader

This object holds a representation of a DNS packet's header.

:getRD () → bool

Get recursion desired flag.

:setRD (*rd*)

Set recursion desired flag.

Parameters **rd** (*bool*) – State of the RD flag

:setTC (*tc*)

Set truncation flag (TC).

Parameters **tc** (*bool*) – State of the TC flag

:setQR (*qr*)

Set Query/Response flag. Setting QR to true means “This is an answer packet”.

Parameters **qr** (*bool*) – State of the QR flag

:getCD () → bool
Get checking disabled flag.

:setCD (*cd*)
Set checking disabled flag.

Parameters *cd* (*bool*) – State of the CD flag

16.10 EDNSOptionView object

class EDNSOptionView

New in version 1.3.3.

An object that represents the values of a single EDNS option received in a query.

:count ()
The number of values for this EDNS option.

:getValues ()
Return a table of NULL-safe strings values for this EDNS option.

16.11 eBPF functions and objects

These are all the functions, objects and methods related to the *eBPF Socket Filtering*.

addBPFFilterDynBlocks (*addresses*, *dynbpf*[[, *seconds=10*], *msg*])
Changed in version 1.3.0: *msg* optional parameter added.

This is the eBPF equivalent of *addDynBlocks* (), blocking a set of addresses for (optionally) a number of seconds, using an eBPF dynamic filter. The default number of seconds to block for is 10.

Parameters

- **addresses** – set of Addresses as returned by an *exceed function*
- **dynbpf** (*DynBPFFilter*) – The dynamic eBPF filter to use
- **seconds** (*int*) – The number of seconds this block to expire
- **msg** (*str*) – A message to display while inserting the block

newBPFFilter (*maxV4*, *maxV6*, *maxQNames*) → *BPFFilter*

Return a new eBPF socket filter with a maximum of *maxV4* IPv4, *maxV6* IPv6 and *maxQNames* qname entries in the block table.

Parameters

- **maxV4** (*int*) – Maximum number of IPv4 entries in this filter
- **maxV6** (*int*) – Maximum number of IPv6 entries in this filter
- **maxQNames** (*int*) – Maximum number of QName entries in this filter

newDynBPFFilter (*bpf*) → *DynBPFFilter*

Return a new dynamic eBPF filter associated to a given BPF Filter.

Parameters *bpf* (*BPFFilter*) – The underlying eBPF filter

setDefaultBPFFilter (*filter*)

When used at configuration time, the corresponding *BPFFilter* will be attached to every bind.

Parameters *filter* (*BPFFilter*) – The filter to attach

registerDynBPFFilter (*dynbpf*)

Register a *DynBPFFilter* filter so that it appears in the web interface and the API.

Parameters `dynbpf` (`DynBPFFilter`) – The dynamic eBPF filter to register

unregisterDynBPFFilter (`dynbpf`)

Remove a DynBPFFilter filter from the web interface and the API.

Parameters `dynbpf` (`DynBPFFilter`) – The dynamic eBPF filter to unregister

class BPFFilter

Represents an eBPF filter

:attachToAllBinds ()

Attach this filter to every bind already defined. This is the run-time equivalent of `setDefaultBPFFilter()`

:block (`address`)

Block this address

Parameters `address` (`ComboAddress`) – The address to block

:blockQName (`name` [, `qtype=255`])

Block queries for this exact qname. An optional qtype can be used, defaults to 255.

Parameters

- **name** (`DNSName`) – The name to block
- **qtype** (`int`) – QType to block

:getStats ()

Print the block tables.

:unblock (`address`)

Unblock this address.

Parameters `address` (`ComboAddress`) – The address to unblock

:unblockQName (`name` [, `qtype=255`])

Remove this qname from the block list.

Parameters

- **name** (`DNSName`) – the name to unblock
- **qtype** (`int`) – The qtype to unblock

class DynBPFFilter

Represents an dynamic eBPF filter, allowing the use of ephemeral rules to an existing eBPF filter.

:purgeExpired ()

Remove the expired ephemeral rules associated with this filter.

:excludeRange (`netmasks`)

New in version 1.3.3.

Exclude this range, or list of ranges, meaning that no dynamic block will ever be inserted for clients in that range. Default to empty, meaning rules are applied to all ranges. When used in combination with `DynBPFFilter:includeRange()`, the more specific entry wins.

Parameters `netmasks` (`int`) – A netmask, or list of netmasks, as strings, like for example “192.0.2.1/24”

:includeRange (`netmasks`)

New in version 1.3.3.

Include this range, or list of ranges, meaning that rules will be applied to this range. When used in combination with `DynBPFFilter:excludeRange()`, the more specific entry wins.

Parameters `netmasks` (`int`) – A netmask, or list of netmasks, as strings, like for example “192.0.2.1/24”

16.12 DNSCrypt objects and functions

addDNSCryptBind (*address*, *provider*, *certificate*, *keyfile* [, *options*])

Changed in version 1.3.0: *cpus* option added.

Adds a DNSCrypt listen socket on *address*.

Parameters

- **address** (*string*) – The address and port to listen on
- **provider** (*string*) – The provider name for this bind
- **certificate** (*string*) – Path to the certificate file
- **keyfile** (*string*) – Path to the key file of the certificate
- **options** (*table*) – A table with key: value pairs with options (see below)

Options:

- *doTCP=true*: bool - Also bind on TCP on *address*.
- *reusePort=false*: bool - Set the `SO_REUSEPORT` socket option.
- *tcpFastOpenSize=0*: int - Set the TCP Fast Open queue size, enabling TCP Fast Open when available and the value is larger than 0
- *interface=""*: str - Sets the network interface to use
- *cpus={}*: table - Set the CPU affinity for this listener thread, asking the scheduler to run it on a single CPU id, or a set of CPU ids. This parameter is only available if the OS provides the `pthread_setaffinity_np()` function.

generateDNSCryptProviderKeys (*publicKey*, *privateKey*)

Generate a new provider keypair and write them to *publicKey* and *privateKey*.

Parameters

- **publicKey** (*string*) – path to write the public key to
- **privateKey** (*string*) – path to write the private key to

generateDNSCryptCertificate (*privatekey*, *certificate*, *keyfile*, *serial*, *validFrom*, *validUntil* [, *version*])

Changed in version 1.3.0: *version* optional parameter added.

generate a new resolver private key and related certificate, valid from the *validFrom* UNIX timestamp until the *validUntil* one, signed with the provider private key.

Parameters

- **privatekey** (*string*) – Path to the private key of the provider
- **certificate** (*string*) – Path where to write the certificate file
- **keyfile** (*string*) – Path where to write the private key for the certificate
- **serial** (*int*) – The certificate's serial number
- **validFrom** (*int*) – Unix timestamp from when the certificate will be valid
- **validUntil** (*int*) – Unix timestamp until when the certificate will be valid
- **version** (*DNSCryptExchangeVersion*) – The exchange version to use. Possible values are `DNSCryptExchangeVersion::VERSION1` (default, X25519-XSalsa20Poly1305) and `DNSCryptExchangeVersion::VERSION2` (X25519-XChacha20Poly1305)

printDNSCryptProviderFingerprint (*keyfile*)

Display the fingerprint of the provided resolver public key

Parameters **keyfile** (*string*) – Path to the key file

showDNSECryptBinds ()

Display the currently configured DNSECrypt binds

getDNSECryptBind (*n*) → DNSECryptContext

Return the *DNSECryptContext* object corresponding to the bind *n*.

16.12.1 Certificates

class DNSECryptCert

Represents a DNSECrypt certificate.

:getClientMagic () → string

Return this certificate's client magic value.

:getEsVersion () → string

Return the cryptographic construction to use with this certificate,.

:getMagic () → string

Return the certificate magic number.

:getProtocolMinorVersion () → string

Return this certificate's minor version.

:getResolverPublicKey () → string

Return the public key corresponding to this certificate.

:getSerial () → int

Return the certificate serial number.

:getSignature () → string

Return this certificate's signature.

:getTSEnd () → int

Return the date the certificate is valid from, as a Unix timestamp.

:getTSStart () → int

Return the date the certificate is valid until (inclusive), as a Unix timestamp

16.12.2 Certificate Pairs

class DNSECryptCertificatePair

Represents a pair of DNSECrypt certificate and associated key

:getCertificate () → DNSECryptCert

Return the certificate.

:isActive () → bool

Return whether this pair is active and will be advertised to clients.

16.12.3 Context

class DNSECryptContext

Represents a DNSECrypt content. Can be used to rotate certs.

:addNewCertificate (*cert*, *key*[, *active*])

New in version 1.3.0.

Add a new certificate to the the given context. Active certificates are advertised to clients, inactive ones are not.

Parameters

- **cert** (*DNSEncryptCert*) – The certificate to add to the context
- **key** (*DNSEncryptPrivateKey*) – The private key corresponding to the certificate
- **active** (*bool*) – Whether the certificate should be advertised to clients. Default is true

:generateAndLoadInMemoryCertificate (*keyfile*, *serial*, *begin*, *end*[, *version*])

Changed in version 1.3.0: *version* optional parameter added.

Generate a new resolver key and the associated certificate in-memory, sign it with the provided provider key, and add it to the context

Parameters

- **keyfile** (*string*) – Path to the provider key file to use
- **serial** (*int*) – The serial number of the certificate
- **begin** (*int*) – Unix timestamp from when the certificate is valid
- **end** (*int*) – Unix timestamp from until the certificate is valid
- **version** (*DNSEncryptExchangeVersion*) – The exchange version to use. Possible values are `DNSEncryptExchangeVersion::VERSION1` (default, X25519-XSalsa20Poly1305) and `DNSEncryptExchangeVersion::VERSION2` (X25519-XChacha20Poly1305)

:getCurrentCertificate () → *DNSEncryptCert*

Deprecated since version 1.3.0: Removed as it relied on one certificate. See `DNSEncryptContext:getCertificate()`.

Return the current certificate.

:getOldCertificate () → *DNSEncryptCert*

Deprecated since version 1.3.0: Removed as it relied on one certificate.

Return the previous certificate.

:hasOldCertificate () → *bool*

Deprecated since version 1.3.0: Removed as it relied on one certificate.

Whether or not the context has a previous certificate, from a certificate rotation.

:getCertificate (*index*) → *DNSEncryptCert*

New in version 1.3.0.

Return the certificate with index *index*.

Parameters *index* (*int*) – The index of the certificate, starting at 0

:getCertificatePair (*index*) → *DNSEncryptCertificatePair*

New in version 1.3.0.

Return the certificate pair with index *index*.

Parameters *index* (*int*) – The index of the certificate, starting at 0

:getCertificatePair (*index*) → table of *DNSEncryptCertificatePair*

New in version 1.3.0.

Return a table of certificate pairs.

:getProviderName () → *string*

Return the provider name

:loadNewCertificate (*certificate*, *keyfile*[, *active*])

Changed in version 1.3.0: *active* optional parameter added.

Load a new certificate and the corresponding private key. If *active* is false, the certificate will not be advertised to clients but can still be used to answer queries tied to it.

Parameters

- **certificate** (*string*) – Path to a certificate file
- **keyfile** (*string*) – Path to a the corresponding key file
- **active** (*bool*) – Whether the certificate should be marked as active. Default is true

:markActive (*serial*)

New in version 1.3.0.

Mark the certificate with serial *serial* as active, meaning it will be advertised to clients.

Parameters **serial** (*int*) – The serial of the number to mark as active

:markInactive (*serial*)

New in version 1.3.0.

Mark the certificate with serial *serial* as inactive, meaning it will not be advertised to clients but can still be used to answer queries tied to this certificate.

Parameters **serial** (*int*) – The serial of the number to mark as inactive

:printCertificates ()

New in version 1.3.0.

Print all the certificates.

:removeInactiveCertificate (*serial*)

New in version 1.3.0.

Remove the certificate with serial *serial*. It will not be possible to answer queries tied to this certificate, so it should have been marked as inactive for a certain time before that. Active certificates should be marked as inactive before they can be removed.

Parameters **serial** (*int*) – The serial of the number to remove

16.13 Protobuf Logging Reference

newRemoteLogger (*address*[, *timeout*=2[, *maxQueuedEntries*=100[, *reconnectWaitTime*=1]]])

Create a Remote Logger object, to use with *RemoteLogAction()* and *RemoteLogResponseAction()*.

Parameters

- **address** (*string*) – An IP:PORT combination where the logger is listening
- **timeout** (*int*) – TCP connect timeout in seconds
- **maxQueuedEntries** (*int*) – Queue this many messages before dropping new ones (e.g. when the remote listener closes the connection)
- **reconnectWaitTime** (*int*) – Time in seconds between reconnection attempts

class **DNSDistProtoBufMessage**

This object represents a single protobuf message as emitted by **dnsmdist**.

:addResponseRR (*name*, *type*, *class*, *ttl*, *blob*)

New in version 1.2.0.

Add a response RR to the protobuf message.

Parameters

- **name** (*string*) – The RR name.
- **type** (*int*) – The RR type.
- **class** (*int*) – The RR class.

- **t1** (*int*) – The RR TTL.
 - **blob** (*string*) – The RR binary content.
- :setBytes** (*bytes*)
Set the size of the query
- Parameters bytes** (*int*) – Number of bytes in the query.
- :setEDNSSubnet** (*netmask*)
Set the EDNS Subnet to *netmask*.
- Parameters netmask** (*string*) – The netmask to set to.
- :setQueryTime** (*sec, usec*)
In a response message, set the time at which the query has been received.
- Parameters**
- **sec** (*int*) – Unix timestamp when the query was received.
 - **usec** (*int*) – The microsecond the query was received.
- :setQuestion** (*name, qtype, qclass*)
Set the question in the protobuf message.
- Parameters**
- **name** (*DNSName*) – The qname of the question
 - **qtype** (*int*) – The qtype of the question
 - **qclass** (*int*) – The qclass of the question
- :setProtobufResponseType** (*sec, usec*)
New in version 1.2.0.
Change the protobuf response type from a query to a response, and optionally set the query time.
- Parameters**
- **sec** (*int*) – Optional query time in seconds.
 - **usec** (*int*) – Optional query time in additional micro-seconds.
- :setRequestor** (*address*)
Set the requestor's address.
- Parameters address** (*ComboAddress*) – The address to set to
- :setRequestorFromString** (*address*)
Set the requestor's address from a string.
- Parameters address** (*string*) – The address to set to
- :setResponder** (*address*)
Set the responder's address.
- Parameters address** (*ComboAddress*) – The address to set to
- :setResponderFromString** (*address*)
Set the responder's address.
- Parameters address** (*string*) – The address to set to
- :setResponseCode** (*rcode*)
Set the response code of the query.
- Parameters rcode** (*int*) – The response code of the answer
- :setServerIdentity** (*id*)
New in version 1.3.3.
Set the server identify field.

Parameters `id (string)` – The server ID

:setTag (value)

New in version 1.2.0.

Add a tag to the list of tags.

Parameters `value (string)` – The tag value

:setTagArray (valueList)

New in version 1.2.0.

Add a list of tags.

Parameters `tags (table)` – A list of tags as strings

:setTime (sec, usec)

Set the time at which the query or response has been received.

Parameters

- `sec (int)` – Unix timestamp when the query was received.
- `usec (int)` – The microsecond the query was received.

:toDebugString () → string

Return an string containing the content of the message

16.14 dnscat Logging Reference

`dnscat` is a flexible, structured binary log format for DNS software. Reader implementations in various languages exist.

`dnscat` supports `dnscat` since version 1.3.0.

Canonically, `dnscat` is sent over a `FrameStream` socket, either a local `AF_UNIX` (see `newFrameStreamUnixLogger()`) or a TCP/IP socket (see `newFrameStreamTcpLogger()`). As an extension, `dnscat` can send raw `dnscat` protobuf messages over a `newRemoteLogger()`.

To use `FrameStream` transport, `dnscat` must have been built with `libfstrm`.

newFrameStreamUnixLogger (path)

Create a `Frame Stream Logger` object, to use with `DnscatLogAction()` and `DnscatLogResponseAction()`. This version will log to a local `AF_UNIX` socket.

Parameters `path (string)` – A local `AF_UNIX` socket path. Note that most platforms have a rather short limit on the length.

newFrameStreamTcpLogger (address)

Create a `Frame Stream Logger` object, to use with `DnscatLogAction()` and `DnscatLogResponseAction()`. This version will log to a possibly remote TCP socket. Needs `tcp_writer` support in `libfstrm`.

Parameters `address (string)` – An IP:PORT combination where the logger will connect to.

class DnscatMessage

This object represents a single `dnscat` message as emitted by `dnscat`.

classmethod `DnscatMessage:setExtra (extraData)`

Sets the `dnscat` “extra” field.

Parameters `extraData (string)` – Extra data stuffed into the `dnscat` “extra” field.

classmethod `DnscatMessage:toDebugString ()` → string

Return a string containing the content of the message

16.15 Carbon export

carbonServer (*serverIP* [, *ourname*] [, *interval*])

Export statistics to a Carbon / Graphite / Metronome server.

Parameters

- **serverIP** (*string*) – Indicates the IP address where the statistics should be sent
- **ourname** (*string*) – An optional string specifying the hostname that should be used
- **interval** (*int*) – An optional unsigned integer indicating the interval in seconds between exports

16.16 SNMP reporting

New in version 1.2.0.

snmpAgent (*enableTraps* [, *masterSocket*])

Enable SNMP support.

Parameters

- **enableTraps** (*bool*) – Indicates whether traps should be sent
- **masterSocket** (*string*) – A string specifying how to connect to the master agent. This is a file path to a unix socket, but e.g. `tcp:localhost:705` can be used as well. By default, SNMP agent's default socket is used.

sendCustomTrap (*message*)

Send a custom SNMP trap from Lua.

Parameters *message* (*string*) – The message to include in the sent trap

16.17 Tuning related functions

setMaxTCPClientThreads (*num*)

Set the maximum of TCP client threads, handling TCP connections. Before 1.4.0 a TCP thread could only handle a single incoming TCP connection at a time, while after 1.4.0 it can handle a larger number of them simultaneously.

Parameters *num* (*int*) –

setMaxTCPConnectionDuration (*num*)

Set the maximum duration of an incoming TCP connection, in seconds. 0 (the default) means unlimited

Parameters *num* (*int*) –

setMaxTCPConnectionsPerClient (*num*)

Set the maximum number of TCP connections per client. 0 (the default) means unlimited

Parameters *num* (*int*) –

setMaxTCPQueriesPerConnection (*num*)

Set the maximum number of queries in an incoming TCP connection. 0 (the default) means unlimited

Parameters *num* (*int*) –

setMaxTCPQueuedConnections (*num*)

Set the maximum number of TCP connections queued (waiting to be picked up by a client thread), defaults to 1000. 0 means unlimited

Parameters *num* (*int*) –

setMaxUDPOutstanding (*num*)

Set the maximum number of outstanding UDP queries to a given backend server. This can only be set at configuration time and defaults to 10240

Parameters *num* (*int*) –

setCacheCleaningDelay (*num*)

Set the interval in seconds between two runs of the cache cleaning algorithm, removing expired entries

Parameters *num* (*int*) –

setCacheCleaningPercentage (*num*)

Set the percentage of the cache that the cache cleaning algorithm will try to free by removing expired entries. By default (100), all expired entries are removed

Parameters *num* (*int*) –

setStaleCacheEntriesTTL (*num*)

Allows using cache entries expired for at most n seconds when no backend available to answer for a query

Parameters *num* (*int*) –

setTCPUseSinglePipe (*val*)

Whether the incoming TCP connections should be put into a single queue instead of using per-thread queues. Defaults to false

Parameters *val* (*bool*) –

setTCPRecvTimeout (*num*)

Set the read timeout on TCP connections from the client, in seconds

Parameters *num* (*int*) –

setTCPSendTimeout (*num*)

Set the write timeout on TCP connections from the client, in seconds

Parameters *num* (*int*) –

setUDPMultipleMessagesVectorSize (*num*)

New in version 1.3.0.

Set the maximum number of UDP queries messages to accept in a single `recvmsg()` call. Only available if the underlying OS support `recvmsg()` with the `MSG_WAITFORONE` option. Defaults to 1, which means only query at a time is accepted, using `recvmsg()` instead of `recvmsg()`.

Parameters *num* (*int*) – maximum number of UDP queries to accept

setUDPTimeout (*num*)

Set the maximum time dnssdist will wait for a response from a backend over UDP, in seconds. Defaults to 2

Parameters *num* (*int*) –

17.1 dnsmdist

17.1.1 Synopsis

dnsmdist [<option>...] [address]...

17.1.2 Description

dnsmdist receives DNS queries and relays them to one or more downstream servers. It subsequently sends back responses to the original requestor.

dnsmdist operates over TCP and UDP, and strives to deliver very high performance over both.

Currently, queries are sent to the downstream server with the least outstanding queries. This effectively implies load balancing, making sure that slower servers get less queries.

If a reply has not come in after a few seconds, it is removed from the queue, but in the short term, timeouts do cause a server to get less traffic.

IPv4 and IPv6 operation can be mixed and matched, in other words, queries coming in over IPv6 could be forwarded to IPv4 and vice versa.

dnsmdist is scriptable in Lua, see the dnsmdist documentation for more information on this.

17.1.3 Scope

dnsmdist does not ‘think’ about DNS queries, it restricts itself to measuring response times and error codes and routing questions accordingly. It comes with a very high performance packet-cache.

The goal for dnsmdist is to remain simple. If more powerful loadbalancing is required, dedicated hardware or software is recommended. Linux Virtual Server for example is often mentioned.

17.1.4 Options

- a <netmask>, --acl <netmask>** Add *netmask* to the ACL.
- C <file>, --config <file>** Load configuration from *file*.
- check-config** Test the configuration file (which may be set with **--config** or **-C**) for errors. dnsmdist will show the errors and exit with a non-zero exit-code when errors are found.
- c <address>, --client <address>** Operate as a client, connect to dnsmdist. This will read the dnsmdist configuration for the **controlSocket** statement and connect to it. When *address* (with an optional port number) is set, dnsmdist will connect to that instead.

- k <key>, --setkey <key>** When operating as a client (**-c, --client**), use *key* as shared secret to connect to dnssdist. This should be the same key that is used on the server (set with **setKey()**). Note that this will leak the key into your shell's history and into the systems running process list. Only available when dnssdist is compiled with libsodium support.
- e, --execute <command>** Connect to dnssdist and execute *command*.
- h, --help** Display a helpful message and exit.
- l, --local <address>** Bind to *address*, Supply as many addresses (using multiple **--local** statements) to listen on as required. Specify IPv4 as 0.0.0.0:53 and IPv6 as [::]:53.
- supervised** Run in foreground, but do not spawn a console. Use this switch to run dnssdist inside a supervisor (use with e.g. systemd and daemontools).
- disable-syslog** Disable logging to syslog. Use this when running inside a supervisor that handles logging (like systemd).
- u, --uid <uid>** Change the process user to *uid* after binding sockets. *uid* can be a name or number.
- g, --gid <gid>** Change the process group to *gid* after binding sockets. *gid* Can be a name or number.
- V, --version** Show the dnssdist version and exit.
- v, --verbose** Be verbose.

address are any number of downstream DNS servers, in the same syntax as used with **--local**. If the port is not specified, 53 is used.

17.1.5 Bugs

Right now, the TCP support has some rather arbitrary limits.

17.1.6 Resources

Website: <http://dnssdist.org>

CHANGELOG

18.1 1.4.0-alpha2

Released: 26th of April 2019

18.1.1 New Features

- Add DNS over HTTPS support based on libh2o [🔗](#) References: [#6911](#), [#7526](#), [pull request 7726](#)

18.1.2 Improvements

- Ignore Path MTU discovery on UDP server socket [🔗](#) References: [pull request 7410](#)
- Alternative solution to the unaligned accesses. [🔗](#) References: [pull request 7708](#)

18.1.3 Bug Fixes

- Exit when setting ciphers fails (GnuTLS) [🔗](#) References: [pull request 7718](#)

18.2 1.4.0-alpha1

Released: 12th of April 2019

18.2.1 New Features

- Make recursor & dnsdist communicate (ECS) ‘variable’ status [🔗](#) References: [pull request 7209](#)
- Add namespace and instance variable to carbon key (Gibheer) [🔗](#) References: [#6941](#), [#2362](#), [pull request 6959](#)
- Allow NoRecurse for use in dynamic blocks or Lua rules (phonedph1) [🔗](#) References: [pull request 7087](#)
- Expose secpoll status [🔗](#) References: [#7194](#), [pull request 7197](#)
- Add an optional ‘checkTimeout’ parameter to ‘newServer()’ [🔗](#) References: [#7236](#), [pull request 7323](#)
- Add a ‘rise’ parameter to ‘newServer()’ [🔗](#) References: [#7237](#), [pull request 7322](#)
- Add a ‘keepStaleData’ option to the packet cache [🔗](#) References: [#7239](#), [pull request 7310](#)
- Expose trailing data (Richard Gibson) [🔗](#) References: [#6897](#), [#6846](#), [pull request 6967](#)
- Add option to set interval between health checks (1848) [🔗](#) References: [pull request 7142](#)
- Add EDNS unknown version handling (Dmitry Alenichev) [🔗](#) References: [pull request 7406](#)

- `DNSNameSet` and `QNameSetRule` (Andrey) [🔗](#) References: [pull request 7537](#)
- Add support for encrypting ip addresses `#gdpr` [🔗](#) References: [#6242](#), [pull request 7481](#)
- Add `'setSyslogFacility()'` [🔗](#) References: [#5653](#), [pull request 7677](#)
- Add `'reloadAllCertificates()'` [🔗](#) References: [pull request 7676](#)

18.2.2 Improvements

- Fix warnings, mostly unused parameters, reported by `-wextra` [🔗](#) References: [pull request 7168](#)
- Add optional `uuid` column to `showServers()` [🔗](#) References: [pull request 7191](#)
- Configure `--enable-pdns-option --with-third-party-module` (Josh Soref) [🔗](#) References: [pull request 7026](#)
- Drop remaining capabilities after startup [🔗](#) References: [pull request 7138](#)
- More sandboxing using `systemd`'s features [🔗](#) References: [pull request 6634](#)
- Reduce `systemcall` usage in `Protobuf` logging [🔗](#) References: [pull request 7428](#)
- Resync `YaHTTP` code to `cmouse/yahttp@11be77a1fc4032` (Chris Hofstaedtler) [🔗](#) References: [pull request 7433](#)
- Pass empty response (Dmitry Alenichev) [🔗](#) References: [pull request 7431](#)
- Change the way `getRealMemusage()` works on linux (using `statm`) [🔗](#) References: [pull request 7502](#)
 - Prevent 0-ttl cache hits
[🔗](#) References: [#7534](#), [pull request 7585](#)
- Add `addDynBlockSMT()` support to `dynBlockRulesGroup` [🔗](#) References: [#7139](#), [pull request 7343](#)
- Add frontend response statistics (Matti Hiljanen) [🔗](#) References: [pull request 7578](#)
- Remove `addLuaAction` and `addLuaResponseAction` [🔗](#) References: [pull request 7670](#)
- Refactoring of the TCP stack [🔗](#) References: [#4814](#), [#7526](#), [pull request 7559](#)
- Prevent a conflict with `BADSIG` being clobbered [🔗](#) References: [#7556](#), [pull request 7692](#)
- Switch to the new `'newPacketCache()'` syntax for 1.4.0 [🔗](#) References: [pull request 7689](#)
- Move constants to proper namespace [🔗](#) References: [pull request 7678](#)
- Unify the management of `DNS/DNSCrypt/DoT` frontends [🔗](#) References: [pull request 7694](#)
 - Fix compiler warning about returning garbage (Adam Majer)
[🔗](#) References: [pull request 7167](#)

18.2.3 Bug Fixes

- Protect `GnuTLS` tickets key rotation with a read-write lock [🔗](#) References: [pull request 7256](#)
- Check that `SO_ATTACH_BPF` is defined before enabling `eBPF` [🔗](#) References: [pull request 7267](#)
- Fix off-by-one in `mvRule` counting [🔗](#) References: [pull request 7426](#)
- Don't convert `nsec` to `usec` if we need `nsec` [🔗](#) References: [pull request 7520](#)
- Fix `setRules()` [🔗](#) References: [pull request 7594](#)
- Handle `EAGAIN` in the `GnuTLS` DNS over TLS provider [🔗](#) References: [pull request 7560](#)
- Gracefully handle a null latency in the `webserver`'s `js` [🔗](#) References: [#7461](#), [pull request 7586](#)
- `EDNSOptionView` improvements [🔗](#) References: [pull request 7652](#)
- Honor `libcrypto` include path [🔗](#) References: [#7481](#), [pull request 7674](#)

18.3 1.3.3

Released: 8th of November 2018

18.3.1 New Features

- Add consistent hash builtin policy [🔗](#) References: [#6932](#), [pull request 6737](#), [pull request 6939](#)
- Add EDNSOptionRule [🔗](#) References: [pull request 6803](#)
- Add DSTPortRule (phonedph1) [🔗](#) References: [pull request 6813](#)
- Make getOutstanding usable from both lua and console (phonedph1) [🔗](#) References: [pull request 6826](#)
- Added :excludeRange and :includeRange methods to DynBPFFilter class (Reinier Schoof) [🔗](#) References: [pull request 6856](#)
- Add Prometheus stats support (Pavel Odintsov, Kai S) [🔗](#) References: [#6002](#), [#4947](#), [pull request 6901](#), [pull request 7089](#), [pull request 3935](#), [pull request 7007](#), [pull request 6343](#)
- Name threads in the programs [🔗](#) References: [#6974](#), [pull request 6997](#)
- Support the NXDomain action with dynamic blocks [🔗](#) References: [#6908](#), [pull request 7075](#)
- Add security polling [🔗](#) References: [pull request 7115](#)
- Add a PoolAvailableRule to easily add backup pools (Robin Geuze) [🔗](#) References: [pull request 7140](#)

18.3.2 Improvements

- Get rid of some allocs/copies in DNS parsing [🔗](#) References: [pull request 6831](#)
- Set a correct EDNS OPT RR for self-generated answers [🔗](#) References: [#4857](#), [#6348](#), [pull request 6847](#)
- Fix a sign-comparison warning in isEDNSOptionInOPT() [🔗](#) References: [pull request 6877](#)
- Add warning rates to DynBlockRulesGroup rules [🔗](#) References: [#6907](#), [pull request 6986](#)
- Add support for exporting a server id in protobuf [🔗](#) References: [#7004](#), [#6990](#), [pull request 7015](#)
- dnsmdist did not set TCP_NODELAY, causing needless latency [🔗](#) References: [pull request 7030](#)
- Add a setting to control the number of stored sessions [🔗](#) References: [pull request 7062](#)
- Wrap GnuTLS and OpenSSL pointers in smart pointers [🔗](#) References: [#7060](#), [pull request 7064](#)
- Add a 'creationOrder' field to rules [🔗](#) References: [#6909](#), [pull request 7078](#)
- Fix return-type detection with boost 1.69's tribool [🔗](#) References: [#7091](#), [pull request 7092](#)
- Fix format string issue on 32bits ARM [🔗](#) References: [#7096](#), [pull request 7104](#)
- Wrap TCP connection objects in smart pointers [🔗](#) References: [pull request 7108](#)
- Add the setConsoleOutputMaxMsgSize function [🔗](#) References: [#7084](#), [pull request 7109](#)
- Add the ability to update webserver credentials [🔗](#) References: [#7112](#), [pull request 7117](#)

18.3.3 Bug Fixes

- Display dynblocks' default action, None, as the global one ¶ References: [pull request 6835](#)
- Fix compilation when SO_REUSEPORT is not defined ¶ References: [pull request 6956](#)
- Release memory on DNS over TLS handshake failure ¶ References: [pull request 7060](#)
- Handle trailing data correctly when adding OPT or ECS info ¶ References: [#6896](#), [pull request 7165](#)

18.4 1.3.2

Released: 10th of July 2018

18.4.1 Bug Fixes

- Add missing include for PRId64, fix build on CentOS 6 / SLES 12 ¶ References: [pull request 6785](#)

18.5 1.3.1

Released: 10th of July 2018

18.5.1 New Features

- Add support for more than one TLS certificate ¶ References: [#6450](#), [pull request 6524](#)
- Add a negative ttl option to the packet cache ¶ References: [#6579](#), [pull request 6740](#)
- Add the ability to dump a summary of the cache content ¶ References: [pull request 6749](#)
- Add netmask-based {ex,in}clusions to DynblockRulesGroup ¶ References: [pull request 6760](#)
- Add DNSAction.NoOp to debug dynamic blocks ¶ References: [#6703](#), [pull request 6776](#)
- Add SetECSAction to set an arbitrary outgoing ecs value ¶ References: [#6404](#), [pull request 6734](#)
- Add support for rotating certificates and keys ¶ References: [pull request 6764](#)

18.5.2 Improvements

- Remove *thelog* and *thel* and replace this with a global *g_log* ¶ References: [#6357](#), [pull request 6358](#)
- Fix two small nits on the documentation ¶ References: [pull request 6422](#)
- Move the el6 dnssdist package to upstart ¶ References: [#6394](#), [pull request 6426](#)
- CLI option improvements (Chris Hofstaedtler) ¶ References: [#6433](#), [pull request 6435](#)
- Split pdns_enable_unit_tests (Chris Hofstaedtler) ¶ References: [pull request 6436](#)
- Re-do lua detection ¶ References: [#6423](#), [pull request 6470](#), [pull request 6457](#), [pull request 6445](#)
- Docs: fix missing ref in the dnssdist docs ¶ References: [pull request 6460](#)
- Be more permissive in wrandom tests, log values on failure ¶ References: [pull request 6502](#)
- Tests: avoid failure on not-so-optimal distribution ¶ References: [#6430](#), [pull request 6523](#)
- Add syntax to dns.proto to silence compilation warning. ¶ References: [pull request 6577](#)

- Fix warnings reported by gcc 8.1.0 [References: pull request 6590](#)
- Document setVerboseHealthchecks() [References: #6483, pull request 6592](#)
- Update dq.rst (phonedph1) [References: pull request 6615](#)
- Fix rpm scriptlets [References: pull request 6641](#)
- Don't copy uninitialized values of SuffixMatchTree [References: pull request 6637](#)
- Expose toString of various objects to Lua (Chris Hofstaedtl) [References: pull request 6684](#)
- Remove 'expired' states from MaxQPSIPRule [References: pull request 6674](#)
- Mark the remote member of DownstreamState as const [References: #6664, pull request 6688](#)
- Test the content of dynamic blocks using the API [References: #6706, pull request 6710](#)
- Default set "connection: close" header for web requests [References: #6532, pull request 6711](#)
- Update timedipsetrule.rst (phonedph1) [References: pull request 6717](#)
- Don't access the TCP buffer vector past its size [References: #6712, pull request 6716](#)
- Show droprate in API output [References: pull request 6563](#)
- Refuse console connection without a proper key set [References: #6683, #6709, pull request 6715](#)
- Use LRU to clean the MaxQPSIPRule's store [References: pull request 6726](#)
- Disable maybe uninitialized warnings with boost optional [References: pull request 6769](#)
- Luawrapper: report caught std::exception as lua_error [References: #6541, pull request 6658](#)
- Dnstap.rst: fix some editing errors (Chris Hofstaedtl) [References: pull request 6602](#)
- Allow known exception types to be converted to string [References: #6535, pull request 6541](#)

18.5.3 Bug Fixes

- Initialize the done variable in the rings' unit tests [References: pull request 6425](#)
- Reorder headers to fix OpenBSD build [References: pull request 6429](#)
- Restrict value range for weight parameter, avoid sum overflows dropping queries (Dan McCombs) [References: pull request 6448](#)
- Fix reconnection handling [References: pull request 6672](#)
- Dynamic blocks were being created with the wrong duration (David Freedman) [References: pull request 6706](#)
- Limit qps and latency to two decimals in the web view [References: #6442, pull request 6718](#)
- Check the flags to detect collisions in the packet cache [References: pull request 6747](#)
- Fix iterating over the results of exceed*() functions [References: pull request 6762](#)
- Fix duration false positive in the dynblock regression tests [References: pull request 6767](#)
- Implement NoneAction() [References: #6758, pull request 6775](#)
- Detect ECS collisions in the packet cache [References: #6747, pull request 6754](#)
- Fix an outstanding counter race when reusing states [References: pull request 6773](#)

18.6 1.3.0

Released: 30th of March 2018

18.6.1 New Features

- Add an optional *status* parameter to `Server:setAuto()`. ¶ References: pull request 5625
- Add `inClientStartup()` function. ¶ References: pull request 6072
- Add tag-based routing of queries. ¶ References: pull request 6037
- Add experimental *DNS-over-TLS* support. ¶ References: pull request 6117, pull request 6176, pull request 6189, pull request 6175, pull request 6177
- Add simple *dnstap* support (Justin Valentini, Chris Hofstaedtler). ¶ References: pull request 5201, pull request 6170
- Add experimental XPF support based on draft-bellis-dnsop-xpf-04. ¶ References: #5654, #5079, pull request 5594, pull request 6220
- Add `ERCodeRule()` to match on extended RCodes (Chris Hofstaedtler). ¶ References: pull request 6147
- Add `TempFailureCacheTTLAction()` (Chris Hofstaedtler). ¶ References: pull request 6003
- Add `DynBlockRulesGroup` to improve processing speed of the `maintenance()` function by reducing memory usage and not walking the ringbuffers multiple times. ¶ References: pull request 6391
- Add `console ACL` functions. ¶ References: #4654, pull request 6399
- Allow adding *EDNS Client Subnet information* to a query before looking in the cache. This allows serving ECS enabled answers from the cache when all servers in a pool are down. ¶ References: #6098, pull request 6400

18.6.2 Improvements

- Add cache sharding, `recvmmsg` and CPU pinning support. With these, the scalability of **dnssdist** is drastically improved. ¶ References: #5859, #5202, pull request 5860, pull request 5576
- Add burst option to `MaxQPSIPRule()` (42wim). ¶ References: pull request 5970
- Add Pools, `cacheHitResponseRules` to the API. ¶ References: pull request 6022
- Add a class option to health checks. ¶ References: #5748, pull request 5929
- Add UUIDs to rules, this allows tracking rules through modifications and moving them around. ¶ References: pull request 6030
- Apply `ResponseRules` to locally generated answers (Chris Hofstaedtler). ¶ References: #6182, pull request 6185
- Report `LuaAction()` and `LuaResponseAction()` failures in the log and send SERVFAIL instead of not answering the query (Chris Hofstaedtler). ¶ References: pull request 6283
- Unify global statistics accounting (Chris Hofstaedtler). ¶ References: pull request 6289
- Speed up the processing of large ring buffers. This change will make **dnssdist** more scalable with a large number of different clients. ¶ References: pull request 6350, pull request 6366
- Make custom `addLuaAction()` and `addLuaResponseAction()` callback's second return value optional. ¶ References: #6346, pull request 6363
- Add “server-up” metric count to Carbon Reporting (Lowell Mower). ¶ References: pull request 6327
- Add `xchacha20` support for *DNSCrypt*. ¶ References: pull request 6045, pull request 6382
- Scalability improvement: Add an option to use several source ports towards a backend. ¶ References: pull request 6317
- Add ‘?’ and ‘help’ for providing help() output on `dnssdist -c` (Kirill Ponomarev, Chris Hofstaedtler). ¶ References: #4845, pull request 6375, pull request 5866

- Replace the Lua mutex with a rw lock to limit contention. This improves the processing speed and parallelism of the policies. ¶ References: [pull request 6381](#), [pull request 6190](#)
- Ensure **dnscat** compiles on NetBSD (Tom Ivar Helbekkmo). ¶ References: [pull request 6146](#)
- Also log eBPF dynamic blocks, as regular dynamic block already are. ¶ References: [#5845](#), [pull request 5845](#)
- Ensure large numbers are shown correctly in the API. ¶ References: [#6211](#), [pull request 6401](#)
- Add option to `showRules()` to truncate the output length. ¶ References: [#5763](#), [pull request 6402](#)
- Fix several warnings reported by clang's analyzer and cppcheck, should lead to small performance increases. ¶ References: [pull request 6407](#)

18.6.3 Bug Fixes

- Handle SNMP alarms so we can reconnect to the master. ¶ References: [#5327](#), [pull request 5328](#)
- Fix signed/unsigned comparison warnings on ARM. ¶ References: [#5489](#), [pull request 5597](#)
- Keep trying if the first connection to the remote logger failed ¶ References: [pull request 5770](#)
- Fix escaping unusual DNS label octets in `DNSName` is off by one (Kees Monshouwer). ¶ References: [pull request 6018](#)
- Avoid assertion errors in `NewServer()` (Chris Hofstaedtler). ¶ References: [pull request 6403](#)

18.6.4 Removals

- Remove the `--daemon` option from **dnscat**. ¶ References: [#6329](#), [pull request 6394](#)

18.7 1.2.1

Released: 16th of February 2018

18.7.1 New Features

- Add configuration option to disable `IP_BIND_ADDRESS_NO_PORT` (Dan McCombs). ¶ References: [pull request 5880](#)

18.7.2 Improvements

- Handle bracketed IPv6 addresses without ports (Chris Hofstaedtler). ¶ References: [pull request 6057](#)

18.7.3 Bug Fixes

- Make `dnscat` dynamic truncate do right thing on TCP/IP. ¶ References: [pull request 5647](#)
- Add missing `QPSAction` ¶ References: [pull request 5686](#)
- Don't create a Remote Logger in client mode. ¶ References: [pull request 5847](#)
- Use `libsodium`'s `CFLAGS`, we might need them to find the includes. ¶ References: [pull request 5858](#)
- Keep the TCP connection open on cache hit, generated answers. ¶ References: [pull request 6012](#)
- Add the missing `<sys/time.h>` include to `mplexer.hh` for struct `timeval`. ¶ References: [pull request 6041](#)
- Sort the servers based on their 'order' after it has been set. ¶ References: [pull request 6043](#)

- Quiet unused variable warning on macOS (Chris Hofstaedtler). [🔗 References: pull request 6073](#)
- Fix the outstanding counter when an exception is raised. [🔗 References: #5652, pull request 6094](#)
- Do not connect the snmpAgent from a dnsmist client. [🔗 References: #6163, pull request 6164](#)

18.8 1.2.0

Released: 21st of August 2017

18.8.1 New Features

- Add an option to export CNAME records over protobuf. [🔗 References: #4709, pull request 4776](#)
- Add TCP management options from **RFC 7766 section 10**. [🔗 References: pull request 4611](#)
- Add an option to ‘mute’ UDP responses per bind. [🔗 References: #4527, pull request 4536](#)
- Save history to home-dir, only use CWD as a last resort. [🔗 References: #4562, pull request 4779](#)
- Add the `setRingBuffersSize()` directive to allows changing the ringbuffer size. [🔗 References: pull request 4898](#)
- Allow TTL alteration via Lua. [🔗 References: #4707, pull request 4787](#)
- Add `RDRule()` to match queries with the RD flag set. [🔗 References: pull request 4837](#)
- Add `setWHashedPerturbation()` for consistent whashed results. [🔗 References: pull request 4897](#)
- Add `tcpConnectTimeout` to `newServer()`. [🔗 References: pull request 4818](#)
- Add cache hit response rules. [🔗 References: #4708, pull request 5036, pull request 4788](#)
- Add *SNMP support*. [🔗 References: pull request 5123, pull request 5204, pull request 4989](#)
- Allow passing *DNSNames* as DNSRules. [🔗 References: pull request 5070](#)
- Add support for setting the server selection policy on a per pool basis (Robin Geuze). [🔗 References: pull request 5113](#)
- Add a `suffixMatch` parameter to `PacketCache:expungeByName()` (Robin Geuze). [🔗 References: pull request 5159](#)
- Add an option so the packet cache entries don’t age. [🔗 References: #5126, pull request 5136](#)
- Add `QNameRule()`. [🔗 References: pull request 5235](#)
- Add an optional action to `addDynBlocks()`. [🔗 References: pull request 5337](#)
- Add an optional interface parameter to `addLocal()/setLocal()`. [🔗 References: pull request 5344](#)
- Make a `truncate` action available to DynBlock and Lua. [🔗 References: pull request 5386](#)
- Implement a runtime changeable rule that matches IP address for a certain time called `TimedIPSetRule()`. [🔗 References: pull request 5336](#)
- Add support for returning several IPs to spoof from Lua. [🔗 References: pull request 5496](#)
- Add Lua bindings to be able to rotate DNSCrypt keys, see *DNSCrypt*. [🔗 References: #5420, #5507, pull request 5508, pull request 5490](#)
- Add the capability to set arbitrary tags in protobuf messages. [🔗 References: pull request 5577, pull request 5396](#)
- Add `setConsoleConnectionsLogging()`. [🔗 References: #5565, pull request 5581](#)

18.8.2 Improvements

- Merge the client and server nonces to prevent replay attacks. [🔗 References: pull request 4815](#)
- Store the computed shared key and reuse it for the response for DNSCrypt messages. [🔗 References: pull request 4813, pull request 4926](#)
- Add `setTCPUseSinglePipe()` to use a single TCP waiting queue. [🔗 References: pull request 4817](#)
- Add `sendSizeAndMsgWithTimeout` to send size and data in a single call and use it for TCP Fast Open towards backends. [🔗 References: #5494, pull request 4985, pull request 5501](#)
- Tune systemd unit-file for medium-sized installations (Winfried Angele). [🔗 References: pull request 4958](#)
- Add the possibility to fill a `NetmaskGroup` (using `NetmaskGroup:addMask()`) from `exceeds*` results. [🔗 References: pull request 5185](#)
- Add labels count to `StatNode`, only set the name once. [🔗 References: pull request 5353](#)
- `DNSName`: Check that both first two bits are set in compressed labels. [🔗 References: #4851, pull request 4852](#)
- Handle unreachable servers at startup, reconnect stale sockets [🔗 References: #4155, #4131, pull request 4285](#)
- Gracefully handle invalid addresses in `newServer()`. [🔗 References: #4471, pull request 4474](#)
- Use `IP_BIND_ADDRESS_NO_PORT` when available. [🔗 References: pull request 4786](#)
- Add an optional `seconds` parameter to `statNodeRespRing()`. [🔗 References: #4775, #4660, pull request 4780](#)
- Report a more specific lua version and report luajit in `--version`. [🔗 References: pull request 4910](#)
- Prevent issues by unshadowing variables. [🔗 References: pull request 5056](#)
- Register `DNSName::chopOff(@plzz)`. [🔗 References: pull request 4920](#)
- Make `includeDirectory()` work sorted (Robin Geuze). [🔗 References: #5053, pull request 5171, pull request 5150](#)
- Allow embedded NULs in strings received from Lua. [🔗 References: pull request 5147](#)
- Cleanup closed TCP downstream connections. [🔗 References: pull request 5163](#)
- Improve reporting of C++ exceptions that bubble up via Lua. [🔗 References: pull request 5230](#)
- Add better logging on queries that get dropped, timed out or received. [🔗 References: pull request 5253](#)
- Print useful messages when query and response actions are mixed. [🔗 References: pull request 5342](#)
- Add `DNSRule::toString()` and add virtual destructors to `DNSRule`, `DNSAction` and `DNSResponseAction` so the destructors of derived classes are run even when deleted via the base type. [🔗 References: pull request 5497](#)
- Don't use square brackets for IPv6 in Carbon metrics. [🔗 References: #5538, pull request 5579](#)

18.8.3 Bug Fixes

- Unified `-k` and `setKey()` behaviour for client and server mode now. [🔗 References: pull request 5199](#)
- Refactor `SuffixMatchNode` using a `SuffixMatchTree`. [🔗 References: #4761, pull request 4950](#)
- Get rid of `std::move()` calls preventing copy elision. [🔗 References: pull request 5359](#)
- Send an HTTP 404 on unknown API paths. [🔗 References: pull request 5089](#)
- `LuaWrapper`: Use the correct index when storing a function. [🔗 References: pull request 4775](#)
- Send a latency of 0 over carbon, null over API for down servers. [🔗 References: #4689, pull request 4785](#)

- Fix negative port detection for IPv6 addresses on 32-bit. [🔗 References: pull request 4911](#)
- Fix crashed on SmartOS/Illumos (Roman Dayneko). [🔗 References: #4579, pull request 4877](#)
- Change `truncateTC` to defaulting to off, having it enabled by default causes an compatibility with **RFC 6891** (Robin Geuze). [🔗 References: #4857, pull request 4859](#)
- Don't cache answers without any TTL (like SERVFAIL). [🔗 References: #4983, pull request 5037, pull request 4987](#)
- Fix destination port reporting on “any” binds. [🔗 References: pull request 5194](#)
- Correctly truncate EDNS Client Subnetmasks. [🔗 References: pull request 5320](#)
- Fix `RecordsTypeCountRule()`'s handling of the # of records in a section. [🔗 References: #5365, pull request 5369](#)
- Change stats functions to always return lowercase names (Robin Geuze). [🔗 References: #5287, pull request 5383](#)
- Only use TCP Fast Open when supported and prevent compiler warnings. [🔗 References: pull request 5449, pull request 5454](#)
- Skip timeouts on the response latency graph. [🔗 References: #5559, pull request 5563](#)
- Copy the DNS header before encrypting it in place. [🔗 References: #5566, pull request 5580](#)

18.8.4 Removals

- Remove `BlockFilter`. [🔗 References: #5513, pull request 5514](#)
- Deprecate syntactic sugar functions. [🔗 References: #5069, pull request 5526](#)

18.8.5 misc

- Fix potential pointer wrap-around on 32 bits. [🔗 References: pull request 5630](#)
- Make the API available with an API key only. [🔗 References: pull request 5631](#)

18.9 1.1.0

Released December 29th 2016

Changes since 1.1.0-beta2:

18.9.1 Improvements

- [#4783](#): Add `-latomic` on powerpc
- [#4812](#): Handle header-only responses, handle Refused as Servfail in the cache

18.9.2 Bug fixes

- [#4762](#): `SuffixMatchNode`: Fix an insertion issue for an existing node
- [#4772](#): Fix `dnssdist` initscript config check

18.10 1.1.0-beta2

Released December 14th 2016

Changes since 1.1.0-beta1:

18.10.1 New features

- #4518: Fix dynblocks over TCP, allow refusing dyn blocked queries
- #4519: Allow altering the ECS behavior via rules and Lua
- #4535: Add `DNSQuestion:getDO()`
- #4653: `getStatisticsCounters()` to access counters from Lua
- #4657: Add `includeDirectory(dir)`
- #4658: Allow editing the ACL via the API
- #4702: Add `setUDPTimeout(n)`
- #4726: Add an option to return `ServFail` when no server is available
- #4748: Add `setCacheCleaningPercentage()`

18.10.2 Improvements

- #4533: Fix building with clang on OS X and FreeBSD
- #4537: Replace luawrapper's `std::forward/std::make_tuple` combo with `std::forward_as_tuple` (Sangwhan "fish" Moon)
- #4596: Change the default max number of queued TCP conns to 1000
- #4632: Improve dnscat error message on a common typo/config mistake
- #4694: Don't use a `const_iterator` for erasing (fix compilation with some versions of gcc)
- #4715: Specify that `dnsmesssage.proto` uses protobuf version 2
- #4765: Some service improvements

18.10.3 Bug fixes

- #4425: Fix a protobuf regression (requestor/responder mix-up) caused by a94673e
- #4541: Fix insertion issues in `SuffixMatchTree`, move it to `dnsname.hh`
- #4553: Flush output in single command client mode
- #4578: Fix destination address reporting
- #4640: Don't exit dnscat on an exception in maintenance
- #4721: Handle exceptions in the UDP responder thread
- #4734: Add the TCP socket to the map only if the connection succeeds. Closes #4733
- #4742: Decrement the queued TCP conn count if writing to the pipe fails
- #4743: Ignore `newBPFFilter()` and `newDynBPFFilter()` in client mode
- #4753: Fix FD leak on TCP connection failure, handle TCP worker creation failure
- #4764: Prevent race while creating new TCP worker threads

18.11 1.1.0-beta1

Released September 1st 2016

Changes since 1.0.0:

18.11.1 New features

- #3762 Teeaction: send copy of query to second nameserver, sponge responses
- #3876 Add `showResponseRules()`, `{mv, rm, top}ResponseRule()`
- #3936 Filter on opcode, records count/type, trailing data
- #3975 Make dnsmdist {A,I}XFR aware, document possible issues
- #4006 Add eBPF source address and qname/qtype filtering
- #4008 Node infrastructure for querying recent traffic
- #4042 Add server-side TCP Fast Open support
- #4050 Add `clearRules()` and `setRules()`
- #4114 Add `QNameLabelsCountRule()` and `QNameWireLengthRule()`
- #4116 Added `src` boolean to `NetmaskGroupRule` to match destination address (Reinier Schoof)
- #4175 Implemented query counting (Reinier Schoof)
- #4244 Add a `setCD` parameter to set `cd=1` on health check queries
- #4284 Add `RCodeRule()`, Allow, Delay and Drop response actions
- #4305 Add an optional Lua callback for altering a Protobuf message
- #4309 Add `showTCPStats` function (RobinGeuze)
- #4329 Add options to `LogAction()` so it can append (instead of truncate) (Duane Wessels)

18.11.2 Improvements

- #3714 Add documentation links to `dnsmdist.service` (Ruben Kerkhof)
- #3754 Allow the use of custom headers in the web server
- #3826 Implement a 'quiet' mode for `SuffixMatchNodeRule()`
- #3836 Log the content of webserver's exceptions
- #3858 Only log YaHTTP's parser exceptions in verbose mode
- #3877 Increase max FDs in systemd unit, warn if clearly too low
- #4019 Add an optional `addECS` option to `TeeAction()`
- #4029 Add version and feature information to version output
- #4079 Return an error on `RemoteLog{,Response}Action()` w/o protobuf
- #4246 API now sends pools as a JSON array instead of a string
- #4302 Add `help()` and `showVersion()`
- #4286 Add response rules to the API and Web status page
- #4068 Display the dyn eBPF filters stats in the web interface

18.11.3 Bug fixes

- #3755 Fix `RegexRule` example in `dnstestconf.lua`
- #3773 Stop copying the HTTP request headers to the response
- #3837 Remove dnstest service file on trusty
- #3840 Catch `WrongTypeException` in client mode
- #3906 Keep the servers ordered inside pools
- #3988 Fix `grepq()` output in the README
- #3992 Fix some typos in the AXFR/IXFR documentation
- #3995 Fix comparison between signed and unsigned integer
- #4049 Fix dnstest rpm building script #4048 (Daniel Stirnimann)
- #4065 Include `editline/readline.h` instead of `readline.h/history.h`
- #4067 Disable eBPF support when `BPF_FUNC_tail_call` is not found
- #4069 Fix a buffer overflow when displaying an `OpcodeRule`
- #4101 Fix `$` expansion in `build-dnstest-rpm`
- #4198 `newServer` setting `maxCheckFailures` makes no sense (stutiredboy)
- #4205 Prevent the use of “any” addresses for downstream server
- #4220 Don't log an error when parsing an invalid UDP query
- #4348 Fix invalid outstanding count for {A,I}XFR over TCP
- #4365 Reset `origFD` asap to keep the outstanding count correct
- #4375 `Tuple` requires `make_tuple` to initialize
- #4380 Fix compilation with clang when eBPF support is enabled

18.12 1.0.0

Released April 21st 2016

Changes since 1.0.0-beta1:

18.12.1 Improvements

- #3700 Create user from the RPM package to drop privs
- #3712 Make check should run `testrunner`
- #3713 Remove `contrib/dnstest.service` (Ruben Kerkhof)
- #3722 Use `LT_INIT` and disable static objects (Ruben Kerkhof)
- #3724 Include `PDNS_CHECK_OS` in `configure` (Christian Hofstaedtler)
- #3728 Document `libedit` Ctrl-R workaround for CentOS 6
- #3730 Make `topBandwidth()` behave like other `top*` functions
- #3731 Clarify a bit the documentation of load-balancing policies

18.12.2 Bug fixes

- #3711 Building rpm needs systemd headers (Ruben Kerkhof)
- #3736 Add missing Lua binding for NetmaskGroupRule()
- #3739 Drop privileges after daemonizing and writing our pid

18.13 1.0.0-beta1

Released April 14th 2016

Changes since 1.0.0-alpha2:

18.13.1 New features

- Per-pool packet cache
- Some actions do not stop the processing anymore when they match, allowing more complex setups: Delay, Disable Validation, Log, MacAddr, No Recurse and of course None
- The new RE2Rule() is available, using the RE2 regular expression library to match queries, in addition to the existing POSIX-based RegexRule()
- SpoofAction() now supports multiple A and AAAA records
- Remote logging of questions and answers via Protocol Buffer

18.13.2 Improvements

- #3405 Add health check logging, maxCheckFailures to backend
- #3412 Check config
- #3440 Client operation improvements
- #3466 Add dq binding for skipping packet cache in LuaAction (Jan Broer)
- #3499 Add support for multiple carbon servers
- #3504 Allow accessing the API with an optional API key
- #3556 Add an option to limit the number of queued TCP connections
- #3578 Add a disable-syslog option
- #3608 Export cache stats to carbon
- #3622 Display the ACL content on startup
- #3627 Remove ECS option from response's OPT RR when necessary
- #3633 Count "TTL too short" cache events
- #3677 systemd-notify support

18.13.3 Bug fixes

- #3388 Lock the Lua context before executing a LuaAction
- #3433 Check that the answer matches the initial query
- #3461 Fix crash when calling rmServer() with an invalid index
- #3550,#3551 Fix build failure on FreeBSD (Ruben Kerkhof)

- #3594 Prevent EOF error for empty console response w/o sodium
- #3634 Prevent dangling TCP fd in case setupTCPDownstream() fails
- #3641 Under threshold, QPS action should return None, not Allow
- #3658 Fix a race condition in MaxQPSIPRule

18.14 1.0.0-alpha2

Released February 5th 2016

Changes since 1.0.0-alpha1:

18.14.1 New features

- Lua functions now receive a `DNSQuestion dq` object instead of several parameters. This adds a greater compatibility with PowerDNS and allows adding more parameters without breaking the API (#3198)
- Added a `source` option to `newServer()` to specify the local address or interface used to contact a downstream server (#3138)
- CNAME and IPv6-only support have been added to spoofed responses (#3064)
- `grepq()` can be used to search for slow queries, along with `topSlow()`
- New Lua functions: `addDomainCNAMEspooF()`, `AllowAction()` by @bearggg, `exceedQRate()`, `MacAddrAction()`, `makeRule()`, `NotRule()`, `OrRule()`, `QClassRule()`, `RCodeAction()`, `SpoofCNAMEAction()`, `SuffixMatchNodeRule()`, `TCPRule()`, `topSlow()`
- NetmaskGroup support have been added in Lua (#3144)
- Added `MacAddrAction()` to add the source MAC address to the forwarded query (#3313)

18.14.2 Bug fixes

- An issue in `DelayPipe` could make dnsmdist crash at startup
- `downstream-timeouts` metric was not always updated
- `truncateTC` was improperly updating the response length (#3126)
- DNSCrypt responses larger than queries were improperly truncated
- An issue prevented info message from being displayed in non-verbose mode, fixed by Jan Broer
- Reinstating an expired Dynamic Rule was not correctly logged (#3323)
- Initialized counters in the TCP client thread might have cause FD and memory leak, reported by Martin Pels (#3300)
- We now drop queries containing no question (`qdcount == 0`) (#3290)
- Outstanding TCP queries count was not always correct (#3288)
- A locking issue in `exceedRespGen()` might have caused crashes (#3277)
- Useless sockets were created in client mode (#3257)
- `addAnyTCRule()` was generating TC=1 responses even over TCP (#3251)

18.14.3 Web interface

- Cleanup of the HTML by Sander Hoentjen
- Fixed an XSS reported by @janeczku (#3217)
- Removed remote images
- Set the charset to UTF-8, added some security-related and CORS HTTP headers
- Added server latency by Jan Broer (#3201)
- Switched to official minified versions of JS scripts, by Sander Hoentjen (#3317)
- Don't log unauthenticated HTTP request as an authentication failure

18.14.4 Various documentation updates and minor cleanups:

- Added documentation for Advanced DNS Protection features (Dynamic rules, maintenance ())
- Make `topBandwidth ()` default to the top 10 clients
- Replaced `readline` with `libedit`
- Added GPL2 License (#3200)
- Added incbin License (#3269)
- Updated completion rules
- Removed wrong option `--daemon-no` by Stefan Schmidt

18.15 1.0.0-alpha1

Released December 24th 2015

Initial release

UPGRADE GUIDE

19.1 1.3.x to 1.4.0

`addLuaAction()` and `addLuaResponseAction()` have been removed. Instead, use `addAction()` with a `LuaAction()`, or `addResponseAction()` with a `LuaResponseAction()`.

`newPacketCache()` now takes an optional table as its second argument, instead of several optional parameters.

Lua's constants for DNS response codes and QTypes have been moved from the 'dnstap' prefix to, respectively, the 'DNSQType' and 'DNSRCode' prefix.

To improve security, all ambient capabilities are now dropped after the startup phase, which might prevent launching the webserver on a privileged port at run-time, or impact some custom Lua code. In addition, systemd's sandboxing features are now determined at compile-time, resulting in more restrictions on recent distributions. See pull requests 7138 and 6634 for more information.

If you are compiling dnstap, note that several `./configure` options have been renamed to provide a more consistent experience. Features that depend on an external component have been prefixed with '-with-' while internal features use '-enable-'. This led to the following changes:

- `--enable-fstrm` to `--enable-dnstap`
- `--enable-gnutls` to `--with-gnutls`
- `--enable-libsodium` to `--with-libsodium`
- `--enable-libssl` to `--with-libssl`
- `--enable-re2` to `--with-re2`

19.2 1.3.2 to 1.3.3

When upgrading from a package before 1.3.3, on CentOS 6 and RHEL 6, dnstap will be stopped instead of restarted.

19.3 1.2.x to 1.3.x

In version 1.3.0, these things have changed.

The *Working with the dnstap Console* has an ACL now, which is set to {"127.0.0.0/8", ":::1/128"} by default. Add the appropriate `setConsoleACL()` and `addConsoleACL()` statements to the configuration file.

The `--daemon` option is removed from the `dnstap` binary, meaning that `dnstap` will not fork to the background anymore. Hence, it can only be run on the foreground or under a supervisor like systemd, supervisord and daemon (8).

Due to changes in the architecture of **dnsmist**, several of the shortcut rules have been removed after deprecating them in 1.2.0. All removed functions have their equivalent *addAction()* listed. Please check the configuration for these statements (or use `dnsmist --check-config`) and update where needed. This removal affects these functions:

- *addAnyTCRule()*
- *addDelay()*
- *addDisableValidationRule()*
- *addDomainBlock()*
- *addDomainCNAMESpoof()*
- *addDomainSpoof()*
- *addNoRecurseRule()*
- *addPoolRule()*
- *addQPSLimit()*
- *addQPSPoolRule()*

19.4 1.1.0 to 1.2.0

In 1.2.0, several configuration options have been changed:

As the amount of possible settings for listen sockets is growing, all listen-related options must now be passed as a table as the second argument to both *addLocal()* and *setLocal()*. See the function's reference for more information.

The `BlockFilter` function is removed, as *addRule()* combined with a *DropAction()* can do the same.

SECURITY ADVISORIES

All security advisories for the DNSDist are listed here.

20.1 PowerDNS Security Advisory 2017-01 for dnsmdist: Crafted backend responses can cause a denial of service

- CVE: CVE-2016-7069
- Date: 2017-08-21
- Credit: Guido Vranken
- Affects: dnsmdist up to and including 1.2.0 on 32-bit systems
- Not affected: dnsmdist 1.2.0, dnsmdist on 64-bit (all versions)
- Severity: Low
- Impact: Degraded service or Denial of service
- Exploit: This issue can be triggered by sending specially crafted response packets from a backend
- Risk of system compromise: No
- Solution: Upgrade to a non-affected version
- Workaround: Disable EDNS Client Subnet addition

An issue has been found in dnsmdist in the way EDNS0 OPT records are handled when parsing responses from a backend. When dnsmdist is configured to add EDNS Client Subnet to a query, the response may contain an EDNS0 OPT record that has to be removed before forwarding the response to the initial client. On a 32-bit system, the pointer arithmetic used when parsing the received response to remove that record might trigger an undefined behavior leading to a crash.

dnsmdist up to and including 1.1.0 is affected on 32-bit systems. dnsmdist 1.2.0 is not affected, dnsmdist on 64-bit systems is not affected.

For those unable to upgrade to a new version, a minimal patch is [available for 1.1.0](#)

We would like to thank Guido Vranken for finding and subsequently reporting this issue.

20.2 PowerDNS Security Advisory 2017-02 for dnsmdist: Alteration of ACLs via API authentication bypass

- CVE: CVE-2017-7557
- Date: 2017-08-21
- Credit: Nixu

- Affects: dnssdist 1.1.0
- Not affected: dnssdist 1.0.0, 1.2.0
- Severity: Low
- Impact: Access restriction bypass
- Exploit: This issue can be triggered by tricking an authenticated user into visiting a crafted website
- Risk of system compromise: No
- Solution: Upgrade to a non-affected version
- Workaround: Keep the API read-only (default) via `setAPIWritable(false)`

An issue has been found in dnssdist 1.1.0, in the API authentication mechanism. API methods should only be available to a user authenticated via an X-API-Key HTTP header, and not to a user authenticated on the webserver via Basic Authentication, but it was discovered by Nixu during a source code audit that dnssdist 1.1.0 allows access to all API methods to both kind of users.

In the default configuration, the API does not provide access to more information than the webserver does, and therefore this issue has no security implication. However if the API is allowed to make configuration changes, via the `setAPIWritable(true)` option, this allows a remote unauthenticated user to trick an authenticated user into editing dnssdist's ACLs by making him visit a crafted website containing a Cross-Site Request Forgery.

For those unable to upgrade to a new version, a minimal patch is [available for 1.1.0](#)

20.3 PowerDNS Security Advisory for dnssdist 2018-08: Record smuggling when adding ECS or XPF

- CVE: CVE-2018-14663
- Date: November 8th 2018
- Affects: PowerDNS DNSDist up to and including 1.3.2
- Not affected: 1.3.3
- Severity: Low
- Impact: Insufficient validation
- Exploit: This problem can be triggered via crafted queries
- Risk of system compromise: No
- Solution: Upgrade to a non-affected version

An issue has been found in PowerDNS DNSDist allowing a remote attacker to craft a DNS query with trailing data such that the addition of a record by dnssdist, for example an OPT record when adding EDNS Client Subnet, might result in the trailing data being smuggled to the backend as a valid record while not seen by dnssdist. This is an issue when dnssdist is deployed as a DNS Firewall and used to filter some records that should not be received by the backend. This issue occurs only when either the 'useClientSubnet' or the experimental 'addXPF' parameters are used when declaring a new backend.

This issue has been assigned CVE-2018-14663 by Red Hat.

PowerDNS DNSDist up to and including 1.3.2 is affected.

We would like to thank Richard Gibson for finding and subsequently reporting this issue.

GLOSSARY

ACL Access Control List

Open Resolver A recursive DNS server available for many hosts on the internet. Usually without adequate rate-limiting, allowing it to be used in reflection attacks.

QPS Queries Per Second

HTTP ROUTING TABLE

/api

GET /api/v1/servers/localhost, 54

GET /api/v1/servers/localhost/config,
54

GET /api/v1/servers/localhost/config/allow-from,
54

GET /api/v1/servers/localhost/statistics,
54

PUT /api/v1/servers/localhost/config/allow-from,
55

/jsonstat

GET /jsonstat, 49

/metrics

GET /metrics, 51

A

ACL, **145**
 addACL () (*built-in function*), **90**
 addAction () (*built-in function*), **15**
 addAnyTCRule () (*built-in function*), **12**
 addBPFFilterDynBlocks () (*built-in function*), **113**
 addCacheHitResponseAction () (*built-in function*), **17**
 addConsoleACL () (*built-in function*), **89**
 addDelay () (*built-in function*), **12**
 addDisableValidationRule () (*built-in function*), **12**
 addDNSECryptBind () (*built-in function*), **115**
 addDOHLocal () (*built-in function*), **86**
 addDomainBlock () (*built-in function*), **12**
 addDomainCNAMESpoof () (*built-in function*), **13**
 addDomainSpoof () (*built-in function*), **13**
 addDynBlocks () (*built-in function*), **99**
 addLocal () (*built-in function*), **86**
 addLuaAction () (*built-in function*), **13**
 addLuaResponseAction () (*built-in function*), **14**
 addNoRecurseRule () (*built-in function*), **14**
 addPool () (*built-in function*), **94**
 addPoolRule () (*built-in function*), **14**
 addQPSLimit () (*built-in function*), **14**
 addQPSPoolRule () (*built-in function*), **15**
 addResponseAction () (*built-in function*), **16**
 addSelfAnsweredResponseAction () (*built-in function*), **18**
 addTLSLocal () (*built-in function*), **87**
 AllowAction () (*built-in function*), **23**
 AllowResponseAction () (*built-in function*), **23**
 AllRule () (*built-in function*), **19**
 AndRule () (*built-in function*), **22**

B

BPFFilter (*built-in class*), **114**
 BPFFilter:attachToAllBinds (), **114**
 BPFFilter:block (), **114**
 BPFFilter:blockQName (), **114**
 BPFFilter:getStats (), **114**
 BPFFilter:unblock (), **114**
 BPFFilter:unblockQName (), **114**

C

carbonServer () (*built-in function*), **121**
 clearDynBlocks () (*built-in function*), **99**
 clearRules () (*built-in function*), **15**
 ClientState (*built-in class*), **97**
 ClientState:attachFilter (), **97**
 ClientState:detachFilter (), **97**
 ClientState:toString (), **97**
 ComboAddress (*built-in class*), **107**
 ComboAddress:getPort (), **107**
 ComboAddress:ipdecrypt (), **107**
 ComboAddress:ipencrypt (), **107**
 ComboAddress:isIPv4 (), **107**
 ComboAddress:isIPv6 (), **107**
 ComboAddress:isMappedIPv4 (), **107**
 ComboAddress:mapToIPv4 (), **107**
 ComboAddress:toString (), **108**
 ComboAddress:toString (), **108**
 ComboAddress:toStringWithPort (), **108**
 ComboAddress:toStringWithPort (), **108**
 ComboAddress:truncate (), **108**
 controlSocket () (*built-in function*), **89**

D

DelayAction () (*built-in function*), **23**
 DelayResponseAction () (*built-in function*), **23**
 dh (*DNSQuestion attribute*), **110**
 DisableECSAction () (*built-in function*), **23**
 DisableValidationAction () (*built-in function*), **23**
 DNSECryptCert (*built-in class*), **116**
 DNSECryptCert:getClientMagic (), **116**
 DNSECryptCert:getEsVersion (), **116**
 DNSECryptCert:getMagic (), **116**
 DNSECryptCert:getProtocolMinorVersion (), **116**
 DNSECryptCert:getResolverPublicKey (), **116**
 DNSECryptCert:getSerial (), **116**
 DNSECryptCert:getSignature (), **116**
 DNSECryptCert:getTSEnd (), **116**
 DNSECryptCert:getTSStart (), **116**
 DNSECryptCertificatePair (*built-in class*), **116**
 DNSECryptCertificatePair:getCertificate (), **116**

DNSCryptCertificatePair:isActive(), 116
 DNSCryptContext (*built-in class*), 116
 DNSCryptContext:addNewCertificate(), 116
 DNSCryptContext:generateAndLoadInMemoryDNSCertificates(), 117
 DNSCryptContext:getCertificate(), 117
 DNSCryptContext:getCertificatePair(), 117
 DNSCryptContext:getCurrentCertificate(), 117
 DNSCryptContext:getOldCertificate(), 117
 DNSCryptContext:getProviderName(), 117
 DNSCryptContext:hasOldCertificate(), 117
 DNSCryptContext:loadNewCertificate(), 117
 DNSCryptContext:markActive(), 118
 DNSCryptContext:markInactive(), 118
 DNSCryptContext:printCertificates(), 118
 DNSCryptContext:removeInactiveCertificates(), 118
 DNSDistProtoBufMessage (*built-in class*), 118
 DNSDistProtoBufMessage:addResponseRR(), 118
 DNSDistProtoBufMessage:setBytes(), 119
 DNSDistProtoBufMessage:setEDNSSubnet(), 119
 DNSDistProtoBufMessage:setProtoBufResponse(), 119
 DNSDistProtoBufMessage:setQueryTime(), 119
 DNSDistProtoBufMessage:setQuestion(), 119
 DNSDistProtoBufMessage:setRequestor(), 119
 DNSDistProtoBufMessage:setRequestorFromSource(), 119
 DNSDistProtoBufMessage:setResponder(), 119
 DNSDistProtoBufMessage:setResponderFromSource(), 119
 DNSDistProtoBufMessage:setResponseCode(), 119
 DNSDistProtoBufMessage:setServerIdentity(), 119
 DNSDistProtoBufMessage:setTag(), 120
 DNSDistProtoBufMessage:setTagArray(), 120
 DNSDistProtoBufMessage:setTime(), 120
 DNSDistProtoBufMessage:toDebugString(), 120
 DNSHeader (*built-in class*), 112
 DNSHeader:getCD(), 112
 DNSHeader:getRD(), 112
 DNSHeader:setCD(), 113
 DNSHeader:setQR(), 112
 DNSHeader:setRD(), 112
 DNSHeader:setTC(), 112
 DNSName (*built-in class*), 109
 DNSName:inferRateOf(), 109
 DNSName:countLabels(), 109
 DNSName:isPartOf(), 109
 DNSName:toString(), 109
 DNSName:tostring(), 109
 DNSName:wirelength(), 109
 DNSNameSet (*built-in class*), 109
 DNSNameSet:add(), 109
 DNSNameSet:check(), 110
 DNSNameSet:clear(), 110
 DNSNameSet:delete(), 110
 DNSNameSet:empty(), 109
 DNSNameSet:size(), 110
 DNSNameSet:toString(), 110
 DNSQuestion (*built-in class*), 110
 DNSQuestion:getDO(), 111
 DNSQuestion:getEDNSOptions(), 111
 DNSQuestion:getTag(), 111
 DNSQuestion:getTagArray(), 111
 DNSQuestion:getTrailingData(), 111
 DNSQuestion:sendTrap(), 111
 DNSQuestion:setTag(), 111
 DNSQuestion:setTagArray(), 111
 DNSQuestion:setTrailingData(), 112
 DNSResponse (*built-in class*), 112
 DNSResponse:editTTLs(), 112
 DNSSyncRule (*built-in function*), 19
 DnstapLogAction() (*built-in function*), 23
 DnstapLogResponseAction() (*built-in function*), 23
 DnstapMessage (*built-in class*), 120
 DnstapMessage:setExtra(), 120
 DnstapMessage:toDebugString(), 120
 DOHFrontend (*built-in class*), 102
 DOHFrontend:reloadCertificates(), 103
 DropAction() (*built-in function*), 24
 DropResponseAction() (*built-in function*), 24
 DSTPortRule() (*built-in function*), 19
 DumpStats() (*built-in function*), 97
 DynBlockRulesGroup (*built-in class*), 101
 DynBlockRulesGroup() (*built-in function*), 100
 DynBlockRulesGroup:apply(), 102
 DynBlockRulesGroup:excludeRange(), 102
 DynBlockRulesGroup:includeRange(), 102
 DynBlockRulesGroup:setQTypeRate(), 101
 DynBlockRulesGroup:setQueryRate(), 101
 DynBlockRulesGroup:setRCodeRate(), 101
 DynBlockRulesGroup:setResponseByteRate(), 102
 DynBlockRulesGroup:toString(), 102
 DynBPFFilter (*built-in class*), 114
 DynBPFFilter:excludeRange(), 114
 DynBPFFilter:includeRange(), 114

DynBPFFilter:purgeExpired(), 114

E

ecsOverride (*DNSQuestion attribute*), 110
 ECSOverrideAction() (*built-in function*), 24
 ecsPrefixLength (*DNSQuestion attribute*), 110
 ECSPrefixLengthAction() (*built-in function*), 24
 EDNSOptionRule() (*built-in function*), 19
 EDNSOptionView (*built-in class*), 113
 EDNSOptionView:count(), 113
 EDNSOptionView:getValues(), 113
 EDNSVersionRule() (*built-in function*), 19
 ERCodeAction() (*built-in function*), 24
 ERCodeRule() (*built-in function*), 19
 exceedNXDOMAINs() (*built-in function*), 100
 exceedQRate() (*built-in function*), 100
 exceedQTypeRate() (*built-in function*), 100
 exceedRespByterate() (*built-in function*), 100
 exceedServFails() (*built-in function*), 100

G

generateDNSCryptCertificate() (*built-in function*), 115
 generateDNSCryptProviderKeys() (*built-in function*), 115
 getAction() (*built-in function*), 15
 getBind() (*built-in function*), 97
 getDNSCryptBind() (*built-in function*), 116
 getDOHFrontend() (*built-in function*), 97
 getPool() (*built-in function*), 94
 getPoolServers() (*built-in function*), 94
 getServer() (*built-in function*), 92
 getServers() (*built-in function*), 92
 getTLSContext() (*built-in function*), 97
 getTLSFrontend() (*built-in function*), 97
 grepq() (*built-in function*), 97

I

inClientStartup() (*built-in function*), 89
 includeDirectory() (*built-in function*), 85

J

JSON Objects
 ConfigSetting, 55
 Frontend, 56
 Pool, 56
 ResponseRule, 57
 Rule, 57
 Server, 57
 StatisticItem, 58

L

len (*DNSQuestion attribute*), 110
 localaddr (*DNSQuestion attribute*), 110
 LogAction() (*built-in function*), 24
 LuaAction() (*built-in function*), 24
 LuaResponseAction() (*built-in function*), 24

M

MacAddrAction() (*built-in function*), 24
 maintenance() (*built-in function*), 102
 makeKey() (*built-in function*), 89
 makeRule() (*built-in function*), 23
 MaxQPSIPRule() (*built-in function*), 20
 MaxQPSRule() (*built-in function*), 20
 muted (*ClientState attribute*), 97
 mvCacheHitResponseRule() (*built-in function*), 17
 mvResponseRule() (*built-in function*), 17
 mvRule() (*built-in function*), 16
 mvSelfAnsweredResponseRule() (*built-in function*), 18

N

name (*Server attribute*), 94
 NetmaskGroup (*built-in class*), 108
 NetmaskGroup:addMask(), 108
 NetmaskGroup:clear(), 108
 NetmaskGroup:match(), 108
 NetmaskGroup:size(), 108
 NetmaskGroupRule() (*built-in function*), 20
 newBPFFilter() (*built-in function*), 113
 newCA() (*built-in function*), 107
 newDNSName() (*built-in function*), 109
 newDNSNameSet() (*built-in function*), 109
 newDynBPFFilter() (*built-in function*), 113
 newFrameStreamTcpLogger() (*built-in function*), 120
 newFrameStreamUnixLogger() (*built-in function*), 120
 newNMG() (*built-in function*), 108
 newPacketCache() (*built-in function*), 95
 newRemoteLogger() (*built-in function*), 118
 newRuleAction() (*built-in function*), 16
 newServer() (*built-in function*), 91
 newServerPolicy() (*built-in function*), 60
 NoneAction() (*built-in function*), 25
 NoRecurseAction() (*built-in function*), 25
 NotRule() (*built-in function*), 22

O

opcode (*DNSQuestion attribute*), 110
 OpcodeRule() (*built-in function*), 20
 Open Resolver, 145
 order (*Server attribute*), 94
 OrRule() (*built-in function*), 22

P

PacketCache (*built-in class*), 96
 PacketCache:dump(), 96
 PacketCache:expunge(), 96
 PacketCache:expungeByName(), 96
 PacketCache:getStats(), 96
 PacketCache:isFull(), 96
 PacketCache:printStats(), 96

PacketCache:purgeExpired(), 96
 PacketCache:toString(), 96
 PoolAction() (built-in function), 25
 PoolAvailableRule() (built-in function), 19
 printDNSCryptProviderFingerprint()
 (built-in function), 115
 ProbaRule() (built-in function), 20

Q

qclass (DNSQuestion attribute), 110
 QClassRule() (built-in function), 20
 qname (DNSQuestion attribute), 110
 QNameLabelsCountRule() (built-in function), 21
 QNameRule() (built-in function), 20
 QNameSetRule() (built-in function), 21
 QNameWireLengthRule() (built-in function), 21
 QPS, 145
 QPSAction() (built-in function), 25
 QPSPoolAction() (built-in function), 25
 qtype (DNSQuestion attribute), 110
 QTypeRule() (built-in function), 21

R

rcode (DNSQuestion attribute), 110
 RCodeAction() (built-in function), 25
 RCodeRule() (built-in function), 21
 RDRule() (built-in function), 21
 RE2Rule() (built-in function), 22
 RecordsCountRule() (built-in function), 21
 RecordsTypeCountRule() (built-in function), 22
 RegexRule() (built-in function), 21
 registerDynBPFFilter() (built-in function),
 113
 reloadAllCertificates() (built-in function),
 85
 remoteaddr (DNSQuestion attribute), 110
 RemoteLogAction() (built-in function), 25
 RemoteLogResponseAction() (built-in func-
 tion), 25
 RFC
 RFC 1918, 7, 63
 RFC 3986#section-3.2.2, 85
 RFC 6891, 103, 134
 RFC 6891#section-6.2.5, 104
 RFC 7766#section-10, 132
 rmCacheHitResponseRule() (built-in function),
 18
 rmResponseRule() (built-in function), 17
 rmRule() (built-in function), 16
 rmSelfAnsweredResponseRule() (built-in
 function), 18
 rmServer() (built-in function), 93

S

sendCustomTrap() (built-in function), 121
 Server (built-in class), 93
 Server:addPool(), 93
 Server:getName(), 93

Server:getNameWithAddr(), 93
 Server:getOutstanding(), 93
 Server:isUp(), 93
 Server:rmPool(), 93
 Server:setAuto(), 93
 Server:setDown(), 93
 Server:setQPS(), 93
 Server:setUp(), 93
 ServerPolicy (built-in class), 60
 ServerPolicy.policy() (built-in function), 60
 ServerPool (built-in class), 94
 ServerPool:getCache(), 94
 ServerPool:getECS(), 94
 ServerPool:setCache(), 94
 ServerPool:setECS(), 94
 ServerPool:unsetCache(), 94
 setACL() (built-in function), 90
 setAddEDNSToSelfGeneratedResponses()
 (built-in function), 103
 setAPIWritable() (built-in function), 90
 setCacheCleaningDelay() (built-in function),
 122
 setCacheCleaningPercentage() (built-in
 function), 122
 setConsoleACL() (built-in function), 89
 setConsoleConnectionsLogging() (built-in
 function), 89
 setConsoleOutputMaxMsgSize() (built-in
 function), 89
 setDefaultBPFFilter() (built-in function), 113
 setDynBlocksAction() (built-in function), 100
 SetECSAction() (built-in function), 26
 setECSOverride() (built-in function), 90
 setECSSourcePrefixV4() (built-in function), 90
 setECSSourcePrefixV6() (built-in function), 91
 setKey() (built-in function), 89
 setLocal() (built-in function), 88
 setMaxTCPClientThreads() (built-in function),
 121
 setMaxTCPConnectionDuration() (built-in
 function), 121
 setMaxTCPConnectionsPerClient() (built-in
 function), 121
 setMaxTCPQueriesPerConnection() (built-in
 function), 121
 setMaxTCPQueuedConnections() (built-in
 function), 121
 setMaxUDPOutstanding() (built-in function),
 121
 setPayloadSizeOnSelfGeneratedAnswers()
 (built-in function), 104
 setPoolServerPolicy() (built-in function), 61
 setPoolServerPolicyLua() (built-in function),
 61
 setRingBuffersLockRetries() (built-in func-
 tion), 91
 setRingBuffersSize() (built-in function), 91
 setRoundRobinFailOnNoServer() (built-in

- function), 61
- setRules() (built-in function), 16
- setSecurityPollInterval() (built-in function), 104
- setSecurityPollSuffix() (built-in function), 104
- setServerPolicy() (built-in function), 61
- setServerPolicyLua() (built-in function), 61
- setServFailWhenNoServer() (built-in function), 61
- setStaleCacheEntriesTTL() (built-in function), 122
- setSyslogFacility() (built-in function), 86
- setTCPRecvTimeout() (built-in function), 122
- setTCPSendTimeout() (built-in function), 122
- setTCPUseSinglePipe() (built-in function), 122
- setUDPMultipleMessagesVectorSize() (built-in function), 122
- setUDPTimeout() (built-in function), 122
- setVerboseHealthChecks() (built-in function), 98
- setWebserverConfig() (built-in function), 90
- setWHashedPerturbation() (built-in function), 59
- showACL() (built-in function), 90
- showBinds() (built-in function), 98
- showCacheHitResponseRules() (built-in function), 18
- showConsoleACL() (built-in function), 89
- showDNSECryptBinds() (built-in function), 116
- showDOHFrontends() (built-in function), 98
- showDynBlocks() (built-in function), 100
- showPools() (built-in function), 94
- showPoolServerPolicy() (built-in function), 61
- showResponseLatency() (built-in function), 98
- showResponseRules() (built-in function), 17
- showRules() (built-in function), 16
- showSelfAnsweredResponseRules() (built-in function), 18
- showServers() (built-in function), 98
- showTCPStats() (built-in function), 98
- showTLSContexts() (built-in function), 98
- showVersion() (built-in function), 98
- size (DNSQuestion attribute), 110
- skipCache (DNSQuestion attribute), 111
- SkipCacheAction() (built-in function), 26
- snmpAgent() (built-in function), 121
- SNMPTrapAction() (built-in function), 26
- SNMPTrapResponseAction() (built-in function), 26
- SpoofAction() (built-in function), 26
- SpoofCNAMEAction() (built-in function), 26
- SuffixMatchNodeRule() (built-in function), 22
- T**
- TagAction() (built-in function), 26
- TagResponseAction() (built-in function), 26
- TagRule() (built-in function), 22
- TCAction() (built-in function), 27
- tcp (DNSQuestion attribute), 111
- TCPRule() (built-in function), 22
- TeeAction() (built-in function), 27
- TempFailureCacheTTLAction() (built-in function), 27
- testCrypto() (built-in function), 89
- TimedIPSetRule (built-in class), 65
- TimedIPSetRule() (built-in function), 65
- TimedIPSetRule:add(), 65
- TimedIPSetRule:cleanup(), 65
- TimedIPSetRule:clear(), 65
- TimedIPSetRule:slice(), 65
- TLSContext (built-in class), 103
- TLSContext:loadNewCertificatesAndKeys() (TLSFrontend method), 103
- TLSContext:loadTicketsKeys(), 103
- TLSContext:rotateTicketsKey(), 103
- TLSFrontend (built-in class), 103
- topBandwidth() (built-in function), 99
- topCacheHitResponseRule() (built-in function), 18
- topClients() (built-in function), 99
- topQueries() (built-in function), 99
- topResponseRule() (built-in function), 17
- topResponses() (built-in function), 99
- topRule() (built-in function), 16
- topSelfAnsweredResponseRule() (built-in function), 19
- topSlow() (built-in function), 99
- TrailingDataRule() (built-in function), 22
- U**
- unregisterDynBPFFilter() (built-in function), 114
- upStatus (Server attribute), 94
- useECS (DNSQuestion attribute), 111
- W**
- webserver() (built-in function), 89
- weight (Server attribute), 94